


Router Bits and Shank Tools



NAPGLADU

Delivering Productivity

3 Carbide Tipped Straight
and Form Router Bits



99 High Speed Steel and
Solid Carbide Router Bits



151 Insert Router Bits
and Knives



157 Leuco Diamond Tooling,
Inserts and Clamping



161 Dowel Drills, Hinge Boring
Bits and Accessories



171 Boring Tools



181 Twist Drills



197 Counterbores and
Countersinks



205 Conversions, Troubleshooting
and Indexes



Cutting Tool Engineering and Supply. NAP GLADU specializes in tooling – specifically cutting tools. We provide quality tools at affordable prices. At some point of the manufacturing process, production materials need to be cut, milled, shaped or profiled. With guidance from our Technical Experts, we can help determine the most cost-effective answer for all of your cutting needs. Our representatives can perform in-plant analysis of machines and the materials you are processing – and provide recommendations for increased productivity levels.

Regardless of the difficulty of the job, our Service Representatives can provide a solution that results in a quality tool at a good price. Exposure gained from nearly 40 years in the business has provided us with the knowledge to aid and improve overall production techniques and ultimately the finished product.

Visit NAP GLADU at www.napgladu.com to check out our monthly specials and to add your name to our mailing list. You can request helpful literature, find related links or view our comprehensive selection of tools. Our address, fax, and phone number are located on the website for your convenience, as well as a toll free number for Canadian and American customers – or contact our Sales Representatives at any time via email. If you have any questions or concerns, please contact our offices in Toronto or Calgary, or visit or showroom at our Toronto Head Office.



Router Bits and Shank Tools: NAP GLADU offers the industry's largest selection of premium grade carbide tipped router bits for trimming, sizing and profiling. We outfit everything from portable routers to multi-head CNC machines. To provide optimum performance and practical solutions for difficult to rout applications, we offer carbide tipped, solid carbide and high speed steel router bits.

Saw Blades: For ripping, cross cutting or sizing, NAP GLADU carries a wide variety of carbide tipped saw blades. The highest quality raw materials combined with state-of-the-art diamond grinding results in precision saw blades which offer superior cutting and durability. Our high speed steel blades are designed for both automatic and manual machines to cut most materials.

Knives: NAP GLADU has cutting knives for every application. From planer knives to lathe knives, we can custom manufacture the knives you require. Knives available include: Tera, Esta disposable, lathe, sticker, Oertli, planer, corrugated back, notched edge shaper, portable planer, super profiler, turnover, insert, circular and Eco Pro knives. Multiple grades are available, including M2 high speed steel, carbide tipped, stellite and solid carbide.


Bandsaw Blades: NAP GLADU carries a broad range of bandsaw blades including: carbon steel, high speed steel, carbide tipped, millband, pallet band and band knives. Each type of band is available in various widths, gauges, tooth styles, sets and pitches. Applications include metal cutting, woodworking, food processing, resawing, log sawing, plastic, rubber and foam cutting and pallet refurbishing. Contact our sales representatives to discuss your cutting application and determine the appropriate blade for your needs.

Profiling Services: Using sophisticated drafting equipment, our engineers can provide custom profiling of high speed steel, carbide tipped and solid carbide knives — done to your exact specifications. Tool profiles are created from wood samples or drawings using computer-aided drafting to the highest tolerances, ensuring an exact profile tool. NAP GLADU also offers a custom template making services if for those who grind their own knives.

Sharpening Services: NAP GLADU takes pride in offering you the best sharpening service available. Using only the most current technology and equipment available, certified technicians sharpen your saw blades, router bits, cutters, knives, hand tools and metal cutting saw blades to their original specifications.

Other Products and Services: In addition to the products mentioned above, NAP GLADU supplies the manufacturing industry with many other quality items and services. We invite you to come and visit our showroom and speak with our knowledgeable sales staff regarding any product you are interested in or cutting problem you may have.

Carbide Tipped Straight and Form Router Bits



Accessories	92-97
Adjustable Sets	59-60
Arbors	97
Ball Grooving	30
Beading (Convex)	31-33
Beading (Edge)	34-39
Bearings	94
Bevel Trim	22-23
Canoe	85
Chamfer	24
Corner Rounding	37-41
Countertop	72-74
Cove Bowl and Tray	28
Decorative Grooving, Solid Carbide	17
Decorative Plunging	40-44
Door Lip Assembly	50
Dovetail	26-27
Edge Forming	82-85
Face Frame	20
Face Inlay	20
Finger Grip	51-52
Glue Joint	64-65
Half Round True Bullnose	31-32
Handrail	69-71
Jointing Sets	66
Keyhole	79
Laminate Overhang	20
Miter Lock Joint	65
Mortise	21
Moulding	80-81, 86-90
Ogee Classical	42-48
Paneling Groover	48-50
Rabbeting	18-19
Rail and Stile	55-57
Raised Panel	61-64
Raised Panel (Vertical)	63-64
Roundnose	29
Slot Cutters	53-55
Straight	5-11
Straight with Bearing	12-14
Thumbnail	68
Tongue and Groove	58
Trimming, Solid Carbide	14-16
T-Slot Undercut	76-78
"V" "C" Panel Sets	58-59
V-Grooving	24

Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Single Flute Straight Router Bits



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
21400	1/16	1/4	1 7/8
21404	1/8	7/16	2 1/2
21406	5/32	7/16	2 3/4
21408	3/16	7/16	2 3/4
21412	1/4	1/2	3
21414	1/4	3/4	2 7/8
21418	1/4	1	3
21422	9/32	3/4	4 1/4
21428	5/16	1	2 7/8
21434	3/8	3/4	2 7/8
21436	3/8	1	2 7/8
21444	1/2	3/4	3 5/8
21445	1/2	1	2 7/8
21458	5/8	3/4	2 7/8
21468	3/4	3/4	2 7/8
21214	1/4	3/4	2 1/2
21218	1/4	1	2 1/2
21228	5/16	1	2 3/4
21236	3/8	1	2 1/2
21238	3/8	1 1/4	2 3/4
21245	1/2	1	2 1/2
21247	1/2	1 1/4	2 7/8
21249	1/2	1 1/2	3 1/8
21252	1/2	2	4 1/4
21256	9/16	1 1/4	2 7/8
21260	5/8	1 1/4	2 7/8

1/4" Shank

1/2" Shank

Series 21000

These bits are designed for higher feed rates in large production or general usage. They are suitable for normal ramp-in plunge cutting and routing in plywoods, chipboards and plastics as well as laminated material with stationary or portable routers.

Carbide Tipped Single Flute Straight Router Bits



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
21469SC	1/8	7/16	2
21470SC	5/32	7/16	2
21471SC	3/16	7/16	2
21472SC	7/32	3/8	2
21473SC	1/4	3/4	2
21474SC	1/4	1	2
21475SC	3 mm	11 mm	51 mm
21476SC	4 mm	11 mm	51 mm
21477SC	5 mm	11 mm	51 mm
21478SC	6 mm	19 mm	51 mm
21479SC	6 mm	25 mm	51 mm

For more solid carbide bits see pages 100-149

1/4" Shank

Series 2100SC

Solid carbide, single flute bits, designed to rout difficult to cut material which call for a small diameter. These are best suited for wood, wood composites and abrasive plastics.

Series 22000

These bits are ideal for routing plywoods, chipboards, plastics and laminated material with stationary or portable routers. Double flute bits provide a smoother finish than single flute bits, yet still maintain high feed rates. Available in 1/4", 1/2" and 3/4" shanks for versatility and strength. These bits are suitable for normal ramp-in plunging and routing operations. For faster plunging, see straight bits for plunging on page 10.




Carbide Tipped Double Flute Straight Router Bits - 1/4" Shank

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	22401	1/16	3/16	1 3/8
	22402	3/32	1/4	1 7/8
	22403	1/8	7/16	1 7/8
	22404	1/8	5/16	2
	22406	5/32	7/16	2 3/16
	22408	3/16	7/16	2
	22409	3/16	5/8	2
	22410	7/32	3/4	2 1/8
	22412	1/4	1/2	1 7/8
	22414	1/4	3/4	2
	22418	1/4	1	2 1/4
	22422	9/32	3/4	2
	22424	9/32	1	2 1/4
	22426	5/16	3/4	2
	22428	5/16	1	2 1/4
	22434	3/8	3/4	2
	22436	3/8	1	2 1/4
	22438	3/8	1 1/4	2 1/2
	22441	7/16	3/4	2
	22442	7/16	1	2 1/8
	22444	1/2	3/4	2
	22445	1/2	1	2 1/8
	22447	1/2	1 1/4	2 1/2
	22455	9/16	3/4	2 1/8
	22456	9/16	1	2 1/2
	22458	5/8	3/4	2
	22459	5/8	1	2 1/4
	22465	11/16	3/4	2
	22466	11/16	1	2 1/4
	22468	3/4	3/4	2
	22469	3/4	1	2 1/4
	22474	13/16	3/4	2
	22476	7/8	3/4	2
	22478	15/16	3/4	2
	22479	1	3/4	2



Series 22000SC

Solid carbide, double flute bits, designed to rout difficult to cut material which call for a small diameter. Best suited for use with rigid plastics, such as acrylic, PVC or nylon, thin laminated material and wood composites.



Solid Carbide Double Flute Straight Router Bits - 1/4" Shank

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	22480SC	5/32	7/16	2
	22481SC	3/16	7/16	2
	22482SC	3/16	1/2	2
	22483SC	7/32	1/4	2
	22484SC	1/4	1/2	2
	22485SC	1/4	3/4	2
	22486SC	1/4	3/4	2 1/2
	22487SC	1/4	1	2 1/2
	22488SC	3 mm	11 mm	51 mm
	22489SC	4 mm	11 mm	51 mm
	22490SC	5 mm	11 mm	51 mm
	22491SC	6 mm	19 mm	51 mm
	22492SC	6 mm	19 mm	63 mm
	22493SC	6 mm	25 mm	63 mm



For more solid carbide bits see pages 100-149

Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Straight Router Bits - 1/2" Shank					Series 22000
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	1/2" Shank Carbide tipped double flute straight router bits continued. 
	22210	15/64	3/4	2 1/2	
	22212	1/4	1/2	2	
	22214	1/4	3/4	2 1/2	
	22218	1/4	1	2 1/2	
	22226	5/16	3/4	2 1/2	
	22228	5/16	1	2 1/2	
	22234	3/8	3/4	2 1/2	
	22236	3/8	1	2 1/2	
	22238	3/8	1 1/4	2 3/4	
	22240	13/32	1	2 3/4	
	22242	7/16	1	2 5/8	
	22243	7/16	1 1/4	2 3/4	
	22244	31/64	1	2 5/8	
	22245	1/2	1	2 5/8	
	22247	1/2	1 1/4	2 7/8	
	22249	1/2	1 1/2	4 1/4	
	22250	1/2	1 1/2	4 3/16	
	22251	1/2	2	4	
	22252	1/2	2	4 1/4	
	22253	1/2	2 1/2	4 1/2	
	22254	17/32	1 1/4	2 7/8	
	22256	9/16	1	2 5/8	
	22257	9/16	1 1/4	2 7/8	
	22259	5/8	1	2 5/8	
	22260	5/8	1 1/4	2 7/8	
	22261	5/8	1 1/2	3	
	22262	5/8	2	3 5/8	
	22264	21/32	1 1/4	2 7/8	
	22267	11/16	1 1/4	2 7/8	
	22268	23/32	1 1/4	2 7/8	
	22269	3/4	1	2 5/8	
	22270	3/4	1 1/4	2 7/8	
	22271	3/4	1 1/2	3	
	22272	3/4	2	3 5/8	
	22273	25/32	1 1/4	2 7/8	
	22274	13/16	1	2 5/8	
	22275	13/16	1 1/4	2 7/8	
	22276	7/8	1	2 5/8	
	22277	7/8	1 1/4	2 7/8	
	22278	15/16	1 1/4	2 7/8	
	22279	1	3/4	2 7/8	
	22280	1	1	2 5/8	
	22281	1	1 1/4	2 7/8	
	22282	1	1 1/2	3	
	22283	1	2	3 5/8	
	22284	1 1/16	1 1/4	2 7/8	
	22285	1 1/8	1 1/4	2 7/8	
22287	1 3/16	1 1/4	2 7/8		
22288	1 1/4	1 1/4	2 7/8		
22290	1 3/8	1 1/4	2 7/8		
22291	1 1/2	1 1/4	2 7/8		
22293	1 5/8	1 1/4	2 7/8		
22294	1 3/4	1 1/4	2 7/8		
22295	1 7/8	1 1/4	2 7/8		
22296	2	1 1/4	2 7/8		

Series 22000

Carbide Tipped Double Flute Straight Router Bits - 3/4" Shank

Carbide tipped double flute straight router bits continued.



3/4" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
22870	3/4	1 1/4	3
22871	3/4	1 1/2	3 1/4
22872	3/4	1 5/8	4
22873	3/4	2	4
22874	3/4	2 1/8	4 1/2
22875	3/4	2 1/2	4 1/2
22876	3/4	2 5/8	5
22878	3/4	3	5 3/8
22879	1	1 1/2	3 1/4
22880	1	2	4 1/4
22881	1	2 1/8	4 1/4
22882	1	3	5 1/8



Series 22000L

Carbide Tipped Double Flute Straight Bits - Left Hand Rotation

Designed to cut while rotating in a counter-clockwise direction.



1/4" Shank

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
22418L	1/4	1	2 1/2
22226L	5/16	3/4	2 1/2
22228L	5/16	1	2 3/4
22236L	3/8	1	2 3/4
22243L	7/16	1 1/4	3
22247L	1/2	1 1/4	2 7/8
22249L	1/2	1 1/2	3
22252L	1/2	2	4 1/4
22257L	9/16	1 1/4	2 7/8
22260L	5/8	1 1/4	2 7/8
22270L	3/4	1 1/4	2 7/8
22272L	3/4	2	3 5/8
22275L	13/16	1 1/4	2 7/8
22277L	7/8	1 1/4	2 7/8
22281L	1	1 1/4	2 7/8
22873L	3/4	2	5
22875L	3/4	2 1/2	5
22876L	3/4	2 1/2	5 1/2



Carbide Tipped - Straight and Form Router Bits

Leuco Diamax Diamond Tipped Router Bit



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Shank Length	Overall Length
178898	1/2	1	1 3/8	2 3/4
178900	5/8	1	1 3/8	2 7/8
178902	3/4	1	1 3/4	3 3/8
178904	3/4	1 5/8	1 3/4	3 7/8

Series 129

Designed for jointing, rabbeting, grooving and sizing particleboard, MDF, plastics, laminated and veneered panel materials and hard or exotic woods. The large shear angle provides for long tool life and optimum quality of cut.

1/2" Shank

5/8" Shank

Carbide Tipped Double Flute Shear Cut Straight Bits




NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
23270	3/8	1	2 3/4
23272	1/2	1 1/4	2 7/8
23274	1/2	1 1/2	3 1/8
23276	1/2	2	4 1/4

Series 23000

A downcut shear angle of 3° produces a clean edge on the laminated surface when overhead routing veneered and laminated surfaces.

1/2" Shank



Series 20000

These bits are designed specifically for high feed rates for large production or general usage. Suitable for normal ramp-in plunge cutting and routing in plywoods, chipboards, plastics and laminated material with stationary or portable routers.



Metric Carbide Tipped Double Flute Straight Bits

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	20410	3 mm	5/16	1 9/16
	20412	4 mm	7/16	2
	20414	5 mm	7/16	2
	20416	6 mm	3/4	2
	20418	7 mm	3/4	2
	20420	8 mm	3/4	2
	20422	8 mm	1	2 1/4
	20424	9 mm	3/4	2
	20426	10 mm	3/4	2
	20428	11 mm	3/4	2
	20430	12 mm	3/4	2
	20432	13 mm	3/4	2
	20434	14 mm	3/4	2
	20436	15 mm	3/4	2
	20438	16 mm	3/4	2
	20440	16 mm	1 1/4	2 1/4
	20442	17 mm	3/4	2
	20444	18 mm	3/4	2
	20446	19 mm	3/4	2
	20448	20 mm	3/4	2
	20450	21 mm	3/4	2
	20452	22 mm	3/4	2
	20454	25 mm	3/4	2
1/2" Shank	20216	6 mm	3/4	2 1/2
	20218	8 mm	1	2 5/8
	20220	10 mm	1	2 1/2
	20222	10 mm	1 1/4	3
	20224	12 mm	1	2 5/8
	20226	12 mm	1 1/4	2 7/8
	20228	12 mm	1 1/2	3
	20230	12 mm	2	4 1/4
	20232	14 mm	1	2 5/8
	20236	16 mm	1	2 5/8
	20238	16 mm	1 1/4	2 7/8
	20240	16 mm	1 1/2	3 1/8
	20242	18 mm	1 1/4	2 7/8
	20244	19 mm	1	2 5/8
	20246	19 mm	1 1/4	2 7/8
	20248	19 mm	1 1/2	3 1/8
	20250	20 mm	1	2 5/8
	20252	20 mm	1 1/4	2 7/8
	20254	22 mm	1	2 5/8
	20256	25 mm	1 1/4	2 7/8
	20258	25 mm	1 1/2	3 1/8
	20260	27 mm	1 1/4	2 7/8
	20262	30 mm	1	2 5/8
	20264	35 mm	1	2 5/8
	20266	40 mm	1 1/4	2 7/8
	20268	51 mm	1 1/4	2 7/8



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Straight Bits for Plunging



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
22426A	5/16	3/4	2
22434A	3/8	3/4	2
22436A	3/8	1	2 1/4
22444A	1/2	3/4	2
22445A	1/2	1	2 1/8
22458A	5/8	3/4	2
22476A	7/8	3/4	2
22479A	1	3/4	2
22226A	5/16	3/4	2 1/2
22238A	3/8	1 1/4	3
22242A	7/16	1	2 3/4
22245A	1/2	1	2 5/8
22247A	1/2	1 1/4	2 7/8
22249A	1/2	1 1/2	3 1/8
22252A	1/2	2	4 1/4
22260A	5/8	1 1/4	2 7/8
22262A	5/8	2	3 3/4
22269A	3/4	1	2 5/8
22277A	7/8	1 1/4	2 7/8
22280A	1	1	2 5/8
22292A	1 5/8	1	2 5/8
22294A	1 3/4	1 1/4	2 7/8
22295A	1 7/8	1 1/4	2 7/8

1/4" Shank

1/2" Shank

Series 22000A

Designed with a special bottom carbide tip for faster straight-in plunging. Ideal for routing most man-made materials on stationary and portable routers.

Carbide Tipped Chipbreaker Bits



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
22247C	1/2	1 1/4	2 3/4
22249C	1/2	1 1/2	3
22252C	1/2	2	4
22253C	1/2	2 1/2	4 1/2
22869C	3/4	2	4

1/2" Shank

3/4" Shank


Series 22000C

Double flute chipbreakers are ideal for routing of hardwood and chipboard materials where high feed rates are desired. Each flute on the bit is ground so that the chip breakers overlap, resulting in a straight cut.


Series 23000		Carbide Tipped Staggered Tooth Straight Bits			
Designed for laminated, veneered or stacked material where high feed rates are essential. Staggered tooth bits provide the balance of a double flute bit with the aggressiveness and high feed rates available in a single flute bit.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	1/4" Shank	23400	1/4	1	2 1/4
	1/2" Shank	23200	3/8	1 1/2	3 1/8
		23201	1/2	1 1/2	3 1/8
		23204	1/2	2	4 1/4
		23206	1/2	2 1/8	4 1/4



Series 23000		Carbide Tipped Staggered Tooth Shear Bits			
An upcut/downcut shearing action produces chip free edges on the top and bottom of melamine or laminated material.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	1/2" Shank	23220	1/2	1 1/4	3 1/8
		23222	1/2	1 1/2	3
		23224	1/2	2	4 1/4
		23226	1/2	2 1/4	4 1/4
	3/4" Shank	23880	3/4	2	4



Series 23000		Carbide Tipped Compression Bits			
Designed with staggered shear cutting angles for fast chip removal at high feed rates in double sided melamine, laminated material and veneer. Carbide centre tip allows for plunging.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	1/2" Shank	23280	1/2	1 1/2	3 1/2
		23281	1/2	2	4
		23282	3/4	2	4 1/4
	3/4" Shank	23882		2	4 3/8



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Straight Bits with Upper Bearing Guide

Series 23000

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
23430	1/2	1/8	1 3/4	A
23432	1/2	1/4	1 7/8	A
23434	1/2	3/4	2 1/4	A
23436	1/2	1	2 1/2	A
23438	1/2	1 1/4	2 3/4	A
23440	5/8	1/4	1 3/4	B
23441	5/8	1/2	2 1/4	B
23442	5/8	3/4	2 1/2	B
23443	5/8	1	2 1/2	B
23444	3/4	3/4	2 3/8	C
23446	3/4	1	2 5/8	C
23244	3/4	1	3	E
23245	3/4	1 1/4	3	E
23246	3/4	1 1/2	3 1/4	E
23248	3/4	2	3 5/8	E
23250	1	1 3/4	3 3/4	F
23251	1 1/8	1	3	G
23252	1 1/8	1 1/2	3 5/8	G
23254	1 1/4	1 3/4	3 1/4	H
23256	1 1/2	1 3/4	3 1/4	I


1/4" Shank

This bit has a straight carbide tip with an upper ball bearing which creates mar free template work.

1/2" Shank

Replacement
Parts - pg 92

This bit has a straight carbide tip with an upper ball bearing which creates mar free template work.



Carbide Tipped Bottom Cleaning Straight Bits							Series 23000	
	NAP GLADU Tool Number	A	Cutting Diameter	B	Cutting Height	Overall Length	Index Code	
	23460		3/4		7/16	2 3/16	C	1/4" Shank
	23262		1		7/16	2 1/2	F	1/2" Shank
	23264		1 1/2		5/8	2 3/4	I	
								Replacement Parts - pg 92

An upper ball bearing allows for mar free template work where smooth flat bottom finishes are required.



23460



23262

An upper ball bearing allows for mar free template work where smooth flat bottom finishes are required.



Series 34000

Double Flute Helix Laminate Flush Trim Bits with Bearing

A specially designed downcutting helix angle on this bit forces the laminate down against the backing, preventing chipping and surface flake. The ball bearing guide allows for smooth precise cuts when routing in laminate material.

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
1/4" Shank	34402	5/8	5/8	2 3/16	P
	34404	3/4	5/8	2 3/8	Q
	34406	3/4	1	2 7/8	Q
1/2" Shank	34202	3/4	5/8	2 11/16	Q
	34204	3/4	1	3	Q
	34206	3/4	1 1/2	3 1/2	Q
	34208	3/4	2	4	Q

Replacement Parts - pg 92



Series 31000

Carbide Tipped Double Flute Straight Flush Trim Bits with Bearing

A ball bearing guide assists trimming for a smooth finish on all types of materials including composite boards and laminated material.

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
1/4" Shank	31400	1/4	1/2	2	J
	31401	1/4	1	2 1/2	J
	31402	3/8	1/2	2 1/4	K
	31404	3/8	1	2 5/8	K
	31406	1/2	1/2	2 1/4	L
	31408	1/2	1	2 5/8	L
	31412	5/8	5/8	2 1/4	M
1/2" Shank	31206	1/2	1/2	2 3/4	L
	31208	1/2	1	3 1/4	L
	31210	1/2	1 1/2	3 7/8	L
	31214	1/2	2	4 1/4	L
	31216	3/4	1	3	N

Replacement Parts - pg 92



Series 31000

Carbide Tipped Triple Flute Straight Flush Trim Bits with Bearing



Identical to its double flute counterpart, but with three flutes for a smoother finish at slightly slower feed rates.


	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
1/4" Shank	31436	1/2	1/2	2 1/4	L
	31438	1/2	1	2 5/8	L
	31444	7/8	1/2	2 1/4	L
1/2" Shank	31236	1/2	1/2	2 3/4	L
	31238	1/2	1	3 1/4	L
	31240	1/2	1 1/2	3 7/8	L
	31242	1/2	2	4	O

Replacement Parts - pg 92



Carbide Tipped - Straight and Form Router Bits

Multi-Flute Straight Flush Trim Bits with Double Bearing							Series 31000	
	NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	1/2" Shank	Identical to the router bits on the previous page, but with double bearings to ensure smooth cutting action around a template.
	31250	Double	1/2	1 1/2	4 1/16	YY		
	31252	Double	1/2	2	4 1/2	YY		
	31254	Three	1/2	1 1/2	4 1/16	YY		
	Replacement Parts - pg 93							
								

Solid Carbide Flush Trim Bits					Series 27000	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	1/4" Shank	Designed to produce flush, square edges on plastic laminates. Built in pilot allows for small intricate cuts to be made easily.
	27402	1/4	1/4	1 1/2		
	27406	1/4	3/8	1 1/2		
						

Solid Carbide Flush Trim Bit with Small Pilot for Dado					Series 27000	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	1/4" Shank	The built in 1/8" pilot allows for shallow dados in plastic laminates.
	27408	1/4	1/4	1 1/2		
						

Series 27000

Solid Carbide Double End Flush Trim Bit

This double ended trim bit has two cutters in one tool at a reasonable, cost efficient price.

1/4" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
27410	1/4	1/4	2



Series 27000

Solid Carbide Flush Trim Bits with Boring Point

This bit is designed to drill its own starting hole then leave a clean, flush edge on plastic laminates.

1/4" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
27412	1/4	1/4	1 1/2
27414	1/4	3/8	1 1/2




Series 27000

Solid Carbide Bevel Trim Bits


Designed to produce a slight bevel on sides of plastic laminated material.


1/4" Shank

NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length
27422	7°	5/16	1/4	1 1/2
27424	7°	5/16	1/4	2 1/2



Carbide Tipped - Straight and Form Router Bits

Solid Carbide Double End Bevel Trim Bit						Series 27000
	NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	This double ended trim bit allows for two cutters in one tool, at a cost efficient price. 1/4" Shank
	27430	7°	1/4	1/4	2	

Solid Carbide Flush and Bevel Trim Bit						Series 27000
	NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	This bit is designed to either flush trim or place a slight bevel on plastic laminated material. 1/4" Shank
	27434	0° or 7°	1/4	3/8	1 1/2	

Solid Carbide Rip and Slotter Bits					Series 27000
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	For chip free ripping and slotting of plastic laminates. Primarily used to cut laminate strips for counter drops and back splashes. 1/4" Shank
	27442	1/4	1/4	1 1/2	
	27444	1/4	3/8	1 1/2	

Series 27000		Solid Carbide Flat Bottom Veining Bits			
This straight carbide bit has an upper ball bearing which can be used for mar-free template work.	1/4" Shank	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
		27480	1/8	1/4	2
		27482	3/16	3/8	2
		27484	1/4	1/2	2



Series 27000		Solid Carbide Round Bottom Veining Bits					
This double flute bit produces a flat bottom groove for decorative routing of cabinet doors and plastic laminates among other materials.	1/4" Shank	NAP GLADU Tool Number	Flute Cut	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
		27464	Single	1/16	1/8	1/4	1 1/2
		27466	Single	3/32	3/16	1/4	1 1/2
		27468	Single	1/8	1/4	11/32	1 1/2
		27470	Double	1/16	1/8	1/4	2
		27472	Double	3/32	3/16	3/8	2
		27474	Double	1/8	1/4	1/2	2




Series 27000		Solid Carbide V-Grooving and Scorer Bits				
Designed to make a decorative "V" groove or to score plastic laminate.	1/4" Shank	NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length
		27452	45°	1/8	1/4	1 1/2
		27454	45°	3/16	1/4	1 1/2
		27455	45°	1/4	1/8	1 1/2
		27456	45°	1/4	1/4	1 1/2
		27460	60°	1/4	7/32	1 1/2
		27462	60°	1/4	7/32	2



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Rabbeting Bits

Series 24000



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Rabbeting Depth	Overall Length	Index Code
24402	1 1/4	1/8	3/8	2	L
24404	1 1/2	5/32	1/2	1 3/4	L
24406	1 1/4	1/4	3/8	2	L
24408	1 1/4	3/8	3/8	2	L
24410	1 1/4	1/2	3/8	2	L
24412	1 3/8	1/2	7/16	2	L
24414	1 1/4	1/2	7/16	2	T
24416	1 3/8	1/2	1/2	2	T
24418	1 1/2	1/2	1/2	2	L
24202	1 1/4	1/8	3/8	2	L
24204	1 1/2	5/32	1/2	2	L
24206	1 1/4	1/4	3/8	2	L
24208	1 1/4	3/8	3/8	2 1/8	L
24210	1 1/4	1/2	3/8	2 3/8	L
24212	1 3/8	1/2	7/16	2 3/8	L
24214	1 1/4	1/2	7/16	2 3/8	T
24216	1 3/8	1/2	1/2	2 3/8	T
24218	1 1/2	1/2	1/2	2 1/4	L
24220	1 1/4	3/4	3/8	2 1/2	L

1/4" Shank


1/2" Shank

Designed to cut an edge step into solid woods and composite materials. Made with a ball bearing guide to allow for mar free cutting. The top and bottom is carbide relieved for easy, chip free cutting.

Replacement Parts - pg 92

Carbide Tipped Double Flute Rabbeting Sets

Series 24000




NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	C Rabbeting Depth	Index Code
24422	1 3/8	1/2	2	5/16	X
				3/8	Y
				7/16	Z
				1/2	AA
24424	1 3/8	1/2	2	flush	U
				1/8	V
				1/4	W
				5/16	X
				3/8	Y
				7/16	Z
				1/2	AA
24222	1 3/8	1/2	2 3/8	5/16	X
				3/8	Y
				7/16	Z
				1/2	AA
24224	1 3/8	1/2	2 3/8	flush	U
				1/8	V
				1/4	W
				5/16	X
				3/8	Y
				7/16	Z
				1/2	AA

1/4" Shank

1/2" Shank

Rabbeting sets are supplied in a styrofoam box which includes one assembled cutter and a variety of different sized ball bearings to provide multiple rabbeting depths. The appropriate washers and allen key are also supplied.



*Cutting Height is not to scale, actual Cutting Height = 1/2"

Replacement Parts - pg 92 | 93

Series 1300|24000

Super Carbide Tipped Double Flute Rabbeting Bits

There are three rabbeting sets available, the largest (Set C) includes 17 different rabbet cuts from 1/16" through 3/4". Also sold separately for specific cuts, the rabbeting bit (BC Tool 1386), a ball bearing, washer, spacer and individual collars, which change the depth of cut.

1/2" Shank



NAP GLADU Tool Number	Rabbet Set	A1 Cutting Diameter	A2 Collar Diameter	B Cutting Height	C Rabbeting Depth	Overall Length
1370	A, B, C	2	44.4 mm	7/8	1/8	1 7/8
1371	A, B, C	2	38.1 mm	7/8	1/4	1 7/8
1372	A, B, C	2	31.7 mm	7/8	3/8	1 7/8
1373	A, B, C	2	25.4 mm	7/8	1/2	1 7/8
1374	A, B, C	2	19.0 mm	7/8	5/8	1 7/8
1375	B, C	2	47.6 mm	7/8	1/16	1 7/8
1376	B, C	2	41.3 mm	7/8	3/16	1 7/8
1377	B, C	2	34.9 mm	7/8	5/16	1 7/8
1378	B, C	2	28.6 mm	7/8	7/16	1 7/8
1379	B, C	2	22.2 mm	7/8	9/16	1 7/8
1380	B, C	2	15.9 mm	7/8	11/16	1 7/8
1381	C	2	38.9 mm	7/8	15/64	1 7/8
1382	C	2	32.5 mm	7/8	23/64	1 7/8
1383	C	2	27.0 mm	7/8	15/32	1 7/8
1384	C	2	20.6 mm	7/8	19/32	1 7/8
1385	C	2	14.3 mm	7/8	23/32	1 7/8

Rabbeting Sets


24244A	6 Piece Rabbeting Set (Set A)
24242B	12 Piece Rabbeting Set (Set B)
24240C	17 Piece Rabbeting Set (Set C)

Replacement Parts


1386	Rabbeting Bit	2 x 1/2 x 7/8 x 3 5/64	without collar, will produce a 3/4" cut
1304	Ball Bearing	1/2 x 1/4 x 3/16	
00804	Spacer	2.2 mm	
00812	Washer		
00512	Screw		



Set A




Set B
(includes Set A plus 6 additional depths)




Set C
(includes Set A and B plus 5 additional depths)


Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Face Inlay Bits							Series 46000	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Cutting Depth	Overall Length	Index Code	1/2" Shank	Designed to leave a mortise type lip in solid plastic countertop materials.
	46290	7/8	1/4	1/16	3 1/16	Q		
	46291	7/8	1/4	1/8	3	R		
	46292	7/8	1/4	3/16	3	S		
	46293	7/8	1/2	1/16	3 1/4	Q		
	46294	7/8	1/2	1/8	3 1/4	R		
	46295	7/8	1/2	3/16	3 1/4	S		
	46296	7/8	3/4	1/16	3 7/16	Q		
	46297	7/8	3/4	1/8	3 1/2	R		
	46298	7/8	3/4	3/16	3 1/2	S		
							Replacement Parts - pg 92	

Carbide Tipped Double Flute Laminate Overhang Bit							Series 34000	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Laminate Overhang	Overall Length	Index Code	1/4" Shank	This bit will leave 3/16" of material for later finish cutting to help eliminate chipping on the final cut.
	34408	3/8	1/2	1/16	2 11/16	C		
	34410	3/8	1/2	1/8	2 13/16	C		
	34412	3/8	1/2	3/16	2 13/16	C		
								
Replacement Parts - pg 92								

Carbide Tipped Double Flute Face Frame Bits						Series 30000	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code		This bit is designed for the removal of any excess overhang while making a decorative “V” where the frame and cabinet join.
	30402	1/2	1	2 5/8	L	1/4" Shank	
	30202	1/2	1	3 1/4	L	1/2" Shank	
	Replacement Parts - pg 92						
							


Series 29000		Carbide Tipped Double Flute Mortise Bits				
This bit is made to be used in all hinge butt templates. A deep centre gullet allows for the maximum chip removal.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	1/4" Shank	29400	1/2	3/4	2	
		29402	5/8	3/4	2	
		29404	3/4	3/4	2	
		29408	1	3/4	2	
		29410	1 1/4	9/16	2	
	1/2" Shank	29210	1 1/4	1 1/4	2 7/8	

Series 29000 00000		Carbide Tipped Double Flute Mortise Bits				Arbors			
These mortise replacement cutters are made to fit on 1/4" shanks, number 00412 or 1/2" shanks, numbers 00212 or 00213.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Screw Type	BC Saw Tool Number	Thread Count	Overall Length	
	1/4 - 28 Thread	12400	1/2	5/8	A	00412	1/4 - 28	1 3/4	1/4" Shank
		12401	33/64	5/8	A	00212	1/4 - 28	1 3/4	1/2" Shank
		12402	17/32	5/8	A	00213	1/4 - 28	2 3/8	
		12403	9/16	5/8	A	Type A Type B 			
		12404	5/8	5/8	A				
		12405	41/64	5/8	A				
		12406	21/32	5/8	A				
		12407	11/16	5/8	A				
		12408	23/32	5/8	A				
		12409	3/4	1/2	A, B				
		12410	49/64	5/8	A				
		12411	25/32	5/8	A				
		12412	13/16	5/8	A				
		12413	7/8	1/2	A, B				
		12414	15/16	5/8	A				
		12415	1	1/2	A, B				
		12416	1 1/8	9/16	A, B				
		12417	1 1/4	5/8	A, B				
									

Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Bevel Bits

Series 32000



NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length
32490	10°	9/16	5/8	1 3/4
32492	15°	1/2	1/2	2
32494	23°	7/8	3/8	1 5/8
32496	30°	1	3/8	1 5/8
32498	45°	1 3/8	3/8	1 5/8


1/4" Shank

These are designed to plunge and rout a bevel groove in the stock material.



Carbide Tipped Double Flute Combination Bevel and Flush Trim Bits

Series 33000



NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length
33402	23°	3/8	1/2	1 5/8
33404*	23°	1/2	1/2	1 5/8
33406	23°	1/2	1/2	1 5/8
33408	30°	1/2	1/2	1 5/8
33410	35°	1/2	1/2	1 5/8
33412	45°	1/2	1/2	1 5/8

1/4" Shank


This versatile bit allows for both beveling and straight trimming of materials. By raising or lowering the bit, the function changes.



*Single Flute Tool

Carbide Tipped Double Flute Bevel Trim Bits with Bearing

Series 32000




NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
32422	0°	1/2	1/4	2 1/8	L
32423	7°	5/8	3/8	2 1/8	L
32424	15°	5/8	1/4	2 1/8	L
32426	15°	1	3/8	2	N
32427	15°	13/16	1/2	2	L
32428	15°	5/8	1/2	2	BB
32429	25°	3/4	1/4	2 1/8	L
32430	25°	1	1/2	2	L
32431	30°	1 1/2	3/4	2 3/4	L
32432	45°	1	1/4	2 1/8	L
32227	15°	1 1/16	15/16	2 3/4	L
32229	22.5°	1 5/16	7/8	2 3/4	L
32231	30°	1 1/2	3/4	2 3/4	L


1/4" Shank


These are designed to remove the square look of the material by leaving a slight beveled edge, angles available from 7° to 45°



Replacement Parts - pg 92 | 93

Series 32000		Carbide Tipped Triple Flute Bevel Trim Bits with Bearing						
An extra cutting edge on this bit leaves the material slightly smoother than the double flute counterpart.		NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
	1/4" Shank	32463	10°	3/4	3/8	1 7/8	M	
		32464	15°	13/16	3/8	1 7/8	M	
		32467	25°	15/16	3/8	1 7/8	M	
		32468	45°	1 7/16	3/8	1 7/8	M	
		Replacement Parts - pg 92						
								


Series 32000		Carbide Tipped Four Flute Bevel Trim Cutter Assemblies					
Designed specifically for trimming high pressure plastic laminates, the four flute design allows for smooth trimming. The complete assembly includes a cutter, bearing 1314 and either arbor 00212 or arbor 00412.		NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	
	1/4" Shank	32472	0°	7/8	1/4	2 3/4	
		32474	15°	1	1/4	2 3/4	
		32476	25°	1 1/16	1/4	2 3/4	
	1/2" Shank	32272	0°	7/8	1/4	2 3/8	
		32274	15°	1	1/4	2 3/8	
		32276	25°	1 1/16	1/4	2 3/8	
							

Series 32000		Carbide Tipped Four Flute Bevel Trim Cutter Assemblies					
These are replacement cutters for the above four flute trim cutter assemblies.		NAP GLADU Tool Number	a	Bevel Angle	A Cutting Diameter	B Cutting Height	D Cutter Bore
		32482		0°	7/8	1/4	5/16
		32484		15°	1	1/4	5/16
		32486		25°	1 1/16	1/4	5/16
							

Carbide Tipped - Straight and Form Router Bits


Carbide Tipped Double Flute Chamfer Bits

Series 32000



NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	C Cutting Depth	Overall Length	Index Code
32408	45°	1 1/4	1/2	5/8	2	BB
32204	45°	1 1/4	1/2	5/8	2 3/8	BB
32206	45°	2	3/4	1	2 5/8	L
32208	45°	2 1/2	1	1 1/4	2 13/16	L
32210	45°	2 5/8	1 1/16	1 1/2	3	L


Replacement
Parts - pg 92 | 93



Designed to place a 45° chamfer on the edge of the material; ball bearing guide provides mar free work.

Carbide Tipped Double Flute V-Grooving Bits

Series 26000




NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	
26402	45°	1/4	5/16	3/16	2	1/4" Shank
26404	45°	3/8	3/4	3/16	1 3/4	
26406	45°	1/2	1/2	1/4	1 3/4	
26408	45°	5/8	1/2	5/16	1 3/4	
26410	45°	3/4	1/2	7/16	1 3/4	
26412	45°	7/8	5/8	7/16	2	
26414	45°	1	5/8	1/2	1 3/4	
26460	30°	1/2	9/16	7/16	2	
26462	30°	1/2	1/2	7/16	1 3/4	
26470	35°	1/2	1/2	3/8	1 3/4	
26204	45°	3/8	1/2	3/16	1 3/4	1/2" Shank
26202	45°	1/2	1/2	9/32	2 1/8	
26208	45°	5/8	1/2	5/16	2 1/8	
26210	45°	3/4	5/8	3/8	2 1/4	
26212	45°	7/8	5/8	7/16	2 1/4	
26214	45°	1	3/4	1/2	2 3/8	
26216	45°	1 1/4	1	5/8	2 1/2	
26218	45°	1 1/2	1 1/4	3/4	2 7/8	
26220	45°	1 3/4	1 1/2	7/8	3	
26222	45°	2	1 3/4	7/8	3	
26260	30°	1/2	9/16	7/16	2 1/4	

Designed for shallow and deep grooves in all types of woods. Good for general decorative cuts, simulated plank design, etc. Can also be used for chamfering.



Carbide Tipped Double Flute V-Groove Bits with Upper Bearing

Series 26000B



NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
26406B	45°	1/2	1/2	2	A

Replacement
Parts - pg 92




Designed to leave a "V" shaped groove in the material. The upper ball bearing aids in template work.

Series 26000

This solid carbide three flute design is for engraving and sign making in a variety of materials.

1/4" Shank

NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length
26490	30°	9/16	7/8	2 1/4




Series 25000

These bits are designed for all solid woods, plywoods, composite boards and laminates.

Made for all dovetail operations including dovetailing and dovetail jointing.

1/4" Shank

NAP GLADU Tool Number	^a Cutting Angle	A Cutting Diameter	B Cutting Height	Overall Length
25480	7.5°	1/4	5/16	2 1/2
25482	8°	1/4	1/4	2 1/2




Series 25000

Designed to rout solid woods, plywoods, composite boards and laminates. Spurs allow room for gluing.

1/4" Shank


NAP GLADU Tool Number	^a Cutting Angle	A Cutting Diameter	B Cutting Height	Overall Length
25460	13°	9/16	17/32	2 3/16




Series 25000


Designed for all dovetail operations
where an upper ball bearing is needed
for template work.

NAP GLADU Tool Number	^a Cutting Angle	^A Cutting Diameter	^B Cutting Height	Overall Length	Index Code
25450	14°	1/2	1/2	2 1/4	A




Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Dovetail Bits						Series 25000	
	NAP GLADU Tool Number	a Cutting Angle	A Cutting Diameter	B Cutting Height	Overall Length	1/4" Shank	Designed for solid woods, plywoods, composite boards and laminates in all dovetail operations including french dovetailing and dovetail joining.
	25400	25°	13/64	5/32	2 3/8		
	25405	7.5°	1/4	5/16	2 1/2		
	25406	8°	5/16	3/8	2 1/4		
	25408	8°	3/8	1/2	2 3/8		
	25410	8°	7/16	5/8	2 3/8		
	25412	8°	1/2	13/16	2 3/4		
	25415	9°	5/16	3/8	2 1/2		
	25416	9°	3/8	3/8	1 5/8		
	25418	10°	1/2	5/8	2 1/2		
	25420	14°	1/2	1/2	1 3/4		
	25422	14°	1/2	1/2	2 3/8		
	25424	14°	17/32	1/2	1 3/4		
	25430	18°	1/2	3/8	2 1/4		
	25316	9°	3/8	3/8	2	3/8" Shank	
	25200	7°	5/8	5/8	2 3/8	1/2" Shank	
	25201	7°	5/8	7/8	2 1/16		
	25202	7°	3/4	7/8	2 1/2		
	25203	7°	7/8	7/8	2 5/8		
	25204	7°	1 1/8	3/4	2 3/8		
	25213	8°	11/16	1	3		
	25214	8°	13/16	1 1/4	3 1/4		
	25215	9°	5/16	3/8	2 1/2		
	25216	9°	3/8	3/8	1 5/8		
	25217	9°	3/8	3/8	2 1/2		
	25218	10°	1/2	5/8	2 5/8		
	25220	14°	1/2	1/2	2 3/16		
	25226	14°	3/4	3/4	2 1/2		
	25227	14°	7/8	7/8	2 5/8		
	25228	14°	1	1	2 5/8		
	25229	14°	1 1/4	1	2 5/16		

Carbide Tipped Double Flute Dovetail Bits - Left Hand Rotation						Series 25000L	
	NAP GLADU Tool Number	a Cutting Angle	A Cutting Diameter	B Cutting Height	Overall Length	1/4" Shank	Same qualities as the dovetail bits above, but cuts in a counter-clockwise rotation.
	25415L	9°	5/16	3/8	2 1/2		
	25420L	14°	1/2	1/2	1 3/4		
	25201L	7°	5/8	7/8	2 1/16	1/2" Shank	
	25202L	7°	3/4	3/4	2 5/16		
	25203L	7°	7/8	7/8	2 5/8		
	25204L	7°	1 1/8	3/4	2 3/8		
	25216L	9°	3/8	3/8	1 5/8		
	25217L	9°	3/8	3/8	2 1/2		
	25220L	14°	1/2	1/2	2 1/4		
	25227L	14°	7/8	7/8	2 5/8		
	25228L	14°	1	1	2 5/8		

Series 25000		Carbide Tipped Double Flute Automatic Dovetail Bits			
These bits are threaded shank bits for automatic and semi-automatic dovetail machines including: Dodds, Wysong-Miles, Bell and Brookman.	Machine	NAP GLADU Tool Number	Rotation Direction	Thread Count	A Cutting Diameter
	Bell	25502	Right	3/8 - 24	5/16
		25502L	Left		
		25504	Right	3/8 - 24	3/8
		25504L	Left		
	Wysong Miles	25512	Right	3/8 - 20	5/16
		25512L	Left		
		25514	Right	3/8 - 20	3/8
		25514L	Left		
	Dodds	25520	Right	5/16 - 24	1/4
		25520L	Left		
		25522	Right	5/16 - 24	5/16
		25522L	Left		
		25524	Right	5/16 - 24	3/8
		25524L	Left		
		25532	Right	3/8 - 20	5/16
		25532L	Left		
		25534	Right	3/8 - 20	3/8
		25534L	Left		




Series 25000 00000		Carbide Tipped Dovetail Slot Cutters				Arbors	
The Series 25000 cutters, may be used on French Dovetail machines for producing slots on drawer bottoms. Needs to be run on arbors from Series 00000.	NAP GLADU Tool Number	Wing Count	A Cutting Diameter	B Dovetail Kerf	BC Saw Tool Number	Overall Length	
	25600	4	1 1/4	3/16	00350	3 7/16	3/8" Shank
	25602	6	1 1/4	3/16	00250	3 7/16	1/2" Shank
							

Carbide Tipped - Straight and Form Router Bits

Double Flute Cove Bits with Upper Bearing - Plunge Type

Series 39000




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
39450	1/8	1/2	1/2	2 1/8	A	1/4" Shank
39452	1/4	3/4	5/8	2 5/16	C	
39252	1/4	3/4	5/8	2 5/16	E	1/2" Shank
39254	1/4	1 1/8	5/8	2 5/8	G	

Replacement
Parts - pg 92

These are designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.

Carbide Tipped Double Flute Bowl and Tray Bits


Series 42000




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
42465	1/8	7/16	5/16	2 1/8	—	1/4" Shank
42466	1/4	3/4	5/8	2 3/8	—	
42466B	1/4	3/4	5/8	2 3/8	C	
42266	1/4	3/4	5/8	2 3/8	—	1/2" Shank
42268	1/4	1 1/4	1/2	2 1/4	—	
42268B	1/4	1 1/4	1/2	2 1/4	H	

Replacement
Parts - pg 92



Designed to rout a rounded bottom groove or channel in solid wood, composites, etc. The router bit numbers which are followed by “B” have an upper ball bearing guide for template work.

Series 42000		Carbide Tipped Double Flute Roundnose Bits					
Designed with a constant radius for general routing, grooving and ornamentation.		NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	
	1/4" Shank	42402	1/16	1/8	3/8	1 3/4	
		42404	3/32	3/16	1/8	1 3/8	
		42406	3/32	3/16	1/2	1 3/4	
		42410	1/8	1/4	1/2	1 3/4	
		42412	5/32	5/16	1/2	1 1/2	
		42414	3/16	3/8	1/4	1 1/2	
		42416	7/32	7/16	5/8	1 3/4	
		42418	1/4	1/2	5/16	1 1/2	
		42424	5/16	5/8	3/8	1 1/2	
		42426	3/8	3/4	1/2	1 1/2	
		42432	7/16	7/8	5/8	1 3/4	
		42436	1/2	1	5/8	1 3/4	
	1/2" Shank	42214	3/16	3/8	1/4	1 7/8	
		42215	3/16	3/8	1	2 3/4	
		42216	7/32	7/16	5/8	2 3/8	
		42218	1/4	1/2	5/16	2	
		42220	1/4	1/2	1 1/4	2 3/4	
		42222	9/32	9/16	1 1/4	2 3/4	
		42224	5/16	5/8	3/8	2	
		42225	5/16	5/8	1 1/4	2 3/4	
		42226	3/8	3/4	1/2	2	
		42228	3/8	3/4	1 1/4	2 3/4	
		42232	7/16	7/8	5/8	2	
		42234	7/16	7/8	1 1/4	2 3/4	
		42236	1/2	1	5/8	2 3/16	
		42238	1/2	1	1 1/4	2 3/4	
		42240	5/8	1 1/4	3/4	2 3/16	
		42242	5/8	1 1/4	1 1/4	2 3/4	
		42244	3/4	1 1/2	1 1/4	2 3/4	
		42246	1	2	1 1/4	2 3/4	
							
Series 42000B		Carbide Tipped Double Flute Roundnose Bit with Upper Bearing					
This bit is designed with a constant radius for general routing, grooving and ornamentation. An upper ball bearing guide allows for trimming and template work.		NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/4" Shank	42418B	1/4	1/2	1/2	2	A
		42424B	5/16	5/8	3/8	2	B
		42426B	3/8	3/4	7/16	2	C
						Replacement Parts - pg 92	
		42426B					
		42426B					
		42418B					
							

Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Ball Grooving Bits					Series 42000	
 A2 A1	NAP GLADU Tool Number	A1 Ball Diameter	A2 Neck Diameter	Overall Length	1/2" Shank	Designed with a constant radius for general routing, grooving and ornamentation. A near full circular ball cutting edge leaves a circular groove for channeling or ornamentation. 
	42250	1/2	1/4	2 1/4		
	42252	5/8	9/32	2 7/16		
	42254	3/4	5/16	2 1/2		
	42256	7/8	5/16	2 5/8		
	42258	1	11/32	2 3/4		
	42260	1 1/8	13/32	2 7/8		
	42262	1 3/4	7/16	3		

Carbide Tipped Double Flute Convex Beading Bits with Bearing							Series 42000	
	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	1/2" Shank	These bits are designed to rout a convex curve in the working material. A ball bearing guide allows for mar free work.
	42270	3/16	3/4	3/8	2 5/8	L		
	42272	5/16	3/4	1/2	2 3/4	L		
	42274	15/32	7/8	3/4	3 1/16	L		
	42276	3/4	7/8	1	3 3/8	L		
	42278	1 1/4	1	1 1/2	3 7/8	L		
							Replacement Parts - pg 92	

Carbide Tipped Double Flute Full Radius Beading Bits with Bearing							Series 42000	
	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	1/4" Shank	
	42480	5/32	13/16	5/16	1 7/8	L		
	42482	3/16	7/8	3/8	2	L		
	42484	15/64	31/32	15/32	2	L	1/2" Shank	
	42286	19/64	1 3/32	19/32	2 3/4	L		
	42288	25/64	1 1/4	25/32	3	L		
Replacement Parts - pg 92								
								

These are designed to rout a half circle in the working material. An added ball bearing guide allows for mar free work.

Series 42000



Carbide Tipped Double Flute Convex Beading Bits with Bearings

These straight carbide bits with an upper ball bearing allow for mar-free template work.

1/4" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
42490	1/8	3/4	1/4	2 1/4	ZZ
42492	13/64	7/8	25/64	2 3/8	ZZ

Replacement Parts - pg 93



Series 47000

Carbide Tipped Double Flute True Bull Nose Bits


This bit is designed to make round edges on furniture, countertops and stair threads.

1/4" Shank

1/2" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	C Cutter Opening	Overall Length
47452	23/32	13/16	1 1/4	7/8	2 1/2
47250	11/32	3/4	1	1/2	2 5/8
47252	23/32	13/16	1 1/4	7/8	2 3/4
47254	1/2	1	1 1/4	3/4	2 7/8
47256	3/4	1	1 1/4	1	2 3/4
47258	1 1/4	1 1/4	1 3/4	1 1/2	3 1/4

Note: 'r' is not exact radius



Series 47000B



Carbide Tipped Double Flute Half Round Bits with Bearing

These bits can accomplish complete edge rounding on both sides of the material, produced by a continuous radius throughout the opening. Flared ends allow for clean cuts at the top and bottom of the material.

1/2" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	C Cutter Opening	Overall Length	Index Code
47210B	9/64	25/32	3/4	17/64	2 5/8	L
47214B	13/64	29/32	3/4	25/64	2 5/8	L
47218B	17/64	1 1/32	1	35/64	3	L
47220B	3/8	1 3/8	1 1/4	3/4	3 5/16	DD
47222B	1/2	1 3/4	1 9/16	1	3 5/8	EE
47224B	5/8	2	2	1 1/4	4	EE


Replacement Parts - pg 92 | 93



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Half Round Bits

Series 47000




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	C Cutter Opening	Overall Length
47402	5/64	17/32	1/2	5/32	1 5/8
47404	3/32	3/4	1/2	3/16	1 13/16
47406	7/64	19/32	1/2	7/32	1 5/8
47408	1/8	7/8	9/16	1/4	1 29/32
47410	9/64	21/32	3/4	9/32	1 7/8
47412	3/16	1	7/8	3/8	2 1/4
47414	13/64	7/8	3/4	13/32	1 7/8
47416	1/4	1 1/8	1	1/2	2 7/16
47418	17/64	1 1/32	1	35/64	2 1/8
47202	5/64	17/32	1/2	5/32	2 3/16
47204	3/32	3/4	1/2	3/16	1 7/8
47206	7/64	19/32	1/2	7/32	2
47208	1/8	7/8	9/16	1/4	2 1/32
47210	9/64	21/32	3/4	9/32	2 1/4
47212	3/16	1	7/8	3/8	2 11/32
47214	13/64	7/8	3/4	13/32	2 1/4
47216	1/4	1 1/8	1	1/2	2 1/2
47218	17/64	1 1/32	1	35/64	2 1/2
47219	5/16	1 1/16	1 1/8	5/8	2 1/2
47220	3/8	1 5/16	1 3/8	3/4	2 7/8
47221	7/16	1 7/8	1 1/2	7/8	3
47222	1/2	1 11/16	1 9/16	1	3 1/16
47223	9/16	1 15/16	1 1/2	1 1/8	3 1/4
47224	5/8	2	2	1 1/4	3 1/2
47226*	3/4	2 3/8	2	1 1/2	3 1/2

*Three flute bit suitable for Corian and Woods

1/4" Shank


1/2" Shank

Complete edge rounding on both sides of the material, produced by a continuous radius through the opening. The flared ends allow for clean cuts at the top and bottom of the material.



Carbide Tipped Double Flute Half Round Bit - Plunge Type

Series 47000



NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	C Cutter Opening	Overall Length	Index Code
47260	1/2	1 1/8	1 9/16	7/8	3 5/8	—
47260B	1/2	1 1/8	1 9/16	7/8	3 5/8	G

B. Upper Bearing Included


Replacement
Parts - pg 92

1/2" Shank

This bit is designed with a boring point to penetrate stock and rout a half round radius in a single pass. The upper ball bearing guide allows for template work.

Series 48000


Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.



Carbide Tipped Double Flute Corner Beading Bits with Bearing

	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
1/4" Shank	48400	1/8	7/8	9/16	2 1/8	L
	48402	3/16	1 1/16	5/8	2 1/4	FF
	48404	1/4	1 1/4	3/4	2 3/8	FF
1/2" Shank	48200	1/8	7/8	9/16	2 1/2	L
	48202	3/16	1 1/16	5/8	2 5/8	FF
	48204	1/4	1 1/4	3/4	2 5/8	FF
	48206	3/8	1 1/2	1	3	FF

Replacement
Parts - pg 92 | 93





Series 48000

Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.

Double Flute Beading Bits with Upper and Lower Bearing - Leaf Edge

	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
1/4" Shank	48410	3/16	1	1/2	2 1/2	D
	48412	1/4	1 1/8	5/8	2 5/8	D
	48414	3/8	1 3/8	7/8	2 7/8	D

Replacement
Parts - pg 92




Series 48000

Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.


Double Flute Beading Bit with Upper and Lower Bearing - Double Leaf


	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
1/4" Shank	48416	3/16	1	7/8	3	D


Replacement
Parts - pg 92



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Variable Beading Bits								Series 48000	
	NAP GLADU Tool Number	r1 r2 r3	Cutting Radius	A	Cutting Diameter	B	Cutting Height	Overall Length	
	48420	r1 r2 r3	5/32 1/8 5/64		7/8		1 1/8	2 1/4	1/4" Shank
	48220	r1 r2 r3	5/32 1/8 5/64		7/8		1 1/8	2 5/8	1/2" Shank
									
Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.									

Carbide Tipped Double Flute Triple Beading Bit								Series 48000	
	NAP GLADU Tool Number	r1 r2	Cutting Radius	A	Cutting Diameter	B	Cutting Height	Overall Length	
	48422	r1 r2	5/64 1/4		3/4		1	2 1/8	1/4" Shank
									
Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.									

Carbide Tipped Double Flute Edge Beading Bits								Series 48000	
	NAP GLADU Tool Number	r	Cutting Radius	A	Cutting Diameter	B	Cutting Height	Overall Length	
	48424		5/32		7/8		1 1/32	2 5/16	1/4" Shank
	48224		5/32		7/8		1 1/32	2 1/2	1/2" Shank
									
Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.									

Series 48000		Carbide Tipped Double Flute Edge Beading Bits with Bearing						
Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.	1/2" Shank	NAP GLADU Tool Number	r1 Cutting r2 Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
		48230	r1 1 r2 3/32	1	7/8	2 3/4	FF	
		48232	r1 3/4 r2 1/8	1	7/8	2 3/4	FF	
		48234	r1 9/16 r2 5/32	1	7/8	2 3/4	FF	
		48236	r1 3/8 r2 3/16	1	7/8	2 3/4	FF	


Series 48000		Carbide Tipped Double Flute Triple Beading Bits with Bearing					
Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.		NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/4" Shank	48440	1/8	7/8	1	2 1/2	FF
	1/2" Shank	48240	1/8	7/8	1	2 7/8	FF
		Replacement Parts - pg 93					

Series 48000		Carbide Tipped Double Flute Triple Beading Bits with Bearing						
Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.		NAP GLADU Tool Number	r1 Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
	1/4" Shank	48442	r1 1/8 r2 3/16	1	1	2 1/4	GG	
	1/2" Shank	48242	r1 1/8 r2 3/16	1	1	2 1/4	GG	

Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Double Beading Bit with Bearing

Series 48000




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
48246	1/8	7/8	3/4	2 5/8	M	1/2" Shank
				Replacement Parts - pg 92		

Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.

Carbide Tipped Double Flute Convex Beading Bits with Bearing

Series 48000




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
48444	1/8	7/8	1	2 1/2	M	1/4" Shank
48244	1/8	7/8	1	2 7/8	M	1/2" Shank
				Replacement Parts - pg 92		

Designed for decorative edging on moulding and furniture. Best for use on natural woods, wood composites and plastics.

Carbide Tipped Double Flute 25° Tee-Bumper Moulding Bits

Series 25000



NAP GLADU Tool Number	a Cutting Angle	A Cutting Diameter	B Cutting Height	Overall Length	
25440	25°	13/64	5/32	2 3/8	1/4" Shank

These are designed to rout a small groove for the insertion of weather stripping, etc.

Series 26000

Carbide Tipped Double Flute 38° Tee-Bumper Moulding Bits

These bits are designed to rout a small groove for the insertion of weather stripping, etc.

1/4" Shank

NAP GLADU Tool Number	a Cutting Angle	A1 Cutting A2 Diameter	B1 Cutting B2 Height	Overall Length
26450	38°	A1 7/32 A2 5/64	B1 5/32 B2 5/16	2 9/16



Series 40000B

Double Flute Rounding Over Bits with Upper Bearing - Plunge Type

Designed to produce decorative rounded edges. Best for use on natural woods, wood composites and plastics. Upper bearing guide aids in template work.



1/4" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
40400B	1/8	1/2	3/8	1 7/8	A
40401B	1/8	3/4	3/8	2	C
40402B	3/16	7/8	1/2	2 1/8	CC

1/2" Shank

40206B	5/16	1 1/8	9/16	2 1/8	G
--------	------	-------	------	-------	---

Replacement
Parts - pg 92 | 93



Series 40000

Carbide Tipped Double Flute Rounding Over Bits - Plunge Type




Designed for decorative rounded edges. Best for use on natural woods, wood composites and plastics.

1/4" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
40400	1/8	3/8	5/16	2
40402	3/16	5/8	3/8	1 3/4
40404	1/4	3/4	1/2	1 5/8
40406	5/16	7/8	9/16	1 11/16
40408	3/8	1	5/8	1 3/4

1/2" Shank


40202	3/16	5/8	5/16	1 1/2
40204	1/4	3/4	1/2	2
40206	5/16	7/8	9/16	2 1/16
40208	3/8	1	5/8	2 1/8
40210	1/2	1 3/8	1	2 3/4
40211	9/16	1 5/8	1 1/4	2 3/4
40212	5/8	1 3/4	1 1/4	2 3/4
40214	3/4	2	1 7/16	2 15/16



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Cove Bits with Bearing

Series 39000




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
39422	1/16	1/2	1/2	2	BB
39424	1/8	5/8	1/2	2	BB
39426	3/16	3/4	9/16	2 1/16	BB
39428	1/4	7/8	9/16	2 1/16	BB
39430	5/16	1	9/16	2 1/16	BB
39432	3/8	1 1/8	9/16	2 1/16	BB
39436	1/2	1 3/8	3/4	2 1/4	BB
39437	1/2	1 1/2	5/8	2 1/2	BB
39222	1/16	1/2	1/2	2 3/8	BB
39224	1/8	5/8	1/2	2 3/8	BB
39226	3/16	3/4	9/16	2 7/16	BB
39228	1/4	7/8	9/16	2 7/16	BB
39230	5/16	1	9/16	2 7/16	BB
39232	3/8	1 1/8	9/16	2 7/16	BB
39236	1/2	1 3/8	3/4	2 7/16	BB
39237	1/2	1 1/2	5/8	2 11/16	BB
39238	5/8	1 5/8	3/4	2 5/8	BB
39240	3/4	1 7/8	1	3	L
39242	7/8	2 3/8	1 1/4	3 3/8	L
39244	1	2 3/8	1 1/4	3 3/8	L
39248	1 1/2	3	1 1/4	3 3/8	L

1/4" Shank

1/2" Shank


Designed for decorative inverted radii edge. For use on natural woods, wood composites and plastics.



Replacement
Parts - pg 92 | 93

Carbide Tipped Double Flute Matching Corner Round | Cove Bits

Series 41000



NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
41480	1/4	1 1/8	35/64	2 19/32
41482	5/16	1 1/4	43/64	2 23/32
41484	3/8	1 3/8	51/64	2 27/32


1/4" Shank

These bits are designed to perform two functions with one tool – matching round over and cove cuts.



Series 41000

Designed to rout decorative rounded edges. This bit is best for use on natural woods, wood composites and plastics.



1/4" Shank


1/2" Shank

Carbide Tipped Double Flute Corner Rounding Bits with Bearing

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
41412	1/16	5/8	5/16	1 3/4	L
41414	1/8	3/4	3/8	1 15/16	L
41416	5/32	3/4	3/8	1 15/16	L
41418	3/16	7/8	1/2	1 15/16	L
41420	1/4	1	1/2	1 15/16	L
41422	5/16	1 1/8	1/2	1 15/16	L
41424	3/8	1 1/4	5/8	2 1/4	L
41426	1/2	1 1/2	3/4	2 3/16	L
41212	1/16	5/8	5/16	2 3/16	L
41214	1/8	3/4	3/8	2 5/16	L
41216	5/32	3/4	3/8	2 5/16	L
41218	3/16	7/8	1/2	2 5/16	L
41220	1/4	1	1/2	2 5/16	L
41222	5/16	1 1/8	1/2	2 5/16	L
41224	3/8	1 1/4	5/8	2 7/16	L
41225	7/16	1 3/8	5/8	2 1/2	L
41226	1/2	1 1/2	3/4	2 9/16	L
41228	5/8	1 3/4	7/8	2 5/8	L
41229	9/16	1 5/8	3/4	2 3/4	L
41230	3/4	2	1	2 3/4	L
41232	7/8	2 1/2	1 1/4	2 7/8	L
41234	1	2 1/2	1 1/4	3	L
41236	1 1/8	2 3/4	1 3/8	3 1/4	L
41238	1 1/4	3	1 1/2	3 1/4	L
41240	1 3/8	3 1/4	1 9/16	3 1/2	L
41242	1 1/2	3 1/2	1 3/4	3 3/4	L

Replace standard bearings with a smaller size to attain a decorative bead on wood

Replacement
Parts - pg 92



Series 41000

Designed to produce decorative edges or mid-stock decorative grooves. This bit is best suited for natural woods, wood composites and plastics.




1/4" Shank

Carbide Tipped Double Flute Beading Bit - Plunge Type

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
41490	1/8	3/8	5/16	2



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Rounding Over Bit - Plunge Type						Series 44000
	NAP GLADU Tool Number	r1 Cutting r2 Radius	A Cutting Diameter	B Cutting Height	Overall Length	1/2" Shank
	44262	r1 1/4 r2 19/32	1 5/8	23/32	2 7/32	
						Designed to produce decorative edges or mid-stock decorative grooves. Best for use on natural woods, wood composites and plastics.
Carbide Tipped Double Flute Rounding Over Bits - Plunge Type						Series 44000
	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	1/2" Shank
	44266	23/32	1 3/4	23/32	2 7/32	
	44268	1	1 5/8	23/32	2 7/32	
						Designed to produce decorative edges or mid-stock decorative grooves. Best for use on natural woods, wood composites and plastics.
Carbide Tipped Double Flute Round and Ogee Bit - Plunge Type						Series 44000
	NAP GLADU Tool Number	r1 Cutting r2 Radius	A Cutting Diameter	B Cutting Height	Overall Length	1/2" Shank
	44272	r1 5/32 r2 7/8	1 9/16	25/32	2 9/32	
						Designed to produce decorative edges or mid-stock decorative grooves. Best for use on natural woods, wood composites and plastics.

Series 40000

Double Flute Point Cutting Roundover Bits - Plunge Type


These bits are designed for decorative trimming and lettering where rounded edges are required. Best for use on natural woods, wood composites and plastics.

1/4" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
40420	3/16	3/8	3/8	2
40422	1/4	1/2	1/2	2
40424	3/8	3/4	5/8	2

1/2" Shank

40224	3/8	3/4	5/8	2 1/4
-------	-----	-----	-----	-------




Series 44000

Carbide Tipped Double Flute Round and Ogee Bits - Plunge Type

Designed to produce decorative edges or mid-stock decorative grooves. This bit is best for use on natural woods, wood composites and plastics.

1/2" Shank

NAP GLADU Tool Number	r1 Cutting Radius r2 Radius	A Cutting Diameter	B Cutting Height	Overall Length
44250	r1 3/8 r2 3/4	1 5/8	23/32	2 13/64
44252	r1 5/8 r2 1 3/16	1 31/32	23/32	2 13/64




Series 44000

Carbide Tipped Double Flute Step Flat Ogee - Plunge Type

Designed to produce decorative edges or mid-stock decorative grooves. This bit is best for use on natural woods, wood composites and plastics.

1/2" Shank


NAP GLADU Tool Number	r Cutting Radius	A1 Cutting Diameter A2 Diameter	B Cutting Height	Overall Length
44256	3/16	A1 1 A2 3/8	19/32	2 3/32
44258	15/64	A1 1 3/64 A2 15/32	19/32	2 3/32



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Beading Bits with Bearing

Series 41000




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
41452	1/16	5/8	5/16	1 3/4	T
41454	1/8	3/4	3/8	1 15/16	T
41456	5/32	3/4	3/8	1 15/16	T
41458	3/16	7/8	1/2	1 15/16	T
41460	1/4	1	1/2	1 15/16	T
41462	5/16	1 1/8	1/2	1 15/16	T
41464	3/8	1 1/4	5/8	2 1/4	T
41466	1/2	1 1/2	3/4	2 3/16	T
41252	1/16	5/8	5/16	2 3/16	T
41254	1/8	3/4	3/8	2 3/16	T
41256	5/32	3/4	3/8	2 1/4	T
41258	3/16	7/8	1/2	2 5/16	T
41260	1/4	1	1/2	2 5/16	T
41262	5/16	1 1/8	1/2	2 5/16	T
41264	3/8	1 1/4	5/8	2 7/16	T
41266	1/2	1 1/2	3/4	2 9/16	T
41268	5/8	1 3/4	7/8	2 5/8	T
41270	3/4	2	1	2 3/4	T
41272	7/8	2 1/4	1 1/4	2 7/8	T
41274	1	2 1/2	1 1/4	3	T
41276	1 1/8	2 3/4	1 3/8	3 1/4	T
41278	1 1/4	3	1 1/2	3 1/4	T
41280	1 3/8	3 1/4	1 9/16	3 1/2	T
41282	1 1/2	3 1/2	1 3/4	3 3/4	T

1/4" Shank

1/2" Shank

These bits are made to rout decorative rounded edges where a combined corner round and edge bead are required. For use on natural woods, wood composites and plastics.



Replacement Parts - pg 92

Carbide Tipped Double Flute Classical Bits - Plunge Type

Series 43000



NAP GLADU Tool Number	r1 Cutting Radius	r2 Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
43430	r1 1/8	r2 5/32	1/2	3/8	2
43432	r1 3/16	r2 1/4	3/4	1/2	2 1/16
43232	r1 3/16	r2 1/4	3/4	1/2	2 3/4
43234	r1 1/4	r2 5/16	1	5/8	2 7/8

1/4" Shank

1/2" Shank

Designed to produce decorative edges or mid-stock decorative grooves. Best for use on natural woods, wood composites and plastics.





Series 43000

Carbide Tipped Double Flute Traditional Bits - Plunge Type

Designed to produce decorative edges or mid-stock decorative grooves. This bit is best suited for on natural woods, wood composites and plastics.

	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	43440	3/64	1/2	3/8	2
	43442	1/16	3/4	7/16	2 1/16
1/2" Shank	43242	1/16	3/4	7/16	2 5/8



Series 43000

Carbide Tipped Double Flute Round Bottom Ogee Bits - Plunge Type

Designed to produce decorative edges or mid-stock decorative grooves. This bit is best suited for on natural woods, wood composites and plastics.

	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	43428	15/64	1 1/16	7/16	2
1/2" Shank	43228	15/64	1 1/16	7/16	2 1/4




Series 43000

Carbide Tipped Double Flute Flat Bottom Ogee Bits - Plunge Type

Designed to produce decorative edges or mid-stock decorative grooves. This bit is best suited for on natural woods, wood composites and plastics.


	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	43420	1/16	3/8	5/16	1 7/8
	43422	5/64	1/2	3/8	2
	43424	1/8	3/4	7/16	2 1/8
1/2" Shank	43224	1/8	3/4	7/16	2 3/4




Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Corner Ogee Bit - Plunge Type

Series 43000




NAP GLADU Tool Number	r	Cutting Radius	A	Cutting Diameter	B	Cutting Height	Overall Length	
43230		3/32		15/16		19/32	2 1/4	1/2" Shank



Designed to produce decorative edges or mid-stock decorative grooves. Best for use on natural woods, wood composites and plastics.

Carbide Tipped Double Flute Flat Ogee Bits - Plunge Type

Series 43000




NAP GLADU Tool Number	r	Cutting Radius	A	Cutting Diameter	B	Cutting Height	Overall Length	
43426		1/8		1		3/8	2	1/4" Shank
43226		1/8		1 3/8		3/8	2 1/4	1/2" Shank



Designed to produce decorative edges or mid-stock decorative grooves. Best for use on natural woods, wood composites and plastics.


Carbide Tipped Double Flute Ogee Fillet Bits with Bearing

Series 43000A



NAP GLADU Tool Number	r	Cutting Radius	A	Cutting Diameter	B	Cutting Height	Overall Length	Index Code
43460		5/32		1 3/8		9/16	2 1/16	L
43260		5/32		1 3/8		9/16	2 1/2	L
43262		1/4		1 5/8		3/4	2 5/8	L

Replacement
Parts - pg 92



This bit is designed to rout a decorative edge where an ogee style is required. This bit is best for use on natural woods, wood composites and plastics.



Series 43000B

Carbide Tipped Double Flute Ogee Fillet Bits with Bearing

Designed to rout a decorative edge where an ogee style is required. This bit is best for use on natural woods, wood composites and plastics.

	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
1/4" Shank	43466	5/32	1 3/8	9/16	2 1/16	T
1/2" Shank	43266	5/32	1 3/8	9/16	2 1/2	T
	43268	1/4	1 5/8	3/4	2 5/8	T

Replacement
Parts - pg 92




Series 43000C

Carbide Tipped Double Flute Ogee Fillet Bits with Bearing

Designed to rout a decorative edge where an ogee style is required. This bit is best for use on natural woods, wood composites and plastics.

	NAP GLADU Tool Number	r1 Cutting Radius	r2	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
1/4" Shank	43470	r1 5/32 r2 5/32		1 1/8	1/2	2	L
	43472	r1 1/4 r2 3/16		1 3/8	11/16	2 3/16	L
1/2" Shank	43270	r1 5/32 r2 5/32		1 1/8	1/2	2 3/8	L
	43272	r1 1/4 r2 3/16		1 3/8	11/16	2 9/16	L

Replacement
Parts - pg 92





Series 43000D

Carbide Tipped Double Flute Ogee Fillet Bits with Bearing

Designed to rout a decorative edge where an ogee style is required. This bit is best for use on natural woods, wood composites and plastics.

	NAP GLADU Tool Number	r1 Cutting Radius	r2	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
1/4" Shank	43476	r1 5/32 r2 5/32		1 1/8	1/2	2	T
	43478	r1 1/4 r2 3/16		1 3/8	11/16	2 3/16	T
1/2" Shank	43276	r1 5/32 r2 5/32		1 1/8	1/2	2 3/8	T
	43278	r1 1/4 r2 3/16		1 3/8	11/16	2 9/16	T


Replacement
Parts - pg 92



Carbide Tipped - Straight and Form Router Bits


Carbide Tipped Double Flute Roman Ogee Fillet Bits with Bearing

Series 43000E



NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
43456	5/32	1	5/8	2 1/16	BB	1/4" Shank
43458	1/4	1 3/8	3/4	2 1/4	BB	
43256	5/32	1	5/8	2 7/16	BB	1/2" Shank
43258	1/4	1 3/8	3/4	2 5/8	BB	

Replacement
Parts - pg 93




This bit is designed to rout a decorative edge where an ogee style is required.

This bit is best for use on natural woods, wood composites and plastics.


Carbide Tipped Double Flute Roman Ogee Fillet Bits with Bearing

Series 43000F



NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
43480	5/32	1	5/8	2 1/16	BB	1/4" Shank
43482	1/4	1 3/8	3/4	2 1/4	BB	
43280	5/32	1	5/8	2 7/16	BB	1/2" Shank
43282	1/4	1 3/8	3/4	2 5/8	BB	

Replacement
Parts - pg 93




This bit is designed to rout a decorative edge where an ogee style is required.

This bit is best for use on natural woods, wood composites and plastics.

Carbide Tipped Double Flute Wavy Ogee Bits with Bearing

Series 43000G



NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
43484	5/32	1 1/4	11/16	2 3/16	L	1/4" Shank
43284	5/32	1 1/4	11/16	2 9/16	L	1/2" Shank




Replacement
Parts - pg 92





This bit is designed to rout a decorative edge where an ogee style is required.

This bit is best for use on natural woods, wood composites and plastics.




Series 43000H		Carbide Tipped Double Flute Flat Cove Bits with Bearing						
Designed to rout a decorative edge where an ogee style is required. This bit is best for use on natural woods, wood composites and plastics.		NAP GLADU Tool Number	r	Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/4" Shank	43486		3/16	1 1/8	1/2	2	L
		43488		5/16	1 3/8	5/8	2 1/8	L
	1/2" Shank	43286		3/16	1 1/8	1/2	2 3/8	L
		43288		5/16	1 3/8	5/8	2 1/2	L
	Replacement Parts - pg 92							



Series 43000I		Carbide Tipped Double Flute Flat Cove Bits with Bearing						
Designed to rout a decorative edge where an ogee style is required. This bit is best for use on natural woods, wood composites and plastics.		NAP GLADU Tool Number	r	Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/4" Shank	43490		3/16	1 1/8	1/2	2	T
		43492		5/16	1 3/8	5/8	2 1/8	T
	1/2" Shank	43290		3/16	1 1/8	1/2	2 3/8	T
		43292		5/16	1 3/8	5/8	2 1/2	T
	Replacement Parts - pg 92							




Series 43000J		Carbide Tipped Double Flute Classical Bits with Bearing						
Designed to rout a decorative edge where an ogee style is required. This bit is best for use on natural woods, wood composites and plastics.		NAP GLADU Tool Number	r1 r2	Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/4" Shank	43400	r1 3/16 r2 1/16		1 1/4	1/2	2 1/16	L
		43402	r1 15/64 r2 9/64		1 1/2	5/8	2 3/32	L
	1/2" Shank	43200	r1 3/16 r2 1/16		1 1/4	1/2	2 3/8	L
		43202	r1 15/64 r2 9/64		1 1/2	5/8	2 1/2	L
	Replacement Parts - pg 92							



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Classical Bits with Bearing

Series 43000K




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
43410	5/32	1 1/8	1/2	2	L	1/4" Shank
43412	7/32	1 3/8	11/16	2 3/16	L	
43210	5/32	1 1/8	1/2	2 3/8	L	1/2" Shank
43212	7/32	1 3/8	11/16	2 9/16	L	

Replacement
Parts - pg 92

These are designed to rout a decorative edge where a classical style is required. Best for use on natural woods, composite woods and plastics.

Carbide Tipped Double Flute Classical Bits with Bearing

Series 43000L




NAP GLADU Tool Number	^r Cutting Radius	^A Cutting Diameter	^B Cutting Height	Overall Length	Index Code	
43416	5/32	1 1/8	1/2	2	T	1/4" Shank
43418	7/32	1 3/8	11/16	2 3/16	T	
43216	5/32	1 1/8	1/2	2 3/8	T	1/2" Shank
43218	7/32	1 3/8	11/16	2 9/16	T	

Replacement
Parts - pg 92

These are designed to rout a decorative edge where a classical style is required. Best for use on natural woods, composite woods and plastics.

Carbide Tipped Double Flute Classic Panel Bits with Bearing

Series 43000M



NAP GLADU Tool Number	^r Cutting Radius	^A Cutting Diameter	^B Cutting Height	Overall Length	Index Code	
43450	3/16	1 1/8	1/2	2	L	1/4" Shank
43452	5/16	1 3/8	5/8	2 1/8	L	
43250	3/16	1 1/8	1/2	2 3/8	L	
43252	5/16	1 3/8	5/8	2 1/2	L	

Replacement
Parts - pg 92

These are designed to rout a decorative edge where a classical style is required. Best for use on natural woods, composite woods and plastics.

Carbide Tipped - Straight and Form Router Bits

Double Flute Flat Bottom Paneling Groover Bits with Upper Bearing

Series 43000R



NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
43438	9/64	7/8	3/8	2	HH	1/4" Shank
43238	13/64	1 3/8	9/16	2 5/8	II	1/2" Shank

Replacement
Parts - pg 93



Made with an upper ban bearing for smooth routing through the centre of natural woods. Leaves a decorative flat bottom design.

Double Flute Rounded Paneling Groover Bits with Upper Bearing

Series 43000S



NAP GLADU Tool Number	r1 Cutting r2 Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
43436	r1 7/32 r2 5/32	7/8	1/2	2	HH	1/4" Shank
43236	r1 13/32 r2 1/4	1 3/8	9/16	2 5/8	II	1/2" Shank


Replacement
Parts - pg 93



Made with an upper ban bearing for smooth routing through the centre of natural woods. Leaves a decorative flat bottom design.

Carbide Tipped Double Flute Door Lip Assembly Bit

Series 45000



NAP GLADU Tool Number	a Bevel Angle	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	
45204	10°	3/8	1 5/8	1	3	1/2" Shank
45206 (upper)	—	3/8	1 9/16	3/8	3/8	5/16" Shank
45207 (lower)	10°	—	1 5/8	7/16	7/16	



This two piece set rounds countertop edges and creates the recess for a cabinet door in one convenient pass. Upper and lower bits can be purchased separately, tool 45204 is the complete assembly.


Series 46000A

Carbide Tipped Double Flute Finger Grip Bits

Designed to rout finger grip recesses
in cabinet doors and drawers.

1/4" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
46420	1/4	3/4	1/4	1 3/4
46422	3/8	1	3/8	1 3/4




Series 46000B

Carbide Tipped Double Flute Finger Grip Bit

Designed to rout finger grip recesses
in cabinet doors and drawers.

1/2" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
46222	3/16	3/4	3/4	2 3/16




Series 46000C

Carbide Tipped Double Flute Finger Grip Bit


Designed to rout finger grip recesses
in cabinet doors and drawers.

1/2" Shank


NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
46220	1/16	7/8	13/16	2 5/16



Carbide Tipped - Straight and Form Router Bits


Carbide Tipped Double Flute Finger Grip Bit						Series 46000D	
	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Designed to rout finger grip recesses in cabinet doors and drawers.	
	46224	15/64	1 1/2	13/16	2 5/16		1/2" Shank
							

Carbide Tipped Double Flute Finger Grip Bit						Series 46000E	
	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Designed to rout finger grip recesses in cabinet doors and drawers.	
	46226	3/16	1 3/4	13/16	2 5/16		1/2" Shank
							

Carbide Tipped Double Flute Finger Grip Bit						Series 46000F	
	NAP GLADU Tool Number	r1 Cutting r2 Radius	A Cutting Diameter	B Cutting Height	Overall Length	Designed to rout finger grip recesses in cabinet doors and drawers.	
	46228	r1 3/16 r2 1/4	2	1 1/4	2 3/4		1/2" Shank
							


Series 11000

Two wing cutter assemblies come complete with cutter, bearing 1314 and arbor 00210 or arbor 00410, excess threads can be removed if necessary. Uses nut 00110 and washer 00100. All replacement parts can be found on pages 94-97. The slot cutter assemblies cut a 1/2" deep slot in all types of wood.



Carbide Tipped Two Wing Slot Cutter Assemblies

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	11406	1 7/8	.062 1/16	2 3/4
	11408	1 7/8	.065	2 3/4
	11412	1 7/8	.075	2 3/4
	11414	1 7/8	.078 5/64	2 3/4
	11420	1 7/8	.093	2 3/4
	11422	1 7/8	.11	2 3/4
	11424	1 7/8	.125 1/8	2 3/4
	11428	1 7/8	.156 5/32	2 3/4
	11430	1 7/8	.187 3/16	2 3/4
1/2" Shank	11432	1 7/8	.25 1/4	2 3/4
	11206	1 7/8	.062 1/16	2 3/8
	11208	1 7/8	.065	2 3/8
	11212	1 7/8	.075	2 3/8
	11214	1 7/8	.078 5/64	2 3/8
	11220	1 7/8	.093 3/32	2 3/8
	11222	1 7/8	.11	2 3/8
	11224	1 7/8	.125 1/8	2 3/8
	11228	1 7/8	.156 5/32	2 3/8
	11230	1 7/8	.187 3/16	2 3/8
	11232	1 7/8	.25 1/4	2 3/8




Series 10000

Two wing carbide tipped replacement cutter for the above assemblies.

Carbide Tipped Two Wing Slot Cutters

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Bore Diameter
10206	1 7/8	.062 1/16	5/16
10208	1 7/8	.065	5/16
10212	1 7/8	.075	5/16
10214	1 7/8	.078 5/64	5/16
10220	1 7/8	.093 3/32	5/16
10222	1 7/8	.11	5/16
10224	1 7/8	.125 1/8	5/16
10228	1 7/8	.156 5/32	5/16
10230	1 7/8	.187 3/16	5/16
10232	1 7/8	.25 1/4	5/16



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Three Wing Slot Cutter Assemblies




NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
11444	1 7/8	.062 1/16	2 3/4
11446	1 7/8	.065	2 3/4
11448	1 7/8	.07	2 3/4
11450	1 7/8	.075	2 3/4
11452	1 7/8	.078 5/64	2 3/4
11454	1 7/8	.085	2 3/4
11458	1 7/8	.093 3/32	2 3/4
11460	1 7/8	.11	2 3/4
11462	1 7/8	.125 1/8	2 3/4
11464	1 7/8	.14	2 3/4
11466	1 7/8	.156 5/32	2 3/4
11468	1 7/8	.187 3/16	2 3/4
11470	1 7/8	.25 1/4	2 3/4
11244	1 7/8	.062 1/16	2 3/8
11246	1 7/8	.065	2 3/8
11248	1 7/8	.07	2 3/8
11250	1 7/8	.075	2 3/8
11252	1 7/8	.078 5/64	2 3/8
11254	1 7/8	.085	2 3/8
11258	1 7/8	.093 3/32	2 3/8
11260	1 7/8	.11	2 3/8
11262	1 7/8	.125 1/8	2 3/8
11264	1 7/8	.14	2 3/8
11266	1 7/8	.156 5/32	2 3/8
11268	1 7/8	.187 3/16	2 3/8
11270	1 7/8	.25 1/4	2 3/8

1/4" Shank


1/2" Shank

Series 11000

Three wing cutter assemblies come complete with cutter, bearing 1314 and arbor 00210 or arbor 00410 – excess threads can be removed if necessary. Uses nut 00110 and washer 00100. All replacement parts can be found on pages 94-97. The slot cutter assemblies cut a 1/2" deep slot in all types of wood.



Carbide Tipped Three Wing Slot Cutters



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Bore Diameter
10306	1 7/8	.062 1/16	5/16
10308	1 7/8	.065	5/16
10310	1 7/8	.07	5/16
10312	1 7/8	.075	5/16
10314	1 7/8	.078 5/64	5/16
10316	1 7/8	.085	5/16
10320	1 7/8	.093 3/32	5/16
10322	1 7/8	.11	5/16
10324	1 7/8	.125 1/8	5/16
10326	1 7/8	.14	5/16
10328	1 7/8	.156 5/32	5/16
10330	1 7/8	.187 3/16	5/16
10332	1 7/8	.25 1/4	5/16

Series 10000

Three wing carbide tipped replacement cutters for the above assemblies.

Series 11000

This two wing multi-slot cutter assembly is supplied with four single cutters of various widths.




1/2" Shank

Quadriset - Multipurpose Slot Cutter Set

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
11290	1 7/8	3.2 mm 1/8"	3	KK
		4.0 mm 5/32"		
		4.8 mm 3/16"		
		6.3 mm 1/4"		

Replacement Parts - pg 93



Series 45000A

This is a convenient tool that routs both the rail and the stile in cabinet door manufacturing. Cutters on the arbor can be flipped to produce the opposite profile.




1/2" Shank

Carbide Tipped 2-Wing Rail and Stile Assembly - 1 Piece Reversible

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	Index Code
45224	1 5/8	1 1/16	3/8	3	JJ

Replacement Parts - pg 93



Series 45000B

This is a convenient tool that routs both the rail and the stile in cabinet door manufacturing. Cutters on the arbor can be flipped to produce the opposite profile.




1/2" Shank

Carbide Tipped 2-Wing Rail and Stile Assembly - 1 Piece Reversible

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	Index Code
45222	1 13/16	1 1/16	1/2	3	JJ

Replacement Parts - pg 93



Carbide Tipped - Straight and Form Router Bits



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	Index Code
45226	1 5/8	1 1/16	3/8	3	JJ

Replacement Parts - pg 93

Series 45000C

This is a convenient tool that routs both the rail and the stile in cabinet door manufacturing. Cutters on the arbor can be flipped to produce the opposite profile.



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	Index Code
45220	1 13/16	1 1/16	1/2	3	JJ

Replacement Parts - pg 93

Series 45000D

This is a convenient tool that routs both the rail and the stile in cabinet door manufacturing. Cutters on the arbor can be flipped to produce the opposite profile.



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	Index Code
45228	1 5/8	1 1/16	3/8	3	JJ

Replacement Parts - pg 93

Series 45000E

This is a convenient tool that routs both the rail and the stile in cabinet door manufacturing. Cutters on the arbor can be flipped to produce the opposite profile.

Series 45000F

Carbide Tipped 2-Wing Rail and Stile Assembly - 2 Piece Reversible

A two piece tool that routs both the rail and stile in cabinet door manufacturing.

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	Index Code
1/2" Shank 45230	1 5/8	1 1/16	3/8	3 5/16	QQ

Replacement Parts - pg 93

Series 45000G

Carbide Tipped 2-Wing Rail and Stile Assembly - 2 Piece Reversible

A two piece tool that routs both the rail and stile in cabinet door manufacturing.

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	Index Code
1/2" Shank 45232	1 5/8	1 1/16	3/8	3 5/16	QQ

Replacement Parts - pg 93

Series 45000H

Carbide Tipped 2-Wing Rail and Stile Assembly - 2 Piece Reversible

A two piece tool that routs both the rail and stile in cabinet door manufacturing.


NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	Index Code
1/2" Shank 45234	1 5/8	1 1/16	3/8	3 5/16	QQ

Replacement Parts - pg 93


Carbide Tipped - Straight and Form Router Bits

Carbide Tipped 2-Wing Sash and Rail Assembly - 1 Piece Reversible

Series 45000




NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	Index Code	
45240	1 3/8	1 7/8	1/4	3 3/4	RR	1/2" Shank
Replacement Parts - pg 93						



This is a convenient tool that routs both the sash and the rail in cabinet door manufacturing. Cutters on the arbor can be flipped to produce the opposite profile.

Carbide Tipped 2-Wing Angular Tongue and Groove Cutter

Series 46000




NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Groove Depth	Overall Length	Index Code	
46240	1 5/8	3/4	3/8	3	KK	1/2" Shank
Replacement Parts - pg 93						



Designed to allow for perfect tongue and groove in stock up to 18 mm. The groove is 1/4" wide and 3/8" deep. Changing arrangement of the assembly produces the counterpart groove or tongue without adjustment of the router height.

Carbide Tipped 2-Wing "V" Panel Set - 1 Piece

Series 45000



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
45250	1 13/16	1 3/16	3	SS	1/2" Shank
Replacement Parts - pg 93					



Designed to create a decorative interlocking groove for wallboard, hardwood flooring and raised panel applications.

Series 45000



Carbide Tipped 2-Wing "C" Panel Set - 1 Piece

This bit is designed to provide a decorative interlocking groove for wallboard, hardwood flooring and raised panel applications.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
45260	1 13/16	1 3/16	3	SS

Replacement
Parts - pg 93



Series 45000



Carbide Tipped 3-Wing Multi-Angle Adjustable Chamfering Set

Fully adjustable set for corner beveling top and bottom in just one pass. Two different corner bevel angles of 30° and 45° rout maximum wood thicknesses of 35 mm for a 30° bevel and 42 mm for a 45° bevel.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	a1 Bevel a2 Angle	Cutting Height min max	Overall Length	Index Code
45290	1 3/8	a1 30° a2 45°	7 mm 35 mm 12 mm 42 mm	4 1/4	TT


Replacement
Parts - pg 93



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped 3-Wing Multi-Radius Adjustable Rounding Over Set


Series 45000



NAP GLADU Tool Number	A Cutting Diameter	r1 Cutting r2 Radius	Cutting min	Height max	Overall Length	Index Code
45280	1 3/8	r1 1/4 r2 3/16	12.7 mm 9.5 mm	38 mm 35 mm	4 1/4	TT

1/2" Shank


Replacement
Parts - pg 93



A fully adjustable set for corner rounding top and bottom simultaneously. Two different corner radii of 1/4" and 3/16" rout a maximum wood thickness of 35 mm for 3/16" radius and 38 mm for 1/4" radius.

Carbide Tipped 3-Wing Adjustable Rounding Over Set


Series 45000



NAP GLADU Tool Number	A Cutting Diameter	r Cutting Radius	Cutting min	Height max	Overall Length	Index Code
45270	1 1/2	3/16	9.5 mm	32 mm	3 5/8	UU
45272	1 5/8	1/4	12.7 mm	32 mm	3 5/8	UU
45274	1 7/8	3/8	12.7 mm	32 mm	3 5/8	UU

1/2" Shank

Replacement
Parts - pg 93



Adjustable sets for corner rounding the top and bottom simultaneously. Wood stock can be routed between the maximum and minimum measurements listed for each bit.

Series 44000

Carbide Tipped Double Flute Raised Panel Bit - Plunge Type

Produces a raised panel effect in the middle of the material.

1/2" Shank

NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length
44200	30°	1 1/8	1/2	2 3/4



Series 44000


Carbide Tipped Double Flute Raised Panel Bit with Bearing

Produces a raised panel in cabinet door manufacturing. Bearing guide provides mar-free routing.

1/2" Shank

NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
44210	25°	1 5/8	3/4	2 1/2	L

Replacement Parts - pg 92



Series 44000

Carbide Tipped Double Flute Raised Panel Bit (French Provincial) - Plunge Type


This bit produces a raised panel effect in the middle of the material.


1/2" Shank


NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length
44202	25°	2 3/4	3/4	2 1/4





Carbide Tipped - Straight and Form Router Bits


Carbide Tipped Double Flute Ogee Fillet Raised Panel Bits with Bearing								Series 44000	
	NAP GLADU Tool Number	r	Cutting Radius	A	Cutting Diameter	B	Cutting Height	Overall Length	Index Code
	44218		3/4		2 5/8		11/16	2 9/16	L
	44220		7/8		3 3/8		5/8	2 1/2	L
								1/2" Shank	
Replacement Parts - pg 92								To produce a raised panel in cabinet door manufacturing. The bearing provides mar-free routing.	

Carbide Tipped Double Flute Classical Raised Panel Bit with Bearing								Series 44000	
	NAP GLADU Tool Number	r	Cutting Radius	A	Cutting Diameter	B	Cutting Height	Overall Length	Index Code
	44222		1/8		2 1/2		1/2	2 3/8	L
								1/2" Shank	
Replacement Parts - pg 92								To produce a raised panel in cabinet door manufacturing. The bearing provides mar-free routing.	


Carbide Tipped Double Flute Cove Raised Panel Bit with Bearing								Series 44000	
	NAP GLADU Tool Number	r	Cutting Radius	A	Cutting Diameter	B	Cutting Height	Overall Length	Index Code
	44226		1 9/16		3 3/8		1/2	2 3/8	L
								1/2" Shank	
Replacement Parts - pg 92								To produce a raised panel in cabinet door manufacturing. The bearing provides mar-free routing.	


Series 44000		Carbide Tipped Double Flute Provincial Raised Panel Bit with Bearing					
To produce a raised panel in cabinet door manufacturing. The bearing provides mar-free routing.		NAP GLADU Tool Number	^a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/2" Shank	44228	15°	3 3/8	1/2	2 3/8	L
		Replacement Parts - pg 92					
							


Series 44000A		Carbide Tipped Double Flute Vertical Raised Panel Bit					
Produces a raised panel in cabinet door manufacturing.		NAP GLADU Tool Number	^a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	
	1/2" Shank	44230	5°	1	1 1/2	2 7/8	
							

Series 44000B		Carbide Tipped Double Flute Vertical Raised Panel Bit					
Produces a raised panel in cabinet door manufacturing.		NAP GLADU Tool Number	^a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	
	1/2" Shank	44232	15°	1 1/8	1 1/2	2 7/8	
							



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Vertical Raised Panel Bit					Series 44000C
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	This bit can be used to produce a raised panel when manufacturing cabinet doors.
	44234	1 1/8	1 1/2	2 7/8	
	1/2" Shank				
					



Carbide Tipped Double Flute Vertical Raised Panel Bit					Series 44000D
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	1/2" Shank
	44236	1 3/16	1 1/2	2 7/8	
					
This bit can be used to produce a raised panel when manufacturing cabinet doors.					

Carbide Tipped Double Flute Glue Joint Bit					Series 46000
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	1/2" Shank
	46230	1 29/64	1 1/8	2 5/8	
					
Designed to rout a lock and key effect in the edge of two pieces of material. This cut provides added strength to the joint when the pieces are glued together.					



Series 46000		Carbide Tipped Double Flute Bevel Glue Joint Set				
A two piece set that will rout both sides of a bevel glue joint.	1/2" Shank	NAP GLADU Tool Number	a Bevel Angle	A1 Cutting A2 Diameter	B1 Cutting B2 Height	Overall Length
		46238	15°	A1 1 1/4 A2 9/16	B1 1 1/4 B2 1/4	2 3/4
		46239	15°	A1 1 1/4 A2 9/16	B1 1 1/4 B2 1/4	2 3/4
		46237	complete set of both bits			

Series 46000 25000		Carbide Tipped Double Flute Spline Glue Joint Set				
Two router bits that will rout both components of a spline glue joint for added strength when joining two pieces of material.	1/2" Shank	NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length
		46235	14°	1 7/64	1 13/16	3 5/16
		25227	14°	7/8	7/8	2 5/8

Series 46000		Carbide Tipped Double Flute Miter Lock Bits				
Designed to rout a staggered lock and key form to the edge of the material. A staggering effect provides added strength to the joint when pieces are joined in a 90° mitre joint.	1/4" Shank	NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length
	1/4" Shank	46432	45°	1 1/2	1/2	1 5/8
	1/2" Shank	46232	45°	1 3/4	3/4	2 1/4
		46234	45°	2 23/32	1 3/16	2 11/16

Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Locking Joint Bits

Series 46000



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
46460	3/4	1/2	1 7/8
46462	1	1/2	1 7/8
46262	1	1/2	1 7/8

1/4" Shank

1/2" Shank

This is designed to create a locking joint for added strength in gluing drawers, table tops and panels.

Carbide Tipped Double Flute Sash Bar Bits

Series 46000



NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
46464	1 1/8	21/32	3/4	1 7/8
46264	1 1/8	21/32	3/4	2 1/2

1/4" Shank

1/2" Shank

This bit is designed to create a decorative locking joint for window grills.

Carbide Tipped Double Flute Ovolo Bits with Bearing

Series 46000



NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length
46474	21/32	1 1/16	11/16	1 7/8
46475	43/64	1 1/16	43/64	2 1/4
46476	11/32	1 5/16	19/32	2 1/4
46274	21/32	1 1/16	11/16	2 1/4

T	1/4" Shank
---	------------


T	1/2" Shank
---	------------

Replacement
Parts - pg 92

This bit is designed to create a decorative locking joint for window grills

Series 46000

Designed to create a decorative locking joint for window grills, etc.




1/4" Shank

Carbide Tipped Double Flute Ovolo Bits with Upper Bearing

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46478	1 3/16	43/64	5/8	2 1/16	A
46480	1 7/16	11/32	15/32	2 1/16	A

Replacement Parts - pg 92



Series 46000


This bit is comprised of a set of five 4 mm kerf and three wing groovers on an arbor. Various super guide bearings allow alternative cutting depths. This bit works on material with a maximum material thickness of 1 9/16".

1/2" Shank

Carbide Tipped Three Wing Jointing Set

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46288	1 7/8	1 3/8	3 3/4	VV

Replacement Parts - pg 93



Series 46000



Designed to create a strong joint by tripling the surface area for gluing. This assembly profiles finger joints in wood thicknesses from 7/16" to 1 3/8". Used for making furniture, board edging, stairs etc.

1/2" Shank

Carbide Tipped Two Wing Finger Joint Set

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46286	1 9/16	1 3/16	3 3/4	WW


Replacement Parts - pg 93



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped 3-Wing Tongue and Groove Jointing Set

Series 46000



NAP GLADU Tool Number	A Cutting Diameter	B1 Cutting B2	Height	Overall Length	Index Code
46284	1 7/8	B1 5/32 B2 5/64	3		XX

1/2" Shank


Replacement Parts - pg 93



Designed to rout a tongue and groove in wood material using two sizes of groovers and super guide bearings to provide smooth joints. Two 5/32" groovers are used to make one half while one 5/64" groover is used to make the other.

Carbide Tipped Double Flute Thumb Nail Bits with Bearing

Series 46000




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46402	15/32	1 3/16	3/8	2 1/16	L
46202	15/32	1 3/16	3/8	2 1/16	L
46204	1 7/8	2 1/2	11/16	2 1/2	L

1/4" Shank

1/2" Shank


Replacement Parts - pg 92



This is made to rout a large decorative radius on the edge of material. Used when a standard corner rounding bit routs a smaller radius than desired.

Carbide Tipped Double Flute Thumb Nail Bits - Beading Type

Series 46000



NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46410	15/32	1 3/16	3/8	2 1/16	T
46210	15/32	1 3/16	3/8	2 1/16	T
46212	1 7/8	2 1/2	11/16	2 1/2	T


1/4" Shank


1/2" Shank



Replacement Parts - pg 92



Designed for the same effect as a standard thumbnail bit, but with a slight bead in the material.

Series 47000D		Carbide Tipped Double Flute Handrail Bit with Bearing				
This bit is designed to rout a decorative edge on handrails, banisters, etc.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/2" Shank	47270	2 5/8	3/4	2 5/8	L
		Replacement Parts - pg 92				
						
						


Series 47000E		Carbide Tipped Double Flute Handrail Bit with Bearing				
This bit is designed to rout a decorative edge on handrails, banisters, etc.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/2" Shank	47272	2 1/2	25/32	2 3/4	L
		Replacement Parts - pg 92				
						
						

Series 47000F		Carbide Tipped Double Flute Handrail Bit with Bearing				
This bit is designed to rout a decorative edge on handrails, banisters, etc.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/2" Shank	47274	2 1/2	25/32	2 3/4	L
		Replacement Parts - pg 92				
						
						

Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Handrail Bit with Bearing

Series 47000G



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
47280	1 1/4	1 1/2	3 3/8	M

1/2" Shank


Replacement Parts - pg 93



This bit is designed to rout a decorative edge on handrails, banisters, etc.

Carbide Tipped Double Flute Handrail Bit with Bearing

Series 47000H



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
47282	1 1/4	1 1/2	3 3/8	M

1/2" Shank


Replacement Parts - pg 93



This bit is designed to rout a decorative edge on handrails, banisters, etc.

Carbide Tipped Double Flute Handrail Bit with Bearing

Series 47000I



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
47284	1 3/8	1 1/2	3 3/8	L

1/2" Shank


Replacement Parts - pg 93



This bit is designed to rout a decorative edge on handrails, banisters, etc.


Sample Profile One

To create this sample profile, use router bit 47282 from page 70 and bit 47272 found on page 69.




Sample Profile Two

To create this sample profile, use router bit 47282 from page 70 and bit 47270 found on page 69.




Sample Profile Three

To create this sample profile, use router bit 47280 from page 70 and bit 47274 found on page 69.




Sample Profile Four

To create this sample profile, use router bit 47284 from page 70 and bit 47272 found on page 69.



Sample Profile Five


To create this sample profile, use router bit 47284 from page 70 and bit 47274 found on page 69.



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Counter Top Bits

Series 46000



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46250	1	7/8	2 7/8	LL
46252	1	1 1/8	3 1/16	LL


Replacement
Parts - pg 93

This bit is designed to rout solid plastic countertop materials and laminates.

1/2" Shank

Carbide Tipped Double Flute Rounding Over Undermount Bowl Bits

Series 46000



NAP GLADU Tool Number	Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46280	1/2	2 1/8	1	3 1/16	MM
46282	9/16	2 1/4	1 1/4	3 15/16	MM


Replacement
Parts - pg 93

This bit is designed to rout solid plastic countertop materials and laminates

1/2" Shank

Carbide Tipped Double Flute Roman Ogee Undermount Bowl Bits

Series 46000



NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46270	1/2	2 1/8	1	3	MM
46272	9/16	2 3/8	1 1/4	3 3/8	MM

Replacement
Parts - pg 93

This bit is designed to rout solid plastic countertop materials and laminates

1/2" Shank

Series 41000



Carbide Tipped Double Flute Rounding Over Bits

This bit is designed to rout solid plastic countertop materials and laminates. A super guide bearing provides a smooth finish in the countertop production.

1/2" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
41290	5/16	1 1/8	1/2	2 15/16	NN
41292	3/8	1 1/4	5/8	2 7/16	NN
41294	1/2	1 1/2	3/4	2 9/16	NN
41296	3/4	2	1	2 3/4	NN

Replacement Parts - pg 93



Series 46000



Carbide Tipped Double Flute Inverted Rounding Over Bits

This bit is designed to rout solid plastic countertop materials and laminates. A super guide bearing provides a smooth finish in the countertop production. When used with the roundover bits above, a complete half circle on countertop edges can be achieved.

1/2" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46276	1/2	2 1/8	3/4	2 1/8	00
46278	3/4	2 5/8	1	2 5/8	00

Replacement Parts - pg 93



Series 46000



Carbide Tipped Double Flute Bevel Undermount Bowl Bit

This bit is designed to rout solid plastic countertop materials and laminates. A super guide bearing provides a smooth finish in the countertop production.

1/2" Shank

NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46260	12°	1 1/4	1	3 3/16	MM

Replacement Parts - pg 93



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Corner Top Bit - No Drip

Series 46000



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
46265	1	1/2	2 1/8

1/2" Shank

Designed for routing solid plastic countertop materials and laminates.

Carbide Tipped Double Flute Topmounted Bowl Bit with Upper Bearing

Series 46000



NAP GLADU Tool Number	^a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46266	12°	1 1/8	1	3 1/8	G

1/2" Shank

This bit is designed to rout solid plastic countertop materials and laminates. The guide bearing provides smooth finish in countertop production.

Carbide Tipped Double Flute Countertop Bit with Upper Bearing

Series 46000



NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46267	12°	1 1/8	1	3 1/8	G

1/2" Shank

This bit is designed to rout solid plastic countertop materials and laminates. The guide bearing provides smooth finish in countertop production.

Series 46000



Carbide Tipped Double Flute Edge Cove Bit with Bearing

These bits are designed to rout solid plastic countertop materials and laminates. The super guide bearing provides a smooth finish in countertop production.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
46268	1	5/8	2 5/8	LL

Replacement Parts - pg 93



Series 31000


Carbide Tipped Double Flute Inlay Trimming Bit with Bearing

These bits are designed to rout solid plastic countertop materials and laminates. The super guide bearing provides a smooth finish in countertop production.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
31256	3/4	1	3	LL

Replacement Parts - pg 93



Series 31000



Carbide Tipped Double Flute Inlay Overhang Trimming Bit with Bearing

These bits are designed to rout solid plastic countertop materials and laminates. The super guide bearing provides a smooth finish in countertop production.

1/2" Shank

NAP GLADU Tool Number	a Bevel Angle	A Cutting Diameter	B Cutting Height	C Laminate Overhang	Overall Length	Index Code
31258	5°	3/4	1	1/16	3	PP

Replacement Parts - pg 93



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped 6-Wing Bowl and Countertop Trim Bit

Series 46000




NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
46269	2 1/16	1/4	3 5/16

1/2" Shank

These are designed to rout solid plastic countertop materials and laminates.

Carbide Tipped Double Flute T-Slot Bits

Series 70000A



NAP GLADU Tool Number	A1 Cutting A2 Diameter	B1 Cutting B2 Height	Overall Length
70300	A1 1 3/32 A2 3/8	B1 13/16 B2 5/16	2 3/8
70200	A1 1 3/32 A2 3/8	B1 13/16 B2 5/16	2 5/8
70202	A1 1 3/8 A2 1/2	B1 7/8 B2 3/8	2 9/16

3/8" Shank

1/2" Shank

These are designed to rout a “T” shaped slot in the material.

Series 70000B


Carbide Tipped Double Flute Rounded T-Slot Bits

These bits are designed to rout a "T" shaped slot in the material.

3/8" Shank

NAP GLADU Tool Number	r Cutting Radius	A1 Cutting A2 Diameter	B1 Cutting B2 Height	Overall Length
70310	5/64	A1 1 1/8 A2 7/16	B1 13/16 B2 5/32	2 1/16
70312	5/64	A1 1 39/64 A2 3/8	B1 13/16 B2 5/32	2 1/16
70210	5/64	A1 1 1/8 A2 7/16	B1 13/16 B2 5/32	2 5/32

1/2" Shank




Series 70000C

Carbide Tipped Double Flute T-Slot Bits

These bits are designed to rout a "T" shaped slot in the material.

1/2" Shank


NAP GLADU Tool Number	A1 Cutting A2 Diameter	B1 Cutting B2 Height	Overall Length
70220	A1 1 3/8 A2 11/32	B1 1/4 B2 17/32	2



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Undercut Bits

Series 72000




NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Cutting Depth	Overall Length
72004	3/4	1/8	1/4	1 7/8
72008	1	1/4	3/8	2

1/4" Shank

These bits are designed to undercut the bottom of a blind pocket or cavity. Ideal for undercutting decorative patterns to give them a bold appearance.

Carbide Tipped Double Flute Undercut Bits with Upper Bearing

Series 72000B



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Cutting Depth	Overall Length	Index Code
72004B	3/4	1/8	1/8	1 7/8	A
72008B	1	1/4	1/4	2	A

1/4" Shank

Replacement
Parts - pg 92


These bits are designed to undercut the bottom of a blind pocket or cavity. Ideal for undercutting decorative patterns to give them a bold appearance.

Series 63000

Designed to bore a hole and rout a “T” shaped slot for built in wall mounting capabilities in plaques and frames.

High Speed Steel Double Flute Keyhole Bits

	NAP GLADU Tool Number	A1 Cutting A2 Diameter	B Cutting Height	Overall Length
1/4" Shank	63410	A1 3/8 A2 3/16	5/16	1 13/16
1/2" Shank	63210	A1 3/8 A2 3/16	5/16	2




Series 63000

Designed to bore a hole and rout a “T” shaped slot for built in wall mounting capabilities in plaques and frames.

Carbide Tipped Single Flute Keyhole Bits

	NAP GLADU Tool Number	A1 Cutting A2 Diameter	B Cutting Height	Overall Length
1/4" Shank	63420	A1 3/8 A2 3/16	3/8	1 1/2
	63422	A1 1/2 A2 5/16	3/8	1 1/2
1/2" Shank	63220	A1 3/8 A2 3/16	7/16	2 1/8
	63222	A1 1/2 A2 5/16	7/16	2 1/8




Series 63000

Designed to bore a hole and rout a “T” shaped slot for built in wall mounting capabilities in plaques and frames.

Solid Carbide Double Flute Keyhole Bit

	NAP GLADU Tool Number	A1 Cutting A2 Diameter	B Cutting Height	Overall Length
1/4" Shank	63430	A1 3/8 A2 3/16	3/8	1 5/8




[illegible]

Carbide Tipped Double Flute Fancy Moulding Bit with Bearing						Series 7500B	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	This bit is made to rout a decorative edge in moulding.	
	75238	1	1 3/4	3 3/4	L		
						1/2" Shank	

Replacement Parts - pg 92



Carbide Tipped Double Flute Fancy Moulding Bit with Bearing						Series 75000C	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	This bit is made to rout a decorative edge in moulding.	
	75240	1	1	2 7/8	L		1/2" Shank
	Replacement Parts - pg 92 						

Series 75000D

Carbide Tipped Double Flute Fancy Moulding Bit with Bearing

This bit is made to rout a decorative edge in moulding.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
75230	7/8	1 1/2	3 3/8	L

Replacement
Parts - pg 92



Series 75000E


Carbide Tipped Double Flute Fancy Moulding Bit with Bearing

This bit is made to rout a decorative edge in moulding.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
75232	1	1 1/2	3 1/2	L

Replacement
Parts - pg 92



Series 75000F


Carbide Tipped Double Flute Fancy Moulding Bit with Bearing

This bit is made to rout a decorative edge in moulding.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
75234	1	1 1/2	3 3/8	L

Replacement
Parts - pg 92




Carbide Tipped - Straight and Form Router Bits


Carbide Tipped Double Flute Edge Forming Bit with Bearing						Series 76000A	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	1/2" Shank	This bit is made to rout a decorative edge in moulding.
	76206	1 3/8	1 3/4	3 5/8	L		
	Replacement Parts - pg 92						
							

Carbide Tipped Double Flute Edge Forming Bit with Bearing						Series 76000B	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	1/2" Shank	This bit is made to rout a decorative edge in moulding.
	76208	1 3/8	1 1/2	3 3/8	M		
	Replacement Parts - pg 92						
							


Carbide Tipped Double Flute Edge Forming Bit with Bearing						Series 76000C	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	1/2" Shank	This bit is designed to rout a decorative edge in moulding.
	76210	2	1 1/4	3 1/8	M		
	Replacement Parts - pg 92						
							

Series 76000D		Carbide Tipped Double Flute Edge Forming Bit with Bearing				
This bit is made to rout a decorative edge in moulding.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/2" Shank	76212	1 3/16	1 3/8	3 1/4	M
		Replacement Parts - pg 92				
		 				

Series 76000E		Carbide Tipped Double Flute Edge Forming Bit with Bearing				
This bit is made to rout a decorative edge in moulding.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/2" Shank	76214	1 3/4	1 1/2	3 7/16	M
		Replacement Parts - pg 92				
		 				

Series 76000F		Carbide Tipped Double Flute Edge Forming Bit with Bearing				
This bit is made to rout a decorative edge in moulding.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
	1/2" Shank	76216	1 3/4	1	3	Y
		Replacement Parts - pg 92				
		 				

Carbide Tipped Double Flute Edge Forming Bit with Bearing						Series 76000G	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	This bit is made to rout a decorative edge in moulding.	
	76218	1 3/4	1	3	L		1/2" Shank
	Replacement Parts - pg 92						

Carbide Tipped Double Flute Edge Forming Bits with Bearing							Series 76000H	
	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	1/2" Shank	This bit is made to rout a decorative edge in moulding.
	76220	15/64	1 1/8	1	2 7/8	M		
	76222	5/16	1 1/4	1 3/16	3 1/8	M		
	76224	33/64	1 3/8	1 9/16	3 1/2	M		
Replacement Parts - pg 92								

Carbide Tipped Double Flute Edge Forming Bit with Bearing						Series 76000I	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	1/2" Shank	This bit is made to rout a decorative edge in moulding.
	76204	1 3/8	1 3/4	3 5/8	L		
							
Replacement Parts - pg 92							

Series 76000J


Carbide Tipped Double Flute Edge Forming Bit with Bearing

This bit is made to rout a decorative edge in moulding.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
76200	1 3/8	1 5/8	3 1/2	L

Replacement Parts - pg 92



Series 76000K


Carbide Tipped Double Flute Edge Forming Bit with Bearing

This bit is made to rout a decorative edge in moulding.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
76202	1 3/8	1 5/8	3 1/2	L

Replacement Parts - pg 92



Series 77000

Carbide Tipped Double Flute Canoe Bits with Bearing

This bit is made to rout a decorative edge in moulding.


1/4" Shank

NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
77490	1/8	1	5/8	2 1/4	L
77492	3/16	1 1/4	1	2 5/8	L



1/2" Shank

77290	1/8	1	5/8	2 5/8	L
77292	3/16	1 1/4	1	2 7/8	L
77294	1/4	2	1 1/4	3 1/8	M

Replacement Parts - pg 92



Carbide Tipped Double Flute Moulding Bit with Bearing							Series 78000A	
	NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	1/2" Shank	
	78260	1/4	2	1	2 7/8	L		
	Replacement Parts - pg 92						This bit is made to rout a decorative edge in moulding.	

Carbide Tipped Double Flute Moulding Bit with Bearing						Series 78000B						
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	This bit is made to rout a decorative edge in moulding.						
	78262	1 1/2	1 3/16	3 1/4	Q							
						1/2" Shank						
						Replacement Parts - pg 92						
												

Carbide Tipped Double Flute Moulding Bit with Bearing						Series 78000C	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	This bit is made to rout a decorative edge in moulding.	
	78264	1 5/8	1 9/16	3 1/2	M		
	Replacement Parts - pg 92					1/2" Shank	
							

Series 78000D


Carbide Tipped Double Flute Moulding Bit with Bearing

This bit is made to rout a decorative edge in moulding.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
78266	1 1/2	1 3/16	3 1/8	M

Replacement
Parts - pg 92



Series 78000E


Carbide Tipped Double Flute Moulding Bit with Bearing

This bit is made to rout a decorative edge in moulding.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
78268	1 3/4	1 3/16	3 3/8	M

Replacement
Parts - pg 92



Series 78000F


Carbide Tipped Double Flute Moulding Bit with Bearing

This bit is made to rout a decorative edge in moulding.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
78270	2 1/4	1	2 7/8	L


Replacement
Parts - pg 92



Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Moulding Bit with Bearing

Series 78000G




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
78272	21/64	2	1 7/32	3 1/8	L

Replacement Parts - pg 92

This bit is made to rout a decorative edge in moulding.

Carbide Tipped Double Flute Moulding Bit with Bearing

Series 78000H




NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
78274	15/64	1 7/8	15/16	2 7/8	L

Replacement Parts - pg 92

This bit is made to rout a decorative edge in moulding.

Carbide Tipped Double Flute Moulding Bit with Bearing


Series 78000I





NAP GLADU Tool Number	r1 Cutting Radius	r2 Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code
78276	r1 1/4	r2 19/64	2 5/16	7/8	2 3/4	L

Replacement Parts - pg 92


This bit is made to rout a decorative edge in moulding.

Series 78000I		Carbide Tipped Double Flute Moulding Bit with Bearing					
This bit is made to rout a decorative edge in moulding.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
	1/2" Shank	78250	1 5/8	1 1/8	3	L	
	Replacement Parts - pg 92						
							

Series 78000K		Carbide Tipped Double Flute Moulding Bits with Bearing						
This bit is made to rout a decorative edge in moulding.		NAP GLADU Tool Number	r1 Cutting Radius r2	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
	1/2" Shank	78252	r1 5/64 r2 5/64	13/16	19/32	2 1/2	M	
		78254	r1 5/32 r2 5/32	1 1/4	7/8	2 3/4	M	
		78256	r1 7/32 r2 15/64	1 9/16	1 3/16	3 1/16	M	
	Replacement Parts - pg 92							
								

Series 78000L		Carbide Tipped Double Flute Moulding Bit with Bearing						
This bit is made to rout a decorative edge in moulding.		NAP GLADU Tool Number	r Cutting Radius	A Cutting Diameter	B Cutting Height	Overall Length	Index Code	
	1/2" Shank	78258	5/32	1 9/16	1 1/16	3	M	
	Replacement Parts - pg 92							
								

Carbide Tipped - Straight and Form Router Bits

Carbide Tipped Double Flute Crown Moulding Bit					Series 79000A
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	This bit is made to rout a decorative edge in moulding.
	79286	1 1/4	2 1/4	3 3/4	1/2" Shank

Carbide Tipped Double Flute Crown Moulding Bit					Series 79000B
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	This bit is made to rout a decorative edge in moulding.
	79288	1 1/4	2 1/4	3 3/4	1/2" Shank

Carbide Tipped Double Flute Crown Moulding Bit					Series 79000C
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	This bit is made to rout a decorative edge in moulding.
	79284	1 1/4	2 1/4	3 3/4	1/2" Shank


Series 79000D

Carbide Tipped Double Flute Crown Moulding Bit

This bit is made to rout a decorative edge in moulding.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
79280	1 1/4	2 1/4	3 3/4




Series 79000E

Carbide Tipped Double Flute Crown Moulding Bit

This bit is made to rout a decorative edge in moulding.

1/2" Shank

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
79282	1 1/4	2 1/4	3 3/4



Carbide Tipped - Straight and Form Router Bits

Router Bit Accessory Index				Parts Listed on Pages 94-97			
Index Code	Bearing Number	Screw Number	Lock Ring Number	Washer Number(s)	Arbor Number	Spacer Number(s)	Nut Number
A	1304	00504	00640	—	—	—	—
B	1307	00504	00640	—	—	—	—
C	1310	00504	00640	—	—	—	—
D	1307 (upper)	00504 (upper)	00640 (upper)	—	—	—	—
	1307 (lower)	00514 (lower)	—	00810 (lower)	—	—	—
E	1312	00504	00610	—	—	—	—
F	1318	00504	00610	—	—	—	—
G	1319	00504	00620	—	—	—	—
H	1322	00504	00620	—	—	—	—
I	1326	00504	00620	—	—	—	—
J	1300	00502	—	—	—	—	—
K	1302	00508	—	00810	—	—	—
				00816			
L	1303	00510	—	00804	—	—	—
				00816			
M	1309	00510	—	00806	—	—	—
				00816			
N	1310	00514	—	00818	—	—	—
O	1316	—	—	—	—	—	—
P	1307	00516	—	—	—	—	—
Q	1310	00514	—	00810	—	—	—
R	1307	00514	—	00810	—	—	—
S	1304	00514	—	00810	—	—	—
T	1302	00510	—	00810	—	—	—
				00816			
U	1324	00512	—	00806	—	—	—
				00816			
V	1320	00512	—	00806	—	—	—
				00816			
W	1315	00512	—	00806	—	—	—
				00816			
X	1311	00512	—	00806	—	—	—
				00816			
Y	1308	00512	—	00806	—	—	—
				00816			
Z	1303	00512	—	00804	—	—	—
				00816			

Router Bit Accessory Index							
				Parts Listed on Pages 94-97			
Index Code	Bearing Number(s)	Screw Number	Lock Ring Number	Washer Number(s)	Arbor Number	Spacer Number(s)	Nut Number
AA	1302	00512	—	00810 00816	—	—	—
BB	1301	00508	—	00802 00814	—	—	—
CC	1314	00504	00640	—	—	—	—
DD	1309	00512	—	00806 00816	—	—	—
EE	1310	00514	—	00806 00818	—	—	—
FF	1309	00510	—	00802 00816	—	—	—
GG	1309	00510	—	00810 00816	—	—	—
HH	1314	—	—	00820	—	—	—
II	1325	—	—	00822	—	—	—
JJ	1314	—	—	—	00214	00702 00704 00708	—
KK	1314	—	—	—	00214	00704 00706 00708 00716	—
LL	1351	00514	—	00818	—	—	—
MM	1352	00514	—	00818	—	—	—
NN	1350	00510	—	00816	—	—	—
OO	1356	00504	00620	—	—	—	—
PP	1353	00514	—	00818	—	—	—
QQ	1314	—	—	—	00220	00702 00704 00708	—
RR	1314	—	—	—	00216	00702 00704 00706 00708 00710 00716	—
SS	1314 1323	—	—	—	00216	00702 00704 00706 00708 00710 00716	—
TT	1314	—	—	—	00222	00704 00706 00708 00710 00716	—
UU	1321	—	—	—	00218	00704 00706 00708 00710 00716	—
VV	1355 1357 1358	—	—	—	00218	00706 00708 00715	—
WW	1321	—	—	—	00218	00704 00706 00708 00712	—
XX	1359 1360	—	—	—	00218	00702 00704 00708 00711 00716	—
YY	1303	—	—	00804 00818	—	—	00112
ZZ	1304 (upper) 1303 (lower) —	00504 (upper) 00510 (lower) —	00640 (upper) — —	— 00804 (lower) 00816 (lower)	— — —	— — —	— — —



Carbide Tipped - Straight and Form Router Bits

Precision Ball Bearings


Series 1300



NAP GLADU Tool Number	X Inside Diameter	Y Outside Diameter	Bearing Thickness
1300	1/8	1/4	7/64
1301	1/8	3/8	5/32
1302	3/16	3/8	1/8
1303	3/16	1/2	5 mm
1304	1/4	1/2	3/16
1305	1/8	1/2	11/64
1306	7 mm	14 mm	5 mm
1306A	8 mm	14 mm	4 mm
1307	1/4	5/8	5 mm
1308	3/16	5/8	5 mm
1309	5 mm	16 mm	5 mm
1309A	8 mm	16 mm	5 mm
1310	1/4	3/4	9/32
1311	3/16	3/4	3/16
1312	1/2	3/4	5/32
1313	6 mm	19 mm	6 mm
1314	5/16	7/8	7 mm
1315	3/16	7/8	6.6 mm
1316	7 mm	22 mm	7 mm
1317	10 mm	1	8 mm
1318	15 mm	1	5.5 mm
1319	1/2	1 1/8	5/16
1320	3/16	1 1/8	6.6 mm
1321	5/16	28 mm	9 mm
1321A	5/16	1 7/32	8.6 mm
1322	15 mm	1 1/4	8.5 mm
1322A	8 mm	1 1/4	5 mm
1323	5/16	1 5/16	8.6 mm
1324	3/16	1 3/8	6.6 mm
1325	15 mm	35 mm	11 mm
1326	15 mm	1 1/2	8.5 mm
1327	15 mm	2	12.5 mm

Super-Guide Precision Ball Bearing Assemblies

Series 1300



NAP GLADU Tool Number	a Bearing Taper	X Inside Diameter	Y Outside Diameter
1350	0°	3/16	1/2
1351	0°	1/4	3/4
1352	10°	1/4	7/8
1353	5°	1/4	7/8
1353A	1/2" radius	1/4	21.4 mm
1353B	3/4" radius	1/4	19.4 mm
1353C	1" radius	1/4	18.5 mm
1353D	5°	1/4	25 mm
1354	0°	1/4	27 mm
1355	0°	5/16	28 mm
1356	0°	15 mm	1 1/8
1357	0°	5/16	29 mm
1358	0°	5/16	34 mm
1359	0°	8 mm	40.8 mm
1360	0°	8 mm	43 mm

These ball bearings are designed with non-marring *Delrin* sleeve for routing solid surface materials.

Series 00500

Screws

	NAP GLADU Tool Number	A Screw Diameter	Overall Length	Use With Allen Key
56 Thread	00502	11/128	7/32	—
48 Thread	00508	2.5 mm	3/8	00906
40 Thread	00504 (headless)	1/8	1/8	00904
	00506 (headless)	1/8	2.5 mm	00904
	00510	1/8	3/8	00908
	00512	1/8	1/2	00908
32 Thread	00514	3/16	1/2	00910
	00516	3/16	1/4	—
	00520 (headless)	3/16	3/16	00908
No Thread	00518	5/32	3/16	00902
	00522	1/4	3/4	00912



Series 00600

Lock Rings

NAP GLADU Tool Number	X Inside Diameter	Use With Screw	Use With Allen Key
00610	1/2	00504	00904
00620	1/2	00504	00904
00630	3/8	00504	00904
00640	1/4	00504	00904





Series 00900


Allen Keys


NAP GLADU Tool Number	A Key Size	Use With Screw	Use With Lock Ring
00902	3 mm	00518	—
00904	1/16	00504	00610 00620 00630 00640
00906	5/64	00508	—
00908	3/32	00512 00510	—
00910	5/32	00514	—
00912	3/16	00522	—




Carbide Tipped - Straight and Form Router Bits

Raised Washers					Series 00800	
	NAP GLADU Tool Number	X	Inside Diameter	Y	Outside Diameter	Washer Thickness
	00802		1/8		3/8	.7 mm
	00804		3/16		1/2	.7 mm
	00806		5 mm		16 mm	.8 mm
Flat Spring Washers					Series 00800	
	NAP GLADU Tool Number	X	Inside Diameter	Y	Outside Diameter	Washer Thickness
	00810		3/16		5/16	1.2 mm
	00812		1/4		3/8	1.4 mm
	00814		7/64		3/16	1/64
	00816		1/8		1/4	1/64
	00818		3/16		3/8	1.0 mm
Lock Washers					Series 00800	
	NAP GLADU Tool Number	X	Inside Diameter		Outside Diameter	Washer Thickness
	00820		3/8		—	.8 mm
	00822		1/2		—	1 mm
Flat Spacers					Series 00700	
	NAP GLADU Tool Number	X	Inside Diameter	Y	Outside Diameter	Spacer Thickness
	00702		5/16		5/8	.05 mm
	00704		5/16		5/8	.1 mm
	00706		5/16		5/8	.5 mm
	00708		5/16		5/8	1 mm
	00710		5/16		5/8	3 mm
	00711		5/16		5/8	3.15 mm
	00712		5/16		16 mm	3.4 mm
	00714		1/4		1/2	5 mm
	00715		5/16		5/8	5.5 mm
	00716		5/16		5/8	6 mm

Series 00100		Nuts and Washers					
	NAP GLADU Tool Number	X Inside Diameter	Y Outside Diameter	Thread Count	Use With Arbor or Router		
Washer	00100	1/2	5/16	—	00210 00216 00410	00214 00218	
Nuts	00110	—	—	—	00210 00216 00410	00214 00218	
	00112	—	—	10-24	31250 31252 31254		

Series 00000		Router Arbors with Nuts and Washers				
	NAP GLADU Tool Number	A Shaft Diameter	B Shaft Height	Overall Length		
1/4" Shank	00410	5/16	1 5/16	2 5/8		
1/2" Shank	00210	5/16	1	2 3/8		
	00214	5/16	1 3/8	3		
	00216	5/16	1 1/2	3 1/8		
	00218	5/16	2 1/8	3 3/4		
	00220	5/16	1 3/4	3 5/16		
	00222	5/16	2 5/8	4 1/4		

Series 00000		CNC Router Arbors				
	NAP GLADU Tool Number	A Shaft Diameter	B Shaft Height	Overall Length		
1/2" Shank	00230	5/16	3/16	2		
	00232	5/16	—	6		

High Speed Steel and and Solid Carbide Router Bits



pg 101



pg 102



pg 103-104



pg 104-105



pg 106-107



pg 108-110



pg 111-113,
117-121
134



pg 112



pg 115-118
132-133



pg 122, 124,
127-129



pg 123-124,
130



pg 131



pg 134-140



pg 136



pg 141



pg 142-143



pg 144



pg 145



pg 145



pg 146



pg 147



pg 147

Accessories	148-149
Ball Nose, Solid Carbide	112
Bottom Cutting, Solid Carbide and High Speed Steel	106-107
Chipbreaker and Finisher, Solid Carbide	122, 124, 127-129
Compression Spiral Bits, Solid Carbide	123-126, 130
Dor-Bits, High Speed Steel	103-104
Dovetails, High Speed Steel	106
Edge Rounding Bits, Solid Carbide	142-143
Fiberglass Router Bits, Solid Carbide	144
High Velocity Spiral Bits, Solid Carbide	131
Latchhole Keyhole Cutter, Solid Carbide	147
Lock-Case Cutter, Solid Carbide	147
"O" Flute Spiral Aluminum Bits, Solid Carbide	136
"O" Flute Spiral Spiral Bits, Solid Carbide	134-140
"O" Flute Straight Bits, High Speed Steel	101
Pilot Bits, High Speed Steel	104-105
Plastic Drills with Special Point	147
Rout and Chamfer Bits, Solid Carbide	141
Saw, Carbide Tipped	145
Saw Arbor, Carbide Tipped	145
Saw, Flush Mounted, Solid Carbide	146
Spiral Bits, High Speed Steel	108-110
Spiral Bits, Solid Carbide	111-113, 117-121, 134
Straight Bits, Solid Carbide	115-119, 132-133
"V" Flute Straight Bits, High Speed Steel	102

Series BC10-00 – BC18-00	101-104
Series BC20-00 – BC28-20	105
Series BC33-00 – BC34-50	149-150
Series BC35-00 – BC38-60	106-107
Series BC40-000 – BC40-550	108-110
Series BC52-000 – BC59-000	112-121
Series BC60-000 – BC60-950	122-132
Series BC61-000 – BC63-900	132-140
Series BC66-000 – BC67-200	142-144
Series BC70-100 – BC90-000	145-147
Series 129-460	148

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits

Router Bit Selection Guide - By Material to be Cut											
	Tool Material	Straight, Single Edge	Straight, Double Edge	Spiral, Single Edge		Spiral, Double Edge		Straight Spiral, Multi-Edge		Shape, Edge Bottom Finish	
Softwood Cedar, Cottonwood, Pine, Redwood	High Speed Steel	BC10-00		BC14-00	BC15-00	BC41-00	BC43-00	BC38-00	BC90-00		
	Solid Carbide	BC61-200 BC61-200	BC56-200	BC62-200	BC63-200	BC52-200 BC52-900 BC57-400	BC52-400 BC57-200 BC57-900	BC60-000 BC60-500M BC60-700	BC60-200 BC60-600 BC60-900	BC16-50 BC38-50 BC90-00	BC37-50 BC52-200B BC52-200BL
Hardwood Ash, Beech, Birch Cherry, Mahogany, Maple, Oak, Poplar, Teak, Walnut	High Speed Steel		BC12-00 BC12-80	BC40-000		BC41-00	BC43-00	BC38-00	BC90-00		
	Solid Carbide	BC61-200	BC56-200	BC60-100M BC60-100SE	BC62-200 BC63-200	BC52-200 BC52-900 BC57-400 BC60-300 BC60-100C BC60-100DE	BC52-400 BC57-200 BC57-900 BC60-400 BC60-950 BC60-100TE	BC60-000 BC60-350 BC60-450 BC60-500 BC60-700 BC60-500M	BC60-200 BC60-430 BC60-470 BC60-600 BC60-900 BC60-100TE	BC16-50 BC38-50 BC90-00	BC37-50 BC52-200B BC52-200BL
Composite Wood MDF, Particle Board, Plywood	Solid Carbide	BC61-200	BC56-200	BC60-100M BC60-100SE	BC62-200 BC63-200	BC52-200 BC52-900 BC57-400 BC60-300 BC60-100C BC60-100DE	BC52-400 BC57-200 BC57-900 BC60-400 BC60-950 BC60-100TE	BC60-000 BC60-430 BC60-470 BC60-600 BC60-900 BC60-500M	BC60-350 BC60-450 BC60-500 BC60-700 BC60-900 BC60-100TE	BC16-50 BC38-50 BC90-00	BC37-50 BC52-200B BC52-200BL
Soft Plastic ABS, Polycarbonate, Polyethylene, PVC, Polypropylene, HDPE, Polystyrene, UHMW, Extruded Acrylic	High Speed Steel	BC10-00 BC11-00	BC11-00					BC70-500			
	Solid Carbide	BC61-00P BC61-400	BC56-430 BC56-600	BC62-750 BC63-750	BC62-850 BC63-850	BC28-20 BC52-200S BC52-400 BC57-600	BC52-600	BC28-20		BC16-50 BC38-50 BC60-000 BC66-200 BC66-300 BC70-200	BC37-50 BC52-200B BC52-200BL BC66-250 BC66-350
Hard Plastic Cast Acrylic, Melamine, Nylon, PVC, Vinyl	High Speed Steel	BC11-00						BC70-500			
	Solid Carbide	BC61-00P BC61-400	BC56-430 BC56-600 BC56-00P BC56-450	BC62-700 BC62-800 BC63-700 BC63-800	BC62-750 BC62-850 BC63-750 BC63-850	BC28-20 BC52-600 BC57-600		BC60-200 BC60-470		BC16-50 BC38-50 BC60-000 BC66-200 BC66-300 BC70-200	BC37-50 BC52-200B BC52-200BL BC66-250 BC66-350
Composite Plastic Fiberglass, Phenolic, Reinforced Acetal	Solid Carbide		BC54-000 BC56-000 BC56-000P BC56-450	BC62-000 BC62-400	BC63-000 BC63-400	BC52-000 BC57-000		BC53-000 BC54-300 BC55-300 BC59-000 BC60-470 BC67-200	BC54-000 BC55-000 BC58-000 BC60-200 BC67-000		
Aluminum	High Speed Steel			BC14-00 BC40-000	BC15-00	BC40-100	BC40-300				
	Solid Carbide			BC62-000 BC62-600 BC63-000 BC63-600	BC62-400 BC62-900 BC63-400 BC63-900	BC52-000	BC57-000			BC66-300 BC66-350	BC52-200B BC52-200BL
Construction Material	High Speed Steel	BC18-00	BC20-00 BC20-10								
Metal Doors	High Speed Steel		BC15-50					BC15-75			
Solid Surface	Solid Carbide		BC56-000P	BC62-700 BC62-800 BC63-700 BC63-800	BC62-750 BC62-850 BC63-750 BC63-850	BC52-000 BC52-400 BC57-200 BC57-600	BC52-200 BC52-600 BC57-400	BC60-200	BC60-470	BC37-50 BC38-50 BC66-000	BC52-200B BC52-200BL
Mortising and Dovetailing	High Speed Steel	BC18-000	BC35-00 BC24-000 BC35-50	BC20-00	BC20-10	BC24-400		BC24-300			
	Solid Carbide		BC60-100M	BC60-100M		BC60-100M		BC60-090	BC60-500M		
Foam	High Speed Steel		BC12-00					BC40-550			
	Solid Carbide		BC56-000P BC56-450								
Laminated and Veneered	Solid Carbide			BC60-100M	BC60-100SE	BC60-100C BC60-100M	BC60-100DE BC60-100MV	BC60-100M BC60-500M BC60-500	BC60-100TE BC60-100MW BC60-600	BC27-00 BC37-50	BC27-50 BC38-50

Series BC10-00

Designed with an open flute design and single edge geometry to provide optimum chip removal at fast feed rates. Best for routing natural woods of soft to medium density and hardness, as well as flexible non-abrasive plastics.

		High Speed Steel Single Edge "O" Flute Straight Bits			
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
1/4" Shank	BC10-00	1/16	3/16	2	
	BC10-01	3/32	3/8	2	
	BC10-02	1/8	3/8	2	
	BC10-20	1/8	1/2	2	
	BC10-03	5/32	1/2	2	
	BC10-04	3/16	5/8	2	
	BC10-22	3/16	3/4	2	
	BC10-05	7/32	5/8	2 1/8	
	BC10-24	1/4	5/8	2 1/8	
	BC10-06	1/4	3/4	2 1/8	
	BC10-07	1/4	1	2 3/8	
	BC10-78	1/4	1 1/4	2 5/8	
5/16" Shank	BC10-18	5/16	1	2 3/8	
3/8" Shank	BC10-09	5/16	1	3	
	BC10-10	3/8	1	2 1/2	
1/2" Shank	BC10-11	3/8	1	2 1/2	
	BC10-13	1/2	1 1/4	2 3/4	

Series BC11-00

Designed with "O" flute geometry for cutting softer, more flexible plastics. Use the single edge for faster feed rates and double edge for a smoother finish. Best for routing ABS, polycarbonate, polystyrene and PVC plastics.

		High Speed Steel Plastic "O" Flute Straight Bits			
	NAP GLADU Tool Number	Edge Count	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC11-01	Single	1/8	1/2	2
	BC11-75*	Single	1/8	5/8	3 1/4
	BC11-03	Single	3/16	5/8	2
	BC11-77*	Single	3/16	3/4	3 1/4
	BC11-05	Single	1/4	3/4	2 1/8
	BC11-71*	Single	1/4	3/4	3 1/4
	BC11-07	Single	1/4	1	2 3/8
	BC11-00	Double	3/16	5/8	2
	BC11-02	Double	1/4	3/4	2 1/8
	BC11-72*	Double	1/4	3/4	3 1/4
	BC11-76	Double	1/4	3/4	3 3/4
	BC11-04	Double	1/4	1	2 3/8
	BC11-78*	Double	1/4	2	3 1/4
3/8" Shank	BC11-09	Single	3/8	1	2 1/2
	BC11-73*	Single	3/8	1	3 1/2
	BC11-06	Double	3/8	1	2 1/2
	BC11-74*	Double	3/8	1	3 1/2
1/2" Shank	BC11-11	Single	1/2	1 1/4	2 3/4
	BC11-10	Double	1/2	1 1/4	2 3/4

*These tools are designed and toleranced for air routers with guide bushings



Single Edge

Double Edge

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits




High Speed Steel Double Edge "V" Flute Straight Bits					Series BC12-00
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC12-30	1/8	3/8	2	1/4" Shank
	BC12-31	5/32	1/2	2	
	BC12-32	3/16	3/4	2	
	BC12-33	7/32	3/4	2	
	BC12-00	1/4	3/4	2 1/8	
	BC12-01	1/4	1	2 3/8	
	BC12-79*	1/4	1	3 1/4	
	BC12-37*	1/4	1 1/4	3 1/4	
	BC12-24	3/8	1	2 1/4	
	BC12-09	1/2	1	2 1/4	
	BC12-25	5/8	3/4	2 1/8	
	BC12-27	3/4	1	2 1/4	
	BC12-03	5/16	1	3	3/8" Shank
	BC12-05	3/8	1	2 1/2	
	BC12-55*	3/8	1	3 1/2	
	BC12-35	1/4	1	2 1/2	1/2" Shank
	BC12-36	5/16	1	2 1/2	
	BC12-06	3/8	1	2 1/2	
	BC12-26	3/8	1 1/4	3 1/4	
	BC12-08	7/16	1 1/4	2 3/4	
	BC12-10	1/2	1 1/4	2 3/4	
	BC12-11	1/2	1 1/2	3 1/2	
	BC12-51	1/2	2	4	
	BC12-12	9/16	1 1/4	2 3/4	
	BC12-13	5/8	1 1/4	2 3/4	
	BC12-14	3/4	1 1/4	2 3/4	
	BC12-16	7/8	1 1/4	2 3/4	
	BC12-17	1	1 1/4	2 3/4	
	BC12-18	1 1/8	1 1/4	2 3/4	
	BC12-19	1 1/4	1 1/4	2 3/4	

*These tools are designed and toleranced for air routers with guide bushings

These bits are designed with "V" flute geometry for smooth finishes in many environments. Best for routing natural woods of medium to high density and hardness, as well as rigid, non-abrasive plastics.



High Speed Steel Double Edge On Shear Straight Bits					Series BC12-80
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC12-86	1/8	3/8	2	1/4" Shank
	BC12-87	3/16	3/4	2	
	BC12-80	1/4	3/4	2 1/8	
	BC12-88	1/4	1	2 3/8	
	BC12-84	3/8	1	2 1/2	3/8" Shank
	BC12-81	5/16	1	2 1/2	1/2" Shank
	BC12-82	3/8	1	2 1/2	
	BC12-83	1/2	1 1/4	2 3/4	
	Shear Angle 3°				

Designed with "V" flute geometry and shearing action to promote longer tool life with desired finish. Best for routing natural woods of medium to hard density and hardness, as well as rigid non-abrasive plastics.

Designed for deep slotting where the upcut action facilitates chip removal or for routing thick stock where the use of a downcut is not practical. Best for routing aluminum and natural woods of soft to medium density and hardness.

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC14-00	1/2	2	4 1/4
BC14-03	1/2	2 1/4	5 1/4
BC14-04	1/2	2 1/2	4 1/4
BC14-05	1/2	2 1/2	5 1/2

Helix Angle 32° 

These bits are designed to rout thick laminated aluminum and wood in construction. These tools can also be used to make straight through cuts in thick stock of either material. Best for routing aluminum, softer materials and metal clad doors.

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC15-00	1/2	2	4 1/4
BC15-02	1/2	2 1/4	4 1/4
BC15-03	1/2	2 1/4	5 1/4
BC15-05	1/2	2 1/2	5 1/2

Helix Angle 18° - 32°



Designed specifically for metal clad doors. Tool geometry facilitates piercing steel and producing superior cuts for door lites and hardware openings. These bits are also available in a titanium coated version for longer life.

NAP GLADU Tool Number	Door Machine	A Cutting Diameter	B Cutting Height	Overall Length
BC15-52	Ruvo	1/2	2 1/4	5 1/4
BC15-53	Ruvo	1/2	2 1/2	5 1/2
BC15-54	Ace	1/2	2 1/2	5
BC15-55*	Falcon	1/2	2 1/2	5 1/2
BC15-57*	Norfield	1/2	2 1/2	5 1/2
BC15-60	Ruvo	1/2	2 1/2	5 1/2
BC15-61*	—	1/2	2 1/2	5 1/2

*Flat edge on shank for locking screws

Helix Angle 18° - 32°



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



High Speed Steel Three Edge CNC Dor-Bits						Series BC15-75
	NAP GLADU Tool Number	Door Machine	A Cutting Diameter	B Cutting Height	Overall Length	1/2" Shank
	BC15-75	Kval	1/2	3	6	
	Helix Angle 18°					
	Designed specifically for machining metal clad doors in a CNC environment. This bit is good for piercing steel and produces a superior cut for door lites and hardware openings. A titanium coated version of this tool is available that will yield a longer life.					

Solid Carbide Single Edge Veining Bits					Series BC16-50
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC16-50	1/16	1/4	1 1/2	
	BC16-51	3/32	1/4	1 1/2	
	BC16-52	1/8	1/4	1 1/2	
1/4" Shank					The tapered edge on these bits allows them to create decorative in natural woods, wood composites, and laminated or veneered plastic.

High Speed Steel Single Edge Straight Pilot Bits					Series BC18-00
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC18-00	1/4	3/4	2 3/4	1/4" Shank
	BC18-02	3/8	7/8	2 7/8	3/8" Shank
	BC18-03	1/2	1	3 1/2	1/2" Shank
Designed for cutting out openings in a diverse combination of materials. Best for routing wood panels, vinyl coated panels, wall board and aluminum layered materials.					

Series BC20-00

Designed with a boring point and spiral flutes to bore through a variety of materials and push chips away from the operator. Best for routing aluminum and plywood sandwich panels, vinyl coated panels, wall board and other layered construction materials.

High Speed Steel Single Edge Downcut Pilot Bits

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC20-00	1/4	3/4	3
3/8" Shank	BC20-02	3/8	1	3 7/16
1/2" Shank	BC20-03	1/2	1 1/4	4

Helix Angle 21°-38°



Series BC20-10

These bits are designed specifically to make cut-outs in drywall. This tool is mainly used in manufactured housing and other onsite construction projects.

High Speed Steel Single Edge Drywall Bits

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/8" Shank	BC20-11	1/8	3/4	2 1/2
1/4" Shank	BC20-10	3/16	1	3 1/4

Helix Angle 30°-41°



Series BC28-20


Designed to trim stacked sheets of plastic and laminates. A double bearing guide ensures smooth cutting action around a template.

Solid Carbide Double Bearing Plastic Trim Bits

	NAP GLADU Tool Number	Edge Count	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC28-20	Double	1/4	3/4	3
1/2" Shank	BC28-25	Double	1/2	1 1/8	4
	BC28-30*	Three	1/2	1 1/8	4

*Upcut | Downcut Compression

Helix Angle 11°-30°



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Right Hand




Left Hand

High Speed Steel Double Edge Dovetail Bits

Series BC35-00 | BC35-50

NAP GLADU Tool Number	Rotation Direction	a Cutting Angle	A1 Cutting A2 Diameter	B Cutting Height	Overall Length
BC35-03	Right	14°2'	A1 3/8 A2 3/16	3/8	1 3/4
BC35-04	Right	9°28'	A1 3/8 A2 1/4	13/32	1 3/4
BC35-51	Left	14°2'	A1 3/8 A2 3/16	3/8	1 3/4
BC35-52	Left	9°28'	A1 3/8 A2 1/4	13/32	1 3/4
BC35-02	Right	17°21'	A1 5/16 A2 5/32	1/4	1 3/4
BC35-06	Right	7°8'	A1 1/2 A2 3/8	9/16	2
BC35-50	Left	17°21'	A1 5/16 A2 5/32	1/4	1 3/4
BC35-05	Right	9°28'	A1 3/8 A2 1/4	13/32	1 7/8
BC35-11	Right	5°43'	A1 5/8 A2 1/2	5/8	2 1/8
BC35-12	Right	9°28'	A1 3/4 A2 1/2	3/4	2 1/4
BC35-13	Right	12°6'	A1 7/8 A2 1/2	7/8	2 3/8
BC35-15	Right	14°2'	A1 1 A2 1/2	1	2 1/2
BC35-53	Left	9°28'	A1 3/8 A2 1/4	13/32	1 7/8



Helix Angle 4°- 8° Shear

Designed for creating right angle dovetail joints. Best for use with natural wood.



BC35-02



BC35-04



BC35-03



BC35-06



BC35-11

Solid Carbide Double Edge "V" Bottom Bits

Series BC37-50


NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC37-50	3/16	5/8	2
BC37-51	1/4	3/4	2
BC37-52	3/8	3/4	2 1/2

Helix Angle 3°- 5° Shear



This bit is designed for "V" grooving or beveling. Best for use with wood, wood composites, laminated and veneered plastics and solid surfaces. Ideal for decorative detailing.

Series BC38-00		High Speed Steel Double Edge Round Bottom Bits			
These round bottom bits are designed with an upshear action for grooving and decorative face cutting. For use on natural wood.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	1/4" Shank	BC38-01	1/8	3/8	2
		BC38-02	3/16	5/8	2
		BC38-03	1/4	3/4	2 1/8
	3/8" Shank	BC38-05	3/8	3/4	2 1/2
	1/2" Shank	BC38-06	1/2	3/4	2 1/4
Helix Angle 3°- 7°					
					
					

Series BC38-50		Solid Carbide Double Edge Round Bottom Bits			
These round bottom bits are designed with an upshear action for grooving and decorative face cutting. For use on natural wood, wood composites, laminated or veneered plastic and solid surfaces.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	1/4" Shank	BC38-50	1/8	3/8	2
		BC38-51	3/16	5/8	2
		BC38-52	1/4	3/4	2
	3/8" Shank	BC38-53	3/8	3/4	2 1/4
	Helix Angle 2°- 4°				
					

Series BC40-100U

Designed to provide a smoother finish than single edge tools when grooving, slotting or blind routing. Recommended for through cuts when fixturing requires upward chip removal. Best for aluminum, natural woods and non-abrasive plastics.

High Speed Steel Double Edge Upcut Spiral Bits				
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC40-101	1/8	3/8	2 5/8
	BC40-103	3/16	5/8	2 7/8
	BC40-153	7/32	7/8	3
	BC40-105	1/4	5/8	2 3/4
	BC40-107	1/4	3/4	2 3/4
	BC40-111*	1/4	1	3
5/16" Shank	BC40-113	5/16	3/4	3
	BC40-115	5/16	1	3
3/8" Shank	BC40-117	5/16	3/4	3
	BC40-119	5/16	1	3
	BC40-131*	3/8	1	3
1/2" Shank	BC40-109	1/4	3/4	3 1/4
	BC40-121	5/16	3/4	3 1/4
	BC40-123	5/16	1	3 1/2
	BC40-133	3/8	1	3 1/2
	BC40-135	3/8	1 1/4	3 3/4
	BC40-143	1/2	1	3
	BC40-137	1/2	1 1/4	3 1/4
	BC40-139	1/2	1 1/2	3 1/2
	BC40-141	3/4	1 1/4	3 1/4

*These tools are designed and toleranced for air routers with guide bushings
Helix Angle 19°-32°



Series BC40-100D

Designed to provide a smoother finished cut than single edge tools in trimming, sizing and plunging operations. These are recommended when chip flow should be directed down to protect the material's top finish. Best for routing in aluminum, natural woods and non-abrasive plastics.

High Speed Steel Double Edge Downcut Spiral Bits				
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC40-102	1/8	5/16	2 5/8
	BC40-104	3/16	5/8	2 7/8
	BC40-106	1/4	5/8	2 3/4
	BC40-108	1/4	3/4	2 3/4
	BC40-112	1/4	1	3
	BC40-158	1/4	1	3 1/4
5/16" Shank	BC40-114	5/16	3/4	3
	BC40-116	5/16	1	3
3/8" Shank	BC40-132	3/8	1	3
	BC40-130	3/8	1	3 1/2
1/2" Shank	BC40-110	1/4	3/4	3 1/4
	BC40-122	5/16	3/4	3 1/4
	BC40-124	5/16	1	3 1/2
	BC40-134	3/8	1	3 1/2
	BC40-136	3/8	1 1/4	3 3/4
	BC40-144	1/2	1	3
	BC40-138	1/2	1 1/4	3 1/4
	BC40-140	1/2	1 1/2	3 1/2
	BC40-142	3/4	1 1/4	3 1/4

*These tools are designed and toleranced for air routers with guide bushings
Helix Angle 19°-32°



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



High Speed Steel Double Edge Spiral Wood Rout Bits

Series BC40-300



NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length
BC40-301S	Upcut	1/8	1/2	2 5/8
BC40-303S	Upcut	3/16	3/4	2 7/8
BC40-307H	Upcut	1/4	7/8	2 3/4
BC40-307S	Upcut	1/4	7/8	2 3/4
BC40-311S	Upcut	1/4	1 1/8	3
BC40-302S	Downcut	1/8	1/2	2 5/8
BC40-304S	Downcut	3/16	3/4	2 7/8
BC40-308H	Downcut	1/4	7/8	2 3/4
BC40-308S	Downcut	1/4	7/8	2 3/4
BC40-312S	Downcut	1/4	1 1/8	3
BC40-333H	Upcut	3/8	1 1/8	3
BC40-333S	Upcut	3/8	1 1/8	3
BC40-334H	Downcut	3/8	1 1/8	3
BC40-334S	Downcut	3/8	1 1/8	3
BC40-335H	Upcut	3/8	1 1/4	3 1/4
BC40-335S	Upcut	3/8	1 1/4	3 1/4
BC40-343H	Upcut	1/2	1 1/8	3
BC40-343S	Upcut	1/2	1 1/8	3
BC40-339H	Upcut	1/2	1 5/8	3 1/2
BC40-339H	Upcut	1/2	1 5/8	3 1/2
BC40-336H	Downcut	3/8	1 1/4	3 1/4
BC40-336S	Downcut	3/8	1 1/4	3 1/4
BC40-344H	Downcut	1/2	1 1/8	3
BC40-344S	Downcut	1/2	1 1/8	3
BC40-340H	Downcut	1/2	1 5/8	3 1/2
BC40-340S	Downcut	1/2	1 5/8	3 1/2

1/4" Shank

3/8" Shank

1/2" Shank

These are designed with double edge geometry for cutting either hard or soft woods. This bit has an improved tool life and an excellent finish. Best for routing natural woods, plastics and aluminum.

* Special Point

Helix Angle 21°-32°

S Soft Wood
H Hard Wood



High Speed Steel Four Edge Upcut Spiral Bits

Series BC40-550



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC40-562	1/2	3 5/8	6
BC40-564	1/2	4 1/8	6 1/2

1/2" Shank

Helix Angle 25°

This bit is designed to cut thick foam with an upward chipflow.

Series BC52-200

Designed to rout wood and wood composites where upward chip removal, long life and quality finish are desired. Best for routing wood, wood composites and plastics.

Solid Carbide Double Edge Upcut Spiral Wood Rout Bits

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/8" Shank	BC52-244	1/8	1/2	2
3/16" Shank	BC52-264	3/16	3/4	2
1/4" Shank	BC52-240	1/8	1/2	2
	BC52-240L	1/8	1/2	2
	BC52-251	5/32	1/2	2 1/2
	BC52-250	5/32	5/8	2
	BC52-260	3/16	3/4	2
	BC52-260L	3/16	3/4	2
	BC52-261	3/16	3/4	2 1/2
	BC52-270	7/32	3/4	2 1/2
	BC52-271	7/32	1	2 1/2
	BC52-280	1/4	7/8	2 1/2
	BC52-281S	1/4	7/8	2 1/2
	BC52-285	1/4	1	2 1/2
	BC52-285L	1/4	1	2 1/2
	BC52-287	1/4	1 1/8	3
5/16" Shank	BC52-290	9/32	1	2 1/2
	BC52-300	5/16	1 1/8	3
3/8" Shank	BC52-318*	3/8	1	3
	BC52-320	3/8	1 1/8	3
	BC52-321S	3/8	1 1/8	3
	BC52-325	3/8	1 1/4	3
	BC52-325L	3/8	1 1/4	3
1/2" Shank	BC52-310	5/16	1 1/8	3
	BC52-310L	5/16	1 1/8	3
	BC52-330	3/8	1 1/4	3
	BC52-340	7/16	1	3
	BC52-360	1/2	1 1/8	3
	BC52-361S	1/2	1 1/8	3
	BC52-362	1/2	1 1/4	3 1/2
	BC52-365	1/2	1 5/8	3 1/2
	BC52-365L	1/2	1 5/8	3 1/2
	BC52-366S	1/2	1 5/8	3 1/2
	BC52-367	1/2	2 1/8	4
	BC52-370	17/32	1 1/8	3
5/8" Shank	BC52-380	5/8	1 5/8	3 1/2
	BC52-385	5/8	2 1/8	4
	BC52-385L	5/8	2 1/8	4
3/4" Shank	BC52-390	3/4	1 5/8	4
	BC52-395	3/4	2 1/8	4
	BC52-395L	3/4	2 1/8	4

*Special Point

Helix Angle 30°

L Left Hand Rotation
S Soft Wood



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Double Edge Upcut Spiral Bits

Series BC52-000



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC52-040	1/8	1/2	2
BC52-050	5/32	9/16	2
BC52-060	3/16	5/8	2
BC52-060L	3/16	5/8	2
BC52-070	7/32	5/8	2 1/2
BC52-080	1/4	3/4	2 1/2
BC52-080L	1/4	3/4	2 1/2
BC52-090	9/32	3/4	2 1/2
BC52-100	5/16	13/16	2 1/2
BC52-120	3/8	7/8	2 1/2
BC52-140	7/16	1	3
BC52-160	1/2	1	3

L Left Hand Rotation

1/4" Shank

3/8" Shank

1/2" Shank

This bit is designed as a general purpose tool with upward chip flow. Solid carbide gives this bit a longer tool life than high speed steel. Best for sign-making and cutting as well as routing wood, non-ferrous, abrasive materials and aluminum.



Solid Carbide Double Edge Upcut Spiral Ball Nose Bits

Series BC52-200B



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC52-240B	1/8	1/2	2
BC52-260B	3/16	3/4	2
BC52-280B	1/4	7/8	2 1/2
BC52-320B	3/8	1 1/8	3
BC52-360B	1/2	1 1/8	3

Helix Angle 30°




This bit is designed for accurate, smooth three-dimensional carving or routing on CNC routers. Best for routing natural wood and plastics.



Solid Carbide Double Edge Upcut Extended Length Ball Nose Bits

Series BC52-200BL



NAP GLADU Tool Number	Cutting Diameter	Cutting Height	Overall Length
BC52-240BL	1/8	1/2	3
BC52-260BL	3/16	3/4	3
BC52-280BL	1/4	1	4
BC52-320BL	3/8	1 1/4	4
BC52-360BL	1/2	1 1/2	5

Helix Angle 30°



This bit is designed for accurate, smooth three-dimensional carving or routing on CNC routers. Best for routing natural wood and plastics.

Series BC52-400

These bits are designed to rout wood and wood composites where upward chip removal, long life and quality finish are desired. Best for routing wood, wood composites and plastics.

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
6 mm Shank	BC52-410	4 mm	16 mm	64 mm
	BC52-411	5 mm	20 mm	64 mm
	BC52-412	6mm	25 mm	64 mm
8 mm Shank	BC52-414	8 mm	25 mm	64 mm
10 mm Shank	BC52-416	10 mm	35 mm	76 mm
12 mm Shank	BC52-418	12 mm	35 mm	76 mm
14 mm Shank	BC52-420	14 mm	50 mm	88 mm
16 mm Shank	BC52-422	16 mm	55 mm	100 mm
18 mm Shank	BC52-424	18 mm	60 mm	120 mm
20 mm Shank	BC52-426	20 mm	60 mm	120 mm

Helix Angle 30°



Series BC52-600

Designed to cut acrylic with a smooth finish and upward chip flow. Best for routing acrylic and rigid plastics.

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC52-622	1/4	3/8	2 1/2
	BC52-624	1/4	3/4	2 1/2
3/8" Shank	BC52-638	3/8	1	3
1/2" Shank	BC52-650	1/2	1 1/8	3 1/2
6 mm Shank	BC52-626	6 mm	25 mm	64 mm
8 mm Shank	BC52-640	8 mm	25 mm	76 mm
10 mm Shank	BC52-642	10 mm	25 mm	76 mm
12 mm Shank	BC52-644	12 mm	35 mm	88 mm

Helix Angle 30°



Series BC52-900

Designed for demanding applications where upward chip removal, tool rigidity and long life are required.

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC52-910	1/4	7/8	2 1/2
3/8" Shank	BC52-923	3/8	1 1/8	3
	BC52-924	3/8	1 1/4	3
1/2" Shank	BC52-936	1/2	1 1/4	3

Helix Angle 30°



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Three Edge Straight Bits

Series BC53-000



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC53-040	1/8	1/2	2
BC53-080	1/4	3/4	2 1/2

1/4" Shank

Designed to rout extremely hard materials. Also recommended to be used when the spindle RPM is lower than normal for routing. This bit is best for routing titanium or hard metal, plastic composites and other composite materials.



Solid Carbide Four Edge Downcut Spiral Bits

Series BC54-300



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC54-320	3/8	5/8	3
BC54-325	3/8	1 1/8	3
BC54-360	1/2	5/8	3 1/2
BC54-365	1/2	1 1/8	3 1/2

3/8" Shank

1/2" Shank


Helix Angle 30°

Designed to work with either low or high speed spindle applications in any CNC machining environment. Free cutting action provides better finishes; best for use on fiberglass.



Solid Carbide Four Edge Upcut Spiral Bits

Series BC55-300



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC55-320	3/8	5/8	3
BC55-325	3/8	1 1/8	3
BC55-360	1/2	5/8	3 1/2
BC55-365	1/2	1 1/8	3 1/2

3/8" Shank

1/2" Shank

Helix Angle 30°

Designed to work with either low or high speed spindle applications in any CNC machining environment. Free cutting action provides better finishes; best for use on fiberglass.

Series BC56-000G

These are designed as a general purpose tool for routing difficult to cut materials, particularly in small diameters. Best for routing wood composites, thin laminated materials and other composite materials.

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC56-040	1/8	1/2	2
	BC56-050	5/32	9/16	2
	BC56-060	3/16	5/8	2
	BC56-070	7/32	5/8	2 1/2
	BC56-080	1/4	3/4	2 1/2
	BC56-084*	1/4	3/4	3 1/4
3/8" Shank	BC56-090	9/32	3/4	2 1/2
	BC56-100	5/16	13/16	2 1/2
	BC56-120	3/8	7/8	2 1/2
1/2" Shank	BC56-140	7/16	1	3
	BC56-160	1/2	1	3

*These tools are designed and toleranced for air routers with guide bushings



Series BC56-000P

Designed to rout harder, more rigid plastics. Best for routing plastics in the acrylic, nylon, melamine and rigid PVC formulations.

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC56-041	1/8	1/4	2
	BC56-061	3/16	3/8	2
	BC56-062	3/16	5/8	2
	BC56-062L	3/16	5/8	2
	BC56-063*	3/16	5/8	4
	BC56-081	1/4	3/8	2 1/2
	BC56-082	1/4	3/4	2 1/2
	BC56-082L	1/4	3/4	2 1/2
	BC56-086*	1/4	1 1/4	4
3/8" Shank	BC56-121	3/8	5/8	2 1/2
	BC56-122	3/8	7/8	2 1/2
	BC56-122L	3/8	7/8	2 1/2
	BC56-124*	3/8	1 5/8	6
1/2" Shank	BC56-162	1/2	1	3
	BC56-162L	1/2	1	3
	BC56-164	1/2	2 1/8	6

*These tools are designed and toleranced for air routers with guide bushings
L Left Hand Rotation



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Double Edge Straight Wood Rout Bits					Series BC56-200	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length		Designed to provide a superior finish in a variety of materials and provide optimum cutter life. Best for routing wood and wood composites, as well as, abrasive plastics and composites.
	BC56-240	1/8	1/2	2	1/4" Shank	
	BC56-250	5/32	5/8	2		
	BC56-260	3/16	3/4	2		
	BC56-270	7/32	3/4	2 1/2		
	BC56-280	1/4	7/8	2 1/2		
	BC56-281S	1/4	7/8	2 1/2		
	BC56-285	1/4	1	2 1/2		
	BC56-287	1/4	1 1/8	3		
	BC56-290	9/32	1	2 1/2	5/16" Shank	
	BC56-300	5/16	1 1/8	3		
	BC56-320	3/8	1 1/8	3	3/8" Shank	
	BC56-321S	3/8	1 1/8	3		
	BC56-325	3/8	1 1/4	3		
	BC56-310	5/16	1 1/8	3	1/2" Shank	
	BC56-330	3/8	1 1/4	3		
	BC56-340	7/16	1	3		
	BC56-360	1/2	1 1/8	3		
	BC56-361S	1/2	1 1/8	3		
	BC56-362	1/2	1 1/4	3 1/2		
	BC56-365	1/2	1 5/8	3 1/2		
	BC56-366S	1/2	1 5/8	3 1/2		
	BC56-370	17/32	1 1/8	3		
	BC56-385	5/8	2 1/8	4	5/8" Shank	
	BC56-390	3/4	1 5/8	4	3/4" Shank	
	BC56-395	3/4	2 1/8	4		

S Soft Wood



Solid Carbide Double Edge Straight “V” Flute Bits					Series BC56-400	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length		Designed to rout harder, more rigid plastics. Best for routing wood composites, thin laminated materials, plastics in the acrylic, nylon, melamine and rigid PVC families and other composite materials.
	BC56-410	4 mm	16 mm	64 mm	6 mm Shank	
	BC56-411	5 mm	20 mm	64 mm		
	BC56-412	6 mm	25 mm	64 mm		
	BC56-414	8 mm	25 mm	64 mm	8 mm Shank	
	BC56-416	10 mm	35 mm	76 mm	10 mm Shank	
	BC56-418	12 mm	35 mm	76 mm	12 mm Shank	

Series BC56-430		Solid Carbide Double Edge Straight "O" Flute Bits			
Designed with free cutting "O" flute geometry and a double flute design for smooth finishes.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	6 mm Shank	BC56-430	4 mm	16 mm	64 mm
		BC56-431	5 mm	20 mm	64 mm
		BC56-432	6 mm	25 mm	64 mm
	8 mm Shank	BC56-434	8 mm	25 mm	76 mm
	10 mm Shank	BC56-436	10 mm	35 mm	88 mm
	12 mm Shank	BC56-438	12 mm	35 mm	88 mm



Series BC56-450		Solid Carbide Double Edge Straight Bits			
Designed specifically to rout harder, more rigid plastics. Best for use on phenolic, acrylic, nylon, PVC, ABS, acetal and solid surface.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	6 mm Shank	BC56-450	4 mm	16 mm	64 mm
		BC56-451	5 mm	20 mm	64 mm
		BC56-452	6 mm	25 mm	64 mm
	8 mm Shank	BC56-454	8 mm	25 mm	76 mm
	10 mm Shank	BC56-456	10 mm	35 mm	88 mm
	12 mm Shank	BC56-458	12 mm	35 mm	88 mm



Series BC57-000		Solid Carbide Double Edge Downcut Spiral Bits			
Designed as a general purpose tool with downward chip flow. Solid carbide gives this bit a longer tool life than high speed steel. Best for routing hard or abrasive materials and aluminum.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	1/4" Shank	BC57-040	1/8	1/2	2
		BC57-050	5/32	9/16	2
		BC57-060	3/16	5/8	2
		BC57-070	7/32	5/8	2 1/2
		BC57-080	1/4	3/4	2 1/2
	3/8" Shank	BC57-090	9/32	3/4	2 1/2
		BC57-100	5/16	13/16	2 1/2
		BC57-120	3/8	7/8	2 1/2
	1/2" Shank	BC57-140	7/16	1	3
		BC57-160	1/2	1	3

Helix Angle 30°



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Double Edge "O" Flute Straight Bits

Series BC56-600

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC56-610	1/8	5/16	2	1/4" Shank
	BC56-612	1/8	1/2	2	
	BC56-614	1/8	5/8	4	
	BC56-616	3/16	3/8	2	
	BC56-618	3/16	5/8	2	
	BC56-620	3/16	1	4	
	BC56-624	1/4	3/8	2 1/2	
	BC56-625	1/4	1	2 1/2	
	BC56-625L	1/4	1	2 1/2	3/8" Shank
	BC56-626	1/4	1	3 1/4	
	BC56-628	1/4	1 1/4	4	
	BC56-638	3/8	7/8	2 1/2	1/2" Shank
	BC56-639	3/8	1	4	
	BC56-650	1/2	1	3	1/2" Shank
	BC56-652	1/2	1	4	
	BC56-654	1/2	1 3/4	4	
BC56-655	1/2	2 1/8	6		

These are designed with free cutting "O" flute geometry and a double flute for a smooth finish in soft flexible plastics. Best for routing plastics in the ABS, polycarbonate, polystyrene and ductile PVC formulations.

L Left Hand Rotation



Solid Carbide Downcut Spiral Wood Rout Bits for Upholstery

Series BC57-300

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC57-324	3/8	3/4	2 1/2	3/8" Shank
	BC57-322	3/8	7/8	3	
	BC57-326	3/8	1	2 1/2	
	BC57-323	3/8	1 1/4	3	

Designed with free cutting "O" flute geometry along with a double flute design for a smooth finish.

Series BC57-200

These are designed to rout wood and wood composites where downward chip removal, long life and quality finish are desired. These are best for routing wood, wood composites and plastics.

Solid Carbide Double Edge Downcut Spiral Wood Rout Bits

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/8" Shank	BC57-244	1/8	1/2	2
3/16" Shank	BC57-264	3/16	3/4	2
1/4" Shank	BC57-240	1/8	1/2	2
	BC57-240L	1/8	1/2	2
	BC57-251	5/32	1/2	2 1/2
	BC57-250	5/32	5/8	2
	BC57-260	3/16	3/4	2
	BC57-260L	3/16	3/4	2
	BC57-261	3/16	3/4	2 1/2
	BC57-270	7/32	3/4	2 1/2
	BC57-271	7/32	1	2 1/2
	BC57-280	1/4	7/8	2 1/2
	BC57-281S	1/4	7/8	2 1/2
	BC57-285	1/4	1	2 1/2
	BC57-285L	1/4	1	2 1/2
	BC57-287	1/4	1 1/8	3
5/16" Shank	BC57-290	9/32	1	2 1/2
	BC57-300	5/16	1 1/8	3
3/8" Shank	BC57-318*	3/8	1	3
	BC57-320	3/8	1 1/8	3
	BC57-321S	3/8	1 1/8	3
	BC57-325	3/8	1 1/4	3
	BC57-325L	3/8	1 1/4	3
1/2" Shank	BC57-310	5/16	1 1/8	3
	BC57-310L	5/16	1 1/8	3
	BC57-330	3/8	1 1/4	3
	BC57-340	7/16	1	3
	BC57-360	1/2	1 1/8	3
	BC57-361S	1/2	1 1/8	3
	BC57-362	1/2	1 1/4	3 1/2
	BC57-365	1/2	1 5/8	3 1/2
	BC57-365L	1/2	1 5/8	3 1/2
	BC57-366S	1/2	1 5/8	3 1/2
	BC57-367	1/2	2 1/8	4
	BC57-370	17/32	1 1/8	3
5/8" Shank	BC57-380	5/8	1 5/8	3 1/2
	BC57-385	5/8	2 1/8	4
	BC57-385L	5/8	2 1/8	4
3/4" Shank	BC57-390	3/4	1 5/8	4
	BC57-395	3/4	2 1/8	4
	BC57-395L	3/4	2 1/8	4



*Special Point

Helix Angle 30°

L Left Hand Rotation
S Soft Wood

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Double Edge Downcut Spiral Wood Rout Bits

Series BC57-400

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
BC57-410	4 mm	16 mm	64 mm	6 mm Shank
BC57-411	5 mm	20 mm	64 mm	
BC57-412	6 mm	25 mm	64 mm	
BC57-414	8 mm	25 mm	64 mm	8 mm Shank
BC57-416	10 mm	35 mm	76 mm	10 mm Shank
BC57-418	12 mm	35 mm	76 mm	12 mm Shank
BC57-420	14 mm	50 mm	88 mm	14 mm Shank
BC57-422	16 mm	55 mm	100 mm	16 mm Shank
BC57-424	18 mm	60 mm	120 mm	18 mm Shank
BC57-426	20 mm	60 mm	120 mm	20 mm Shank

Designed to rout wood and wood composites where downward chip removal, long life and quality finish are desired. Best for routing wood, wood composites and plastics.



Solid Carbide Double Edge Downcut Spiral Bits - Plastic

Series BC57-600

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
BC57-623	1/4	3/8	2 1/2	1/4" Shank
BC57-625	1/4	3/4	2 1/2	
BC57-637	3/8	1	3	3/8" Shank
BC57-651	1/2	1 1/8	3 1/2	1/2" Shank
BC57-627	6 mm	25 mm	64 mm	6 mm Shank
BC57-639	8 mm	25 mm	76 mm	8 mm Shank
BC57-643	10 mm	25 mm	76 mm	10 mm Shank
BC57-645	12 mm	35 mm	88 mm	12 mm Shank

Helix Angle 11°

Designed to cut acrylic with a smooth finish and downward chip flow. Best for routing acrylic and rigid plastics.



Solid Carbide Double Edge Downcut Extreme Heavy Duty Standard

Series BC57-900

NAP GLADU Tool Number	Cutting Diameter	Cutting Height	Overall Length	
BC57-910	1/4	7/8	2 1/2	1/4" Shank
BC57-921	3/8	7/8	3	
BC57-923	3/8	1 1/8	3	3/8" Shank
BC57-924	3/8	1 1/4	3	
BC57-936	1/2	1 1/4	3	1/2" Shank

Helix Angle 30°

Designed for routing where extreme loads are placed upon the cutting tools and when extra part hold down is required.

Series BC58-000 BC55-000		Solid Carbide Multi-Edge Upcut Spiral Bits					
Designed to rout difficult to cut materials when horsepower or spindle speed may be a problem. Best for routing fiberglass, composite materials, laminates and other man-made abrasive materials.	1/4" Shank	NAP GLADU Tool Number	Edge Count	A Cutting Diameter	B Cutting Height	Overall Length	
		BC58-040	Three	1/8	1/2	2	
		BC58-060	Three	3/16	5/8	2	
		BC58-080	Three	1/4	3/4	2 1/2	
		BC55-040	Four	1/8	1/2	2	
		BC55-050	Four	5/32	9/16	2	
		BC55-060	Four	3/16	5/8	2	
		BC55-080	Four	1/4	3/4	2 1/2	
Series BC58-000, Helix Angle 30° Series BC55-000, Helix Angle 15°							 Three Edge Four Edge

Series BC59-000 BC54-000		Solid Carbide Multi-Edge Downcut Spiral Bits					
Designed to rout difficult to cut materials when horsepower or spindle speed may be a problem. Best for routing fiberglass, composite materials and other man-made abrasive materials.		NAP GLADU Tool Number	Edge Count	A Cutting Diameter	B Cutting Height	Overall Length	
	1/4" Shank	BC59-040	Three	1/8	1/2	2	
		BC59-060	Three	3/16	5/8	2	
		BC59-080	Three	1/4	3/4	2 1/2	
		BC54-040	Four	1/8	1/2	2	
		BC54-050	Four	5/32	9/16	2	
		BC54-060	Four	3/16	5/8	2	
		BC54-080	Four	1/4	3/4	2 1/2	
	6 mm Shank	BC59-440	Three	3 mm	12 mm	64 mm	
		BC59-460	Three	5 mm	16 mm	64 mm	
		BC59-480	Three	6 mm	19 mm	76 mm	
		BC54-440	Four	3 mm	12 mm	64 mm	
		BC54-460	Four	5 mm	16 mm	64 mm	
		BC54-480	Four	6 mm	19 mm	76 mm	
Helix Angle 30°							

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Three Edge High Helix Chipbreaker Bits						Series BC60-000
	NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length	
	BC60-001	Upcut	3/8	1 1/8	3 1/2	3/8" Shank
	BC60-002	Downcut	3/8	1 1/8	3 1/2	
	BC60-005	Upcut	1/2	1 1/8	3 1/2	1/2" Shank
	BC60-007	Upcut	1/2	1 5/8	4	
	BC60-006	Downcut	1/2	1 1/8	3 1/2	
	BC60-008	Downcut	1/2	1 5/8	4	
	BC60-009	Upcut	5/8	1 5/8	4	5/8" Shank
	BC60-011	Upcut	5/8	2 1/8	5	
	BC60-010	Downcut	5/8	1 5/8	4	
	BC60-012	Downcut	5/8	2 1/8	5	
	BC60-017	Upcut	3/4	1 5/8	4	3/4" Shank
	BC60-019	Upcut	3/4	2 1/8	5	
	BC60-018	Downcut	3/4	1 5/8	4	
	BC60-020	Downcut	3/4	2 1/8	5	
	BC60-003	Upcut	12 mm	25 mm	76 mm	12 mm Shank
	BC60-004	Downcut	12 mm	25 mm	76 mm	
	BC60-013	Upcut	16 mm	55 mm	120 mm	16 mm Shank
	BC60-014	Downcut	16 mm	55 mm	120 mm	
	BC60-015	Upcut	18 mm	60 mm	120 mm	18 mm Shank
	BC60-016	Downcut	18 mm	60 mm	120 mm	

Helix Angle 30°

Designed with a unique scalloped cutting edge design for extremely fast routing or hogging. Best for routing in plywoods and hardwoods.



Solid Carbide Three Edge Low Helix Chipbreaker Bits						Series BC60-000
	NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length	
	BC60-037	Upcut	3/8	1 1/8	3 1/2	3/8" Shank
	BC60-038	Downcut	3/8	1 1/8	3 1/2	
	BC60-053	Upcut	1/2	1 1/8	3 1/2	1/2" Shank
	BC60-051	Upcut	1/2	1 5/8	4	
	BC60-054	Downcut	1/2	1 1/8	3 1/2	
	BC60-052	Downcut	1/2	1 5/8	4	
	BC60-065	Upcut	5/8	1 5/8	4	5/8" Shank
	BC60-061	Upcut	5/8	2 1/8	5	
	BC60-066	Downcut	5/8	1 5/8	4	
	BC60-062	Downcut	5/8	2 1/8	5	
	BC60-073	Upcut	3/4	1 5/8	4	3/4" Shank
	BC60-071	Upcut	3/4	2 1/8	5	
	BC60-074	Downcut	3/4	1 5/8	4	
	BC60-072	Downcut	3/4	2 1/8	5	
	BC60-055	Upcut	12 mm	25 mm	76 mm	12 mm Shank
	BC60-056	Downcut	12 mm	25 mm	76 mm	
	BC60-063	Upcut	16 mm	55 mm	120 mm	16 mm Shank
	BC60-064	Downcut	16 mm	55 mm	120 mm	
	BC60-075	Upcut	18 mm	60 mm	120 mm	18 mm Shank
	BC60-076	Downcut	18 mm	60 mm	120 mm	

Helix Angle 10°

Designed with a unique scalloped cutting edge design for extremely fast routing or hogging of hardwoods and wood composites.

Series BC60-100SE

Designed for fast feed rates and optimum edge finishes on both sides of laminated material. Best for routing double sided laminated materials, hardwoods and wood composites.

Solid Carbide Single Edge Compression Spiral Bits

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC60-102	1/8	3/8	2 1/2
	BC20-106	3/16	5/8	2 1/2
	BC60-110	1/4	7/8	2 1/2
3/8" Shank	BC60-122HS	3/8	1	3
	BC60-120	3/8	1 1/8	3
	BC60-120L	3/8	1 1/8	3
1/2" Shank	BC60-160	1/2	1	3
	BC60-162HS*	1/2	1	3
	BC60-167	1/2	1 1/8	3
	BC60-168HW	1/2	1 1/8	3
	BC60-170	1/2	1 3/8	3 1/2
	BC60-165	1/2	1 5/8	3 1/2
	BC60-165L	1/2	1 5/8	3 1/2
5/8" Shank	BC60-185	5/8	2 1/4	4
3/4" Shank	BC60-195	3/4	2	4
6 mm Shank	BC60-132	6 mm	25 mm	64 mm
8 mm Shank	BC60-134	8 mm	25 mm	64 mm
10 mm Shank	BC60-136	10 mm	35 mm	76 mm
12 mm Shank	BC60-138	12 mm	35 mm	76 mm
16 mm Shank	BC60-142	16 mm	55 mm	100 mm

HS Hard Surface Double Laminate Geometry

HW Hardwood geometry

L Left Hand Rotation

Helix Angle 30°

*Helix Angle 20°



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Double Edge Compression Spiral Bits					Series BC60-100DE
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC60-112	1/4	7/8	2 1/2	1/4" Shank
	BC60-124	3/8	1 1/8	3	3/8" Shank
	BC60-164	1/2	1	3	1/2" Shank
	BC60-171	1/2	1 3/8	3 1/2	
	BC60-169	1/2	1 1/8	3	
	BC60-172	1/2	1 5/8	4	
	BC60-172L	1/2	1 5/8	4	
	BC60-186	5/8	2 1/4	5	5/8" Shank
	BC60-186L	5/8	2 1/4	5	
	BC60-196	3/4	1 7/8	4	3/4" Shank
	BC60-198	3/4	2 1/2	5	
	BC60-198L	3/4	2 1/2	5	
	BC60-133	6 mm	25 mm	64 mm	6 mm Shank
	BC60-135	8 mm	25 mm	64 mm	8 mm Shank
	BC60-137	10 mm	35 mm	76 mm	10 mm Shank
	BC60-139	12 mm	35 mm	76 mm	12 mm Shank
	BC60-140	20 mm	50 mm	100 mm	20 mm Shank
L Left Hand Rotation					Helix Angle 30°

Designed for fast feed rates and optimum edge finishes on both sides of laminated material. These are best for routing double sided laminated materials, hardwoods and wood composites.



Solid Carbide Double Edge Compression Spiral Chipbreaker Bits					Series BC60-100C
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC60-123C	3/8	7/8	3	3/8" Shank
	BC60-124C	3/8	1 1/8	3	
	BC60-163C	1/2	7/8	3	1/2" Shank
	BC60-164C	1/2	1	3	
	BC60-169C	1/2	1 1/8	3	
	BC60-171C	1/2	1 3/8	3 1/2	
	BC60-172C	1/2	1 5/8	4	
	BC60-186C	5/8	2 1/4	5	5/8" Shank
	BC60-196C	3/4	1 7/8	4	3/4" Shank
	BC60-135C	8 mm	25 mm	64 mm	8 mm Shank
	BC60-137C	10 mm	35 mm	76 mm	10 mm Shank
	BC60-139C	12 mm	35 mm	76 mm	12 mm Shank
	BC60-140C	20 mm	50 mm	100 mm	20 mm Shank
					Helix Angle 30°

Designed to give the optimum edge finish of the compression spiral along with the increased feed rates of the chipbreaker/finisher design. This is best for routing double sided laminated materials, hardwoods and wood composites.

Series BC60-100TE

Designed with upcut/downcut design for ultra high feed rates and optimum edge finishes on both sides of laminated material. Best for routing double sided laminated materials, hardwoods and wood composites.

Solid Carbide Three Edge Compression Up|Down Spiral Bits

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
3/8" Shank	BC60-125	3/8	1 1/8	3
1/2" Shank	BC60-174	1/2	1 1/8	3
	BC60-175	1/2	1 5/8	3 1/2
3/4" Shank	BC60-197	3/4	2	4

Helix Angle 30°



Series BC60-100M

Designed for fast feed rates with an excellent finish. The short upcut allows a mortise cut with downcut action. Best for mortising and routing of double sided laminates and hardwoods.

Solid Carbide Multi-Edge Mortise Compression Up|Down Spiral Bits

	NAP GLADU Tool Number	Edge Count	A Cutting Diameter	B Cutting Height	C Upcut Height	Overall Length
1/4" Shank	BC60-111	Single	1/4	7/8	.175	2 1/2
	BC60-113	Double	1/4	7/8	.188	2 1/2
3/8" Shank	BC60-121	Single	3/8	7/8	.188	3
	BC60-123	Double	3/8	7/8	.188	3
	BC60-127L	Double	3/8	1 1/8	.188	3
	BC60-126	Three	3/8	7/8	.200	3
1/2" Shank	BC60-161	Single	1/2	7/8	.200	3
	BC60-161L	Single	1/2	7/8	.200	3
	BC60-166	Single	1/2	1 5/8	.200	3 1/2
	BC60-163	Double	1/2	7/8	.200	3
	BC60-173	Double	1/2	1 3/8	.200	3 1/2
	BC60-173L	Double	1/2	1 3/8	.200	3 1/2
	BC60-176	Three	1/2	7/8	.200	3
	BC60-177	Three	1/2	1 3/8	.200	3 1/2
3/4" Shank	BC60-199	Three	3/4	2	.200	4
6 mm Shank	BC60-152	Single	6 mm	22 mm	4 mm	64 mm
8 mm Shank	BC60-154	Single	8 mm	22 mm	4 mm	64 mm
10 mm Shank	BC60-156	Single	10 mm	22 mm	4 mm	76 mm
	BC60-155	Double	10 mm	22 mm	4 mm	76 mm
12 mm Shank	BC60-158	Single	12 mm	22 mm	4 mm	76 mm
	BC60-157	Double	12 mm	22 mm	4 mm	76 mm

L Left Hand Rotation

Helix Angle 30°



Single Edge



Double Edge



Three Edge

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits




Double Edge



Three Edge

Solid Carbide Multi-Edge Max Life Compression Spiral Bits

Series BC60-100MW



NAP GLADU Tool Number	Edge Count	A Cutting Diameter	B Cutting Height	Overall Length
BC60-123MW*	Double	3/8	7/8	3
BC60-126MW*	Three	3/8	7/8	3
BC60-163MW*	Double	1/2	7/8	3
BC60-169MW	Double	1/2	1 1/8	3
BC60-171MW	Double	1/2	1 3/8	3 1/2
BC60-172MW	Double	1/2	1 5/8	3 1/2

*Mortise Compression

Helix Angle 30°


Designed for maximum life when cutting in high-wear applications. Best for double sided laminates and veneered materials.

3/8" Shank

1/2" Shank

Solid Carbide Three Edge Low Helix Finisher Bits

Series BC60-200



NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length
BC60-239	Upcut	1/4	3/8	3
BC60-241	Upcut	1/4	7/8	3
BC60-240	Downcut	1/4	3/8	3
BC60-242	Downcut	1/4	7/8	3
BC60-243	Upcut	3/8	5/8	3
BC60-245	Upcut	3/8	1 1/8	3
BC60-244	Downcut	3/8	5/8	3
BC60-246	Downcut	3/8	1 1/8	3
BC60-249	Upcut	1/2	1 1/8	3 1/2
BC60-253	Upcut	1/2	1 5/8	4
BC60-251	Upcut	1/2	2 1/8	4 1/2
BC60-250	Downcut	1/2	1 1/8	3 1/2
BC60-254	Downcut	1/2	1 5/8	4
BC60-252	Downcut	1/2	2 1/8	4 1/2
BC60-269	Upcut	3/4	1 5/8	4
BC60-271	Upcut	3/4	2 1/8	5
BC60-270	Downcut	3/4	1 5/8	4
BC60-272	Downcut	3/4	2 1/8	5

Helix Angle 10°

Designed with a fast helix for perfect balance and smooth finish over a wide speed range. Best for routing hardwoods, wood composites and acrylic.

1/4" Shank

3/8" Shank

1/2" Shank


3/4" Shank

Series BC60-300

Solid Carbide Double Edge Chipbreaker | Finisher Bits

This bit is designed for faster feed rates and smoother finishes than conventional two flute bits. Best for routing hardwoods, MDF and plywood.

	NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length
3/8" Shank	BC60-307	Upcut	3/8	1 1/8	3
	BC60-308	Downcut	3/8	1 1/8	3
1/2" Shank	BC60-311	Upcut	1/2	1 1/8	3
	BC60-313	Upcut	1/2	1 5/8	3 1/2
	BC60-317	Upcut	1/2	1 7/8	3 1/2
	BC60-315	Upcut	1/2	2 1/8	4
	BC60-312	Downcut	1/2	1 1/8	3
	BC60-314	Downcut	1/2	1 5/8	3 1/2
	BC60-318	Downcut	1/2	1 7/8	3 1/2
	BC60-316	Downcut	1/2	2 1/8	4
5/8" Shank	BC60-321	Upcut	5/8	2 1/8	4
	BC60-322	Downcut	5/8	2 1/8	4
3/4" Shank	BC60-325	Upcut	3/4	2 1/8	4
	BC60-326	Downcut	3/4	2 1/8	4




Helix Angle 30°

Series BC60-350

Solid Carbide Three Edge Chipbreaker | Finisher Bits

Designed for additional balance at fast feed rates with a smooth finish. Best for routing hardwoods, wood composites and plywood.

	NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length
3/8" Shank	BC60-337	Upcut	3/8	1 1/8	3
	BC60-338	Downcut	3/8	1 1/8	3
1/2" Shank	BC60-351	Upcut	1/2	1 1/8	3
	BC60-355	Upcut	1/2	1 3/8	3 1/2
	BC60-353	Upcut	1/2	1 5/8	3 1/2
	BC60-350	Downcut	1/2	1 1/8	3
	BC60-354	Downcut	1/2	1 3/8	3 1/2
	BC60-352	Downcut	1/2	1 5/8	3 1/2
5/8" Shank	BC60-361	Upcut	5/8	1 5/8	4
	BC60-360	Downcut	5/8	1 5/8	4
3/4" Shank	BC60-371	Upcut	3/4	1 5/8	4
	BC60-373	Upcut	3/4	2 1/4	4
	BC60-375	Upcut	3/4	3 1/8	6
	BC60-370	Downcut	3/4	1 5/8	4
	BC60-372	Downcut	3/4	2 1/4	5
	BC60-374	Downcut	3/4	3 1/8	6




Helix Angle 30°

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Double Edge Chipbreaker | Finisher Bits

Series BC60-400



NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length	
BC60-411	Upcut	8 mm	25 mm	64 mm	8 mm Shank
BC60-412	Downcut	8 mm	25 mm	64 mm	
BC60-413	Upcut	10 mm	35 mm	76 mm	10 mm Shank
BC60-414	Downcut	10 mm	35 mm	76 mm	
BC60-415	Upcut	12 mm	35 mm	76 mm	12 mm Shank
BC60-416	Downcut	12 mm	35 mm	76 mm	
BC60-417	Upcut	16 mm	55 mm	100 mm	16 mm Shank
BC60-418	Downcut	16 mm	55 mm	100 mm	
BC60-419	Upcut	18 mm	60 mm	120 mm	18 mm Shank
BC60-420	Downcut	18 mm	60 mm	120 mm	

Helix Angle: 30°

This bit is designed for faster feed rates and smoother finishes than the conventional two flute bits. Best for routing hardwoods, MDF and plywood.



Solid Carbide Three Edge Chipbreaker | Finisher Bits

Series BC60-430



NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length	
BC60-431	Upcut	8 mm	25 mm	64 mm	8 mm Shank
BC60-432	Downcut	8 mm	25 mm	64 mm	
BC60-433	Upcut	10 mm	35 mm	76 mm	10 mm Shank
BC60-434	Downcut	10 mm	35 mm	76 mm	
BC60-435	Upcut	12 mm	35 mm	76 mm	12 mm Shank
BC60-436	Downcut	12 mm	35 mm	76 mm	
BC60-437	Upcut	16 mm	55 mm	100 mm	16 mm Shank
BC60-438	Downcut	16 mm	55 mm	100 mm	
BC60-439	Upcut	18 mm	60 mm	120 mm	18 mm Shank
BC60-440	Downcut	18 mm	60 mm	120 mm	

Helix Angle: 30°

Designed for additional balance at fast feed rates with a smooth finish. Best for routing hardwoods, wood composites and plywood.

Series BC60-450

Designed for additional balance at fast feed rates with a smooth finish. Best for routing natural wood, plastic, plastic composites and solid surfaces.

Solid Carbide Three Edge High Helix Finisher Bits

	NAP GLADU Tool Number	Flute Cut	A	Cutting Diameter	B	Cutting Height	Overall Length
6 mm Shank	BC60-461	Upcut		6 mm		25 mm	76 mm
	BC60-462	Downcut		6 mm		25 mm	76 mm
8 mm Shank	BC60-451	Upcut		8 mm		25 mm	76 mm
	BC60-452	Downcut		8 mm		25 mm	76 mm
10 mm Shank	BC60-453	Upcut		10 mm		35 mm	76 mm
	BC60-454	Downcut		10 mm		35 mm	76 mm
12 mm Shank	BC60-455	Upcut		12 mm		35 mm	88 mm
	BC60-456	Downcut		12 mm		35 mm	88 mm
16 mm Shank	BC60-457	Upcut		16 mm		55 mm	120 mm
	BC60-458	Downcut		16 mm		55 mm	120 mm
18 mm Shank	BC60-459	Upcut		18 mm		60 mm	120 mm
	BC60-460	Downcut		18 mm		60 mm	120 mm

Helix Angle 30°



Series BC60-470

Designed for additional balance at fast feed rates with a smooth finish. Best for routing hardwoods, wood composites and plywood.

Solid Carbide Three Edge Low Helix Finisher Bits

	NAP GLADU Tool Number	Flute Cut	A	Cutting Diameter	B	Cutting Height	Overall Length
6 mm Shank	BC60-481	Upcut		6 mm		25 mm	76 mm
	BC60-482	Downcut		6 mm		25 mm	76 mm
8 mm Shank	BC60-471	Upcut		8 mm		25 mm	76 mm
	BC60-472	Downcut		8 mm		25 mm	76 mm
10 mm Shank	BC60-473	Upcut		10 mm		35 mm	76 mm
	BC60-474	Downcut		10 mm		35 mm	76 mm
12 mm Shank	BC60-475	Upcut		12 mm		35 mm	88 mm
	BC60-476	Downcut		12 mm		35 mm	88 mm
14 mm Shank	BC60-483	Upcut		14 mm		45 mm	110 mm
	BC60-484	Downcut		14 mm		45 mm	110 mm
16 mm Shank	BC60-477	Upcut		16 mm		55 mm	120 mm
	BC60-478	Downcut		16 mm		55 mm	120 mm
18 mm Shank	BC60-479	Upcut		18 mm		60 mm	120 mm
	BC60-480	Downcut		18 mm		60 mm	120 mm

Helix Angle 30°



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Four Edge Compression Spiral Bits

Series BC60-500



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC60-564	1/2	1	3
BC60-569	1/2	1 1/8	3
BC60-571	1/2	1 3/8	3 1/2
BC60-572	1/2	1 5/8	4
BC60-586	5/8	2 1/4	5
BC60-596	3/4	1 7/8	4
BC60-598	3/4	2 1/2	5

Helix Angle 30°

The ultimate in compression spiral tooling, these tools produce extremely fine finishes on CNC routers. Best for use with double sided laminate and veneer, natural wood and wood composites.

1/2" Shank

5/8" Shank

3/4" Shank



Solid Carbide Four Edge Mortise Compression Spiral Bits

Series BC60-500M



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	C Upcut Height	Overall Length
BC60-563	1/2	7/8	.200	3
BC60-573	1/2	1 3/8	.200	3 1/2

Helix Angle 30°

A compression design that allows for fast feed and excellent finish with a short upcut to allow mortise cuts with downcut action.

1/2" Shank



Solid Carbide Four Edge High Velocity Compression Spiral Bits

Series BC60-600



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC60-664	1/2	1	3
BC60-669	1/2	1 1/8	3
BC60-671	1/2	1 3/8	3 1/2
BC60-672	1/2	1 5/8	4
BC60-686	5/8	2 1/4	5
BC60-696	3/4	1 7/8	4
BC60-698	3/4	2 1/2	5

Helix Angle 30°

This bit is designed to combine a roughing and finishing cut in one tool for rapid feed rates with good finish. These are best for use when routing a high velocity of double sided laminate and veneer, natural wood and wood composites.

1/2" Shank

5/8" Shank

3/4" Shank

Series BC60-700

Designed to combine a roughing and finishing cut in one tool for rapid feed rates with good finish. Best for use when routing a high velocity of natural wood and wood composites.

	NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length
1/2" Shank	BC60-711	Upcut	1/2	1 1/8	3 1/2
	BC60-715	Upcut	1/2	1 5/8	4
	BC60-719	Upcut	1/2	2 1/8	4 1/2
	BC60-710	Downcut	1/2	1 1/8	3 1/2
	BC60-714	Downcut	1/2	1 5/8	4
	BC60-718	Downcut	1/2	2 1/8	4 1/2
5/8" Shank	BC60-721	Upcut	5/8	2 1/8	5
	BC60-720	Downcut	5/8	2 1/8	5
3/4" Shank	BC60-731	Upcut	3/4	2 1/8	5
	BC60-730	Downcut	3/4	2 1/8	5

Helix Angle 30°



Series BC60-900

Designed for heavy material removal operations where the bit is subjected to excessive cutting forces and finish is not a primary concern. Best for use with natural wood and wood composites.

	NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length
3/8" Shank	BC60-901	Upcut	3/8	1 1/8	3
	BC60-902	Downcut	3/8	1 1/8	3
1/2" Shank	BC60-905	Upcut	1/2	1 1/8	3
	BC60-907	Upcut	1/2	1 5/8	3 1/2
	BC60-909	Upcut	1/2	2 1/8	4
	BC60-906	Downcut	1/2	1 1/8	3
	BC60-908	Downcut	1/2	1 5/8	3 1/2
	BC60-910	Downcut	1/2	2 1/8	4

Helix Angle 30°




High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



SC Double Edge Extreme Heavy Duty Chipbreaker | Finisher Bits

Series BC60-950



NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length
BC60-951	Upcut	3/8	1 1/8	3
BC60-950	Downcut	3/8	1 1/8	3
BC60-955	Upcut	1/2	1 1/8	3
BC60-957	Upcut	1/2	1 5/8	3 1/2
BC60-959	Upcut	1/2	2 1/8	4
BC60-954	Downcut	1/2	1 1/8	3
BC60-956	Downcut	1/2	1 5/8	3 1/2
BC60-958	Downcut	1/2	2 1/8	4


Helix Angle 30°

This bit is designed to be fed very fast while withstanding excessive cutting forces and at the same time leaving a smooth finish. For use with natural wood and wood composites.



Solid Carbide Single Edge Straight Wood Rout Bits

Series BC61-200



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC61-240	1/8	1/2	2
BC61-260	3/16	3/4	2
BC61-280	1/4	7/8	2 1/2
BC61-285	1/4	1	2 1/2
BC61-300	5/16	1 1/8	3
BC61-320	3/8	1 1/8	3
BC61-360	1/2	1 1/8	3

These are designed to enhance operations where the benefits of spiral action are not needed. The single edge provides fast, free cutting with an optimum cutter life. Best for routing natural wood, wood composites and abrasive plastics.



Metric Solid Carbide Single Edge Straight Bits

Series BC61-400



NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
BC61-410	4 mm	16 mm	64 mm
BC61-411	5 mm	20 mm	64 mm
BC61-412	6 mm	25 mm	64 mm
BC61-414	8 mm	25 mm	64 mm
BC61-416	10 mm	35 mm	88 mm
BC61-418	12 mm	35 mm	88 mm

This bit is designed with fast, free cutting "O" flute geometry made from solid carbide to rout softer, ductile plastics. Best for routing wood composites, plastics in the ABS, polycarbonate, polystyrene and ductile PVC formulations and other composite materials.

Series BC61-000

Designed with fast, free cutting “O” flute geometry and solid carbide body to rout wood composites and other composite materials.

Solid Carbide Single Edge Straight Bits - General Purpose

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/4" Shank	BC61-040	1/8	1/2	2
	BC61-050	5/32	9/16	2
	BC61-060	3/16	5/8	2
	BC61-070	7/32	5/8	2 1/2
	BC61-080	1/4	3/4	2 1/2
3/8" Shank	BC61-090	9/32	3/4	2 1/2
	BC61-100	5/16	13/16	2 1/2
	BC61-120	3/8	7/8	2 1/2
1/2" Shank	BC61-140	7/16	1	3
	BC61-160	1/2	1	3



Series BC61-000P

This bit is designed with fast, free cutting “O” flute geometry and a solid carbide body to rout softer, ductile plastics. Best for routing plastics in the ABS, polycarbonate and ductile PVC formulations.

Solid Carbide Single Edge Straight Bits - Plastics

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
1/8" Shank	BC61-044	1/8	1/2	2
	BC61-045	1/8	5/8	3
3/16" Shank	BC61-064	3/16	5/8	2 1/2
1/4" Shank	BC61-041	1/8	5/16	2
	BC61-042	1/8	1/2	2
	BC61-042L	1/8	1/2	2
	BC61-043	1/8	5/8	4
	BC61-052	5/32	9/16	2
	BC61-061	3/16	3/8	2
	BC61-062	3/16	5/8	2
	BC61-062L	3/16	5/8	2
	BC61-063*	3/16	1	4
	BC61-072	7/32	5/8	2 1/2
	BC61-081	1/4	3/8	2 1/2
	BC61-082	1/4	3/4	2 1/2
	BC61-082L	1/4	3/4	2 1/2
	BC61-083*	1/4	3/4	3 1/4
	BC61-083L*	1/4	3/4	3 1/4
	BC61-085*	1/4	1	3 1/4
	BC61-084*	1/4	1 1/4	4
3/8" Shank	BC61-121	3/8	5/8	2 1/2
	BC61-122	3/8	7/8	2 1/2
	BC61-123*	3/8	1 5/8	6
1/2" Shank	BC61-162	1/2	1	3
	BC61-164	1/2	1 5/8	4
	BC61-166	1/2	2 1/8	6



*These tools are designed and toleranced for air routers with guide bushings
L Left Hand Rotation

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Single Edge Downcut Spiral Bits

Series BC62-000 | BC62-400

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
BC62-040	1/8	1/2	2	1/4" Shank
BC62-080	1/4	3/4	2 1/2	
BC62-100	5/16	13/16	2 1/2	3/8" Shank
BC62-120	3/8	7/8	2 1/2	
BC62-410	4 mm	16 mm	64 mm	6 mm Shank
BC62-411	5 mm	20 mm	64 mm	
BC62-412	6 mm	25 mm	64 mm	8 mm Shank
BC62-414	8 mm	25 mm	64 mm	

Helix Angle 30°

These bits are designed for routing abrasive materials at extremely fast feed rates when small diameters are a priority. Best for routing hard or abrasive materials and aluminum.



Solid Carbide Single Edge Downcut Spiral Wood Rout Bits

Series BC62-200

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
BC62-240	1/8	1/2	2	1/4" Shank
BC62-260	3/16	3/4	2	
BC62-280	1/4	5/8	2 1/2	
BC62-285	1/4	1	2 1/2	
BC62-300	5/16	1 1/8	3	5/16" Shank
BC62-320	3/8	1 1/8	3	3/8" Shank
BC62-360	1/2	1 1/8	3	1/2" Shank

Helix Angle 30°

These are designed for routing wood and wood composites where aggressive downward chip removal is necessary in hand-fed or CNC applications. These tools are characterized by long life, rigidity and high quality finish. Best for routing wood, wood composites and plastics.



Solid Carbide Single Edge Downcut Spiral "O" Bits

Series BC62-700

NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
BC62-713	1/8	1/2	2	1/8" Shank
BC62-719	3/16	5/8	2	3/16" Shank
BC62-712	1/8	1/2	2	1/4" Shank
BC62-715	5/32	9/16	2	
BC62-718	3/16	5/8	2	2 1/2
BC62-720	7/32	3/4	2 1/2	
BC62-725	1/4	3/4	2 1/2	3
BC62-726	1/4	1 1/4	3	
BC62-733	3/8	1 1/8	3	3/8 Shank

Helix Angle 21°

Designed to provide a smooth finish in rigid plastics with downward chip removal. Best for routing hard, rigid plastics, and may be used for soft flexible plastics.

Series BC62-600		Solid Carbide Single Edge Downcut Spiral “O” Flute Bits				
These are designed to provide a smooth finish in hard plastics with downward chip removal. Best for use on acrylic, nylon, PVC, polycarbonate and solid surfaces.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	1/8" Shank	BC62-604	1/8	1/4	1 1/2	
	3/16" Shank	BC62-612	3/16	3/8	1 1/2	
	1/4" Shank	BC62-606	1/8	1/4	2	
		BC62-610	1/8	1/2	2	
		BC62-614	3/16	3/8	2	
		BC62-618	3/16	5/8	2	
		BC62-620	1/4	3/8	2	
		BC62-622	1/4	3/4	2 1/2	
		BC62-624	1/4	1 1/4	3	
	3/8" Shank	BC62-625	3/8	3/4	3	
		BC62-626	3/8	1 1/8	3	
	1/2" Shank	BC62-630	5/16	3/4	3	
		BC62-634	21/64	3/4	3	
	Helix Angle 22°					

Series BC62-750		Solid Carbide Single Edge Downcut Spiral “O” Flute Bits				
Designed to provide a smooth finish in soft plastics with downward chip removal. Best for routing soft, flexible plastics, may be used for hard, rigid plastics.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	1/8" Shank	BC62-763	1/8	1/2	2	
	3/16" Shank	BC62-769	3/16	5/8	2	
	1/4" Shank	BC62-762	1/8	1/2	2	
		BC62-768	3/16	5/8	2	
		BC62-775	1/4	3/4	2 1/2	
		BC62-776	1/4	1 1/4	3	
	3/8" Shank	BC62-783	3/8	1 1/8	3	
Helix Angle 21°						

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Single Edge Downcut Spiral "O" Flute Bits					Series BC62-900	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length		Designed as high speed cutters for machining aluminum sheet metal. For use on high speed CNC mills, high speed machining centres and CNC routers.
	BC62-902	2 mm	6 mm	50 mm	2 mm Shank	
	BC62-906	2.5 mm	6 mm	50 mm	2.5 mm Shank	
	BC62-910	3 mm	8 mm	50 mm	3 mm Shank	
	BC62-914	3 mm	12 mm	64 mm		
	BC62-918	4 mm	8 mm	64 mm	4 mm Shank	
	BC62-920	4 mm	12 mm	64 mm		
	BC62-922	4 mm	20 mm	64 mm		
	BC62-926	4 mm	30 mm	64 mm		
	BC62-928	5 mm	16 mm	64 mm	5 mm Shank	
	BC62-932	5 mm	30 mm	64 mm		
	BC62-904	2 mm	6 mm	64 mm	6 mm Shank	
	BC62-908	2.5 mm	6 mm	64 mm		
	BC62-912	3 mm	8 mm	64 mm		
	BC62-916	3 mm	12 mm	64 mm		
	BC62-924	4 mm	20 mm	64 mm		
	BC62-930	5 mm	16 mm	64 mm		
	BC62-934	6 mm	8 mm	64 mm		
	BC62-936	6 mm	12 mm	64 mm		
	BC62-938	6 mm	20 mm	64 mm		
	BC62-940	6 mm	30 mm	76 mm		
	BC62-942	6 mm	38 mm	76 mm		
	BC62-944	8 mm	25 mm	64 mm	8 mm Shank	
	BC62-946	8 mm	38 mm	76 mm		
	BC62-948	10 mm	30 mm	76 mm	10 mm Shank	



SC Single Edge Downcut Spiral "O" Flute Bits - Hard Plastic					Series BC62-800	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length		Designed to provide a smooth finish in hard plastics with downward chip removal. Best for use on acrylic, nylon, PVC, polycarbonate and solid surfaces.
	BC62-802	2 mm	8 mm	50 mm	2 mm Shank	
	BC62-806	2.5 mm	8 mm	50 mm	2.5 mm Shank	
	BC62-810	3 mm	8 mm	50 mm	3 mm Shank	
	BC62-814	3 mm	12 mm	64 mm		
	BC62-818	4 mm	8 mm	64 mm	4 mm Shank	
	BC62-820	4 mm	12 mm	64 mm		
	BC62-822	4 mm	20 mm	64 mm		
	BC62-826	4 mm	30 mm	64 mm		
	BC62-828	5 mm	16 mm	64 mm	5 mm Shank	
	BC62-832	5 mm	30 mm	64 mm		
	BC62-804	2 mm	8 mm	64 mm	6 mm Shank	
	BC62-808	2.5 mm	8 mm	64 mm		
	BC62-812	3 mm	8 mm	64 mm		
	BC62-816	3 mm	12 mm	64 mm		
	BC62-824	4 mm	20 mm	64 mm		
	BC62-830	5 mm	16 mm	64 mm		
	BC62-834	6 mm	8 mm	64 mm		
	BC62-836	6 mm	12 mm	64 mm		
	BC62-838	6 mm	20 mm	64 mm		
	BC62-840	6 mm	30 mm	76 mm		
	BC62-842	6 mm	38 mm	76 mm		
	BC62-844	8 mm	25 mm	64 mm	8 mm Shank	
	BC62-846	8 mm	38 mm	76 mm		
	BC62-848	10 mm	30 mm	76 mm	10 mm Shank	
	BC62-849	10 mm	35 mm	76 mm		

Series BC62-850

Designed to provide a smooth finish in soft plastics with downward chip removal. Best for use on HDPE, HIPS, UHMW, ABS, polycarbonate, PE, polystyrene, polypropylene, acetal, acrylic, PET and solid surfaces.

SC Single Edge Downcut Spiral "O" Flute Bits - Soft Plastic					
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
2 mm Shank	BC62-852	2 mm	8 mm	50 mm	
2.5 mm Shank	BC62-856	2.5 mm	8 mm	50 mm	
3 mm Shank	BC62-860	3 mm	8 mm	50 mm	
	BC62-864	3 mm	12 mm	64 mm	
4 mm Shank	BC62-868	4 mm	8 mm	64 mm	
	BC62-870	4 mm	12 mm	64 mm	
	BC62-872	4 mm	20 mm	64 mm	
	BC62-876	4 mm	30 mm	64 mm	
5 mm Shank	BC62-878	5 mm	16 mm	64 mm	
	BC62-882	5 mm	30 mm	64 mm	
6 mm Shank	BC62-854	2 mm	8 mm	64 mm	
	BC62-858	2.5 mm	8 mm	64 mm	
	BC62-862	3 mm	8 mm	64 mm	
	BC62-866	3 mm	12 mm	64 mm	
	BC62-874	4 mm	20 mm	64 mm	
	BC62-880	5 mm	16 mm	64 mm	
	BC62-884	6 mm	8 mm	64 mm	
	BC62-886	6 mm	12 mm	64 mm	
	BC62-888	6 mm	20 mm	64 mm	
	BC62-890	6 mm	30 mm	76 mm	
8 mm Shank	BC62-894	8 mm	25 mm	64 mm	
	BC62-896	8 mm	38 mm	76 mm	
10 mm Shank	BC62-898	10 mm	30 mm	76 mm	
	BC62-899	10 mm	35 mm	76 mm	

Helix Angle 22°

Series BC63-000 | BC63-400

Designed to replace high speed steel bits when the material to be cut is too abrasive or the feed rates too high for steel. Best for routing in hard or abrasive materials in wood, wood composites and aluminum.

Solid Carbide Single Edge Upcut Spiral Bits					
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
1/4" Shank	BC63-040	1/8	1/2	2	
	BC63-050	5/32	9/16	2	
	BC63-060	3/16	5/8	2	
	BC63-070	7/32	5/8	2 1/2	
	BC63-080	1/4	3/4	2 1/2	
3/8" Shank	BC63-090	9/32	3/4	2 1/2	
	BC63-100	5/16	13/16	2 1/2	
	BC63-120	3/8	7/8	2 1/2	
1/2" Shank	BC63-140	7/16	1	3	
	BC63-160	1/2	1	3	
6 mm Shank	BC63-410	4 mm	16 mm	64 mm	
	BC63-411	5 mm	20 mm	64 mm	
	BC63-412	6 mm	25 mm	64 mm	
8 mm Shank	BC63-414	8 mm	25 mm	64 mm	

Helix Angle 30°

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Single Edge Upcut Spiral Wood Rout Bits					Series BC63-200
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC63-240	1/8	1/2	2	1/4" Shank
	BC63-260	3/16	3/4	2	
	BC63-280	1/4	7/8	2 1/2	
	BC63-285	1/4	1	2 1/2	
	BC63-300	5/16	1 1/8	3	5/16" Shank
	BC63-320	3/8	1 1/8	3	3/8" Shank
	BC63-360	1/2	1 1/8	3	1/2" Shank
Helix Angle 30°					

These are designed for routing wood and wood composites where aggressive chip removal is necessary in hand-fed or CNC applications. For use when long life, rigidity and high quality finish are desired from tool. Best for routing wood, wood composites and plastics.



Solid Carbide Single Edge Upcut Spiral "O" Flute Bits					Series BC63-600
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC63-604	1/8	1/4	1 1/2	1/8" Shank
	BC63-612	3/16	3/8	1 1/2	3/16" Shank
	BC63-606	1/8	1/4	2	1/4" Shank
	BC63-610	1/8	1/2	2	
	BC63-614	3/16	3/8	2	
	BC63-618	3/16	5/8	2	
	BC63-620	1/4	3/8	2	3/8" Shank
	BC63-622	1/4	3/4	2 1/2	
	BC63-624	1/4	1 1/4	3	
	BC63-625	3/8	3/4	3	
	BC63-626	3/8	1 1/8	3	1/2" Shank
	BC63-630	5/16	3/4	3	
	BC63-634	21/64	3/4	3	

These high speed cutters are designed for machining aluminum sheet and block material. These tools are optimized for use on high-speed CNC mills, CNC routers and high speed machining centres.



Solid Carbide Single Edge Upcut Spiral "O" Flute Bits					Series BC63-700
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC63-701	1/16	1/4	2	1/8" Shank
	BC63-711	1/8	1/4	2	
	BC63-713	1/8	1/2	2	
	BC63-716	3/16	3/8	2	3/16" Shank
	BC63-719	3/16	5/8	2	
	BC63-700	1/16	1/4	2	1/4" Shank
	BC63-710	1/8	1/4	2	
	BC63-712	1/8	1/2	2	
	BC63-715	5/32	9/16	2	
	BC63-717	3/16	3/8	2	3/8" Shank
	BC63-718	3/16	5/8	2	
	BC63-720	7/32	3/4	2 1/2	
	BC63-724	1/4	3/8	2	
	BC63-725	1/4	3/4	2 1/2	1/2" Shank
	BC63-726	1/4	1 1/4	3	
	BC63-733	3/8	1 1/8	3	

Designed to provide a smooth finish in rigid plastics with upward chip removal. Best for routing hard, rigid plastics, but can be used for soft, flexible plastics as well.

Series BC63-750		Solid Carbide Single Edge Upcut Spiral “O” Flute Bits			
Designed to provide a smooth finish in soft plastics with upward chip removal. Best for routing soft, flexible plastics, but can be used for hard, rigid plastics as well.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	1/8" Shank	BC63-751	1/16	1/4	2
		BC63-761	1/8	1/4	2
		BC63-763	1/8	1/2	2
	3/16" Shank	BC63-766	3/16	3/8	2
		BC63-769	3/16	5/8	2
	1/4" Shank	BC63-750	1/16	1/4	2
		BC63-760	1/8	1/4	2
		BC63-762	1/8	1/2	2
		BC63-767	3/16	3/8	2
		BC63-768	3/16	5/8	2
		BC63-774	1/4	3/8	2
		BC63-775	1/4	3/4	2 1/2
		BC63-776	1/4	1 1/4	3
	3/8" Shank	BC63-783	3/8	1 1/8	3

Helix Angle 21°



Series BC63-800		Solid Carbide Single Edge Upcut Spiral “O” Flute Bits			
Designed to provide a smooth finish in hard plastics with upward chip removal. Best for use on acrylic, nylon, PVC, polycarbonate and solid surfaces.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	2 mm Shank	BC63-802	2 mm	8 mm	50 mm
	2.5 mm Shank	BC63-806	2.5 mm	8 mm	50 mm
	3 mm Shank	BC63-810	3 mm	8 mm	50 mm
		BC63-814	3 mm	12 mm	64 mm
	4 mm Shank	BC63-818	4 mm	8 mm	64 mm
		BC63-820	4 mm	12 mm	64 mm
		BC63-822	4 mm	20 mm	64 mm
		BC63-826	4 mm	30 mm	64 mm
	5 mm Shank	BC63-828	5 mm	16 mm	64 mm
		BC63-832	5 mm	30 mm	64 mm
	6 mm Shank	BC63-804	2 mm	8 mm	64 mm
		BC63-808	2.5 mm	8 mm	64 mm
		BC63-812	3 mm	8 mm	64 mm
		BC63-816	3 mm	12 mm	64 mm
		BC63-824	4 mm	20 mm	64 mm
		BC63-830	5 mm	16 mm	64 mm
		BC63-834	6 mm	8 mm	64 mm
		BC63-836	6 mm	12 mm	64 mm
		BC63-838	6 mm	20 mm	64 mm
		BC63-840	6 mm	30 mm	76 mm
		BC63-842	6 mm	38 mm	76 mm
	8 mm Shank	BC63-844	8 mm	25 mm	64 mm
		BC63-846	8 mm	38 mm	76 mm
	10 mm Shank	BC63-848	10 mm	30 mm	76 mm
		BC63-849	10 mm	35 mm	76 mm

Helix Angle 30°



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Single Edge Upcut Spiral "O" Flute Bits					Series BC63-850
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC63-852	2 mm	8 mm	50 mm	2 mm Shank
	BC63-856	2.5 mm	8 mm	50 mm	2.5 mm Shank
	BC63-860	3 mm	8 mm	50 mm	3 mm Shank
	BC63-864	3 mm	12 mm	64 mm	4 mm Shank
	BC63-868	4 mm	8 mm	64 mm	
	BC63-870	4 mm	12 mm	64 mm	
	BC63-872	4 mm	20 mm	64 mm	
	BC63-876	4 mm	30 mm	64 mm	5 mm Shank
	BC63-878	5 mm	16 mm	64 mm	
	BC63-882	5 mm	30 mm	64 mm	6 mm Shank
	BC63-854	2 mm	8 mm	64 mm	
	BC63-858	2.5 mm	8 mm	64 mm	
	BC63-862	3 mm	8 mm	64 mm	
	BC63-866	3 mm	12 mm	64 mm	
	BC63-874	4 mm	20 mm	64 mm	
	BC63-880	5 mm	16 mm	64 mm	
	BC63-884	6 mm	8 mm	64 mm	
	BC63-886	6 mm	12 mm	64 mm	
	BC63-888	6 mm	20 mm	64 mm	
	BC63-890	6 mm	30 mm	76 mm	8 mm Shank
	BC63-892	6 mm	38 mm	76 mm	
	BC63-894	8 mm	25 mm	64 mm	10 mm Shank
	BC63-896	8 mm	38 mm	76 mm	
	BC63-898	10 mm	30 mm	76 mm	10 mm Shank
	BC63-899	10 mm	35 mm	76 mm	

Helix Angle 21°

Designed to provide a smooth finish in soft plastic with upward chip removal. Best for use on HDPE, HIPS, UHMW, ABS, polycarbonate, polystyrene, PE, polypropylene, acetal, acrylic, PET and solid surfaces.



Solid Carbide Single Edge Upcut Spiral "O" Flute Bits					Series BC63-900
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length	
	BC63-902	2 mm	6 mm	50 mm	2 mm Shank
	BC63-906	2.5 mm	6 mm	50 mm	2.5 mm Shank
	BC63-910	3 mm	8 mm	50 mm	3 mm Shank
	BC63-914	3 mm	12 mm	64 mm	4 mm Shank
	BC63-918	4 mm	8 mm	64 mm	
	BC63-920	4 mm	12 mm	64 mm	
	BC63-922	4 mm	20 mm	64 mm	
	BC63-926	4 mm	30 mm	64 mm	5 mm Shank
	BC63-928	5 mm	16 mm	64 mm	
	BC63-932	5 mm	30 mm	64 mm	6 mm Shank
	BC63-904	2 mm	6 mm	64 mm	
	BC63-908	2.5 mm	6 mm	64 mm	
	BC63-912	3 mm	8 mm	64 mm	
	BC63-916	3 mm	12 mm	64 mm	
	BC63-924	4 mm	20 mm	64 mm	
	BC63-930	5 mm	16 mm	64 mm	
	BC63-934	6 mm	8 mm	64 mm	
	BC63-936	6 mm	12 mm	64 mm	
	BC63-938	6 mm	20 mm	64 mm	
	BC63-940	6 mm	30 mm	76 mm	8 mm Shank
	BC63-942	6 mm	38 mm	76 mm	
	BC63-944	8 mm	25 mm	64 mm	10 mm Shank
	BC63-946	8 mm	38 mm	76 mm	
	BC63-948	10 mm	30 mm	76 mm	10 mm Shank

Helix Angle 22°

These bits are high speed cutters designed for machining aluminum sheet and block material, best for use on high speed CNC mills, high speed machining centres and CNC routers.

Series BC66-200 | BC66-250

Designed to provide up to a 1/16" top face chamfer and a finished side edge on plastic sheets or parts.



BC66-208

Solid Carbide Double Edge Rout and Chamfer Bits

	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Material Thickness	Overall Length
3/8" Shank	BC66-200	1/4	3/16	1/8	2 1/4
	BC66-204	1/4	1/4	3/16	2 1/4
	BC66-208	1/4	5/16	1/4	2 1/4
1/2" Shank	BC66-202	3/8	3/16	1/8	3
	BC66-206	3/8	1/4	3/16	3
	BC66-210	3/8	5/16	1/4	3
10 mm Shank	BC66-250	6 mm	5 mm	3 mm	70 mm
	BC66-254	6 mm	6 mm	4 mm	70 mm
	BC66-258	6 mm	8 mm	6 mm	70 mm
12 mm Shank	BC66-252	8 mm	5 mm	3 mm	76 mm
	BC66-256	8 mm	6 mm	4 mm	76 mm
	BC66-260	8 mm	8 mm	6 mm	76 mm



Series BC66-300 | BC66-350

Designed for pocketing applications where the bottom of the pocket must be smooth.
Best for use on plastic and aluminum.

Solid Carbide Double Edge Upcut Bottom Surfacing Bits

	NAP GLADU Tool Number	r Corner Radius	A Cutting Diameter	B Cutting Height	Overall Length
1/8" Shank	BC66-306	.04	1/8	1/4	2
1/4" Shank	BC66-308	.04	1/8	1/4	2
	BC66-314	.05	1/4	3/8	2
3/8" Shank	BC66-320	.05	3/8	5/8	2 1/2
1/2" Shank	BC66-326	.05	1/2	7/8	3
3 mm Shank	BC66-356	1 mm	3 mm	6 mm	40 mm
6 mm Shank	BC66-358	1 mm	3 mm	6 mm	51 mm
	BC66-364	1.25 mm	6 mm	10 mm	51 mm
8 mm Shank	BC66-370	1.25 mm	8 mm	12 mm	64 mm
12 mm Shank	BC66-376	1.25 mm	12 mm	20 mm	76 mm

Helix Angle: 30°



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits



Solid Carbide Single Edge Straight "O" Rounding Bits										Series BC66-000	
	NAP GLADU Tool Number	Cutting Radius	A1 Cutting A2 Diameter	B Cutting Height	C Tip to Radius	O Cutter Opening	Plastic Size	Overall Length	1/4" Shank Designed for rounding the edge of plastic sheets or parts.		
	BC66-082	1/8	A1 1/4 A2 .195	3/8	1/16	5/32	1/8	2 1/2			
	BC66-083	3/16	A1 1/4 A2 .18	3/8	1/16	7/32	3/16	2 1/2			
	BC66-084	1/4	A1 1/4 A2 .163	3/8	1/16	9/32	1/4	2 1/2			



Solid Carbide Double Edge Straight "O" Rounding Bits										Series BC66-000	
	NAP GLADU Tool Number	Cutting Radius	A1 Cutting A2 Diameter	B Cutting Height	C Tip to Radius	O Cutter Opening	Plastic Size	Overall Length	Designed for rounding the edge of plastic sheets or parts.		
	BC66-092	1/8	A1 1/4 A2 .195	3/8	1/16	5/32	1/8	2 1/2	1/4" Shank		
	BC66-093	3/16	A1 1/4 A2 .18	3/8	1/16	7/32	3/16	2 1/2			
	BC66-094	1/4	A1 1/4 A2 .163	3/8	1/16	9/32	1/4	2 1/2			
	BC66-073	3 mm	A1 6 mm A2 4.47 mm	10 mm	1.5 mm	4 mm	3 mm	64 mm	6 mm Shank		
	BC66-074	4 mm	A1 6 mm A2 4.24 mm	10 mm	1.5 mm	5 mm	4 mm	64 mm			
	BC66-075	5 mm	A1 6 mm A2 3.96 mm	10 mm	1.5 mm	6 mm	5 mm	64 mm			
	BC66-076	6 mm	A1 6 mm A2 3.73 mm	10 mm	1.5 mm	7 mm	6 mm	64 mm			

Series BC66-000		Solid Carbide Single Edge Spiral “O” Rounding Bits								
Designed for rounding the edge of plastic sheets or parts.	1/4" Shank	NAP GLADU Tool Number	Cutting Radius	A1 Cutting A2 Diameter	B Cutting Height	C Tip to Radius	O Cutter Opening	Plastic Size	Overall Length	
		BC66-085	1/8	A1 1/4 A2 .195	3/8	1/16	5/32	1/8	2 1/2	
		BC66-086	3/16	A1 1/4 A2 .18	3/8	1/16	7/32	3/16	2 1/2	
		BC66-087	1/4	A1 1/4 A2 .163	3/8	1/16	9/32	1/4	2 1/2	
		Helix Angle 21°								

Series BC66-000		Solid Carbide Double Edge Straight "V" Rounding Bits								
Designed for rounding the edge of plastic sheets or parts.	3/8" Shank	NAP GLADU Tool Number	Cutting Radius	A1 Cutting A2 Diameter	B Cutting Height	C Tip to Radius	O Cutter Opening	Plastic Size	Overall Length	
		BC66-120	1/8	A1 3/8 A2 .32	3/8	1/16	5/32	1/8	2 1/2	
		BC66-121	3/16	A1 3/8 A2 .305	3/8	1/16	7/32	3/16	2 1/2	
		BC66-122	1/4	A1 3/8 A2 .288	3/8	1/16	9/32	1/4	2 1/2	
	1/2" Shank	BC66-123	3/8	A1 3/8 A2 .255	1/2	1/16	13/32	3/8	2 1/2	
		BC66-160	1/8	A1 1/2 A2 .445	3/8	1/16	5/32	1/8	3	
		BC66-161	3/16	A1 1/2 A2 .43	3/8	1/16	7/32	3/16	3	
		BC66-162	1/4	A1 1/2 A2 .413	3/8	1/16	9/32	1/4	3	
		BC66-163	1/2	A1 1/2 A2 .347	5/8	1/16	17/32	1/2	3	
	8 mm Shank	BC66-077	8 mm	A1 8 mm A2 5.21 mm	12 mm	1.5 mm	9 mm	8 mm	64 mm	
	10 mm Shank	BC66-078	10 mm	A1 10 mm A2 6.68 mm	14 mm	1.5 mm	11 mm	10 mm	70 mm	
	12 mm Shank	BC66-079	12 mm	A1 12 mm A2 8.18 mm	16 mm	1.5 mm	13 mm	12 mm	76 mm	

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits

Solid Carbide Fiberglass Router Bits						Series BC67-000	
	NAP GLADU Tool Number	Router Machine	A Cutting Diameter	B Cutting Height	Overall Length		
	BC67-080	Burr	1/4	3/4	2 1/2	1/4" Shank	
	BC67-082	2 Flutes	1/4	3/4	2 1/2		
	BC67-084	Aramid Tool	1/4	3/4	2 1/2		
	BC67-120	Burr	3/8	7/8	2 1/2	3/8" Shank	
	BC67-122	2 Flutes	3/8	7/8	2 1/2		
	BC67-124	Aramid Tool	3/8	7/8	2 1/2		
	BC67-160	Burr	1/2	1	3	1/2" Shank	
	BC67-162	2 Flutes	1/2	1	3		
	BC67-164	Aramid Tool	1/2	1	3		
	BC67-090	Burr	4 mm	16 mm	50 mm	6 mm Shank	
	BC67-091	Burr	6 mm	19 mm	63 mm		
	BC67-092	Burr	6 mm	25 mm	75 mm		
	BC67-093	Burr	8 mm	25 mm	63 mm	8 mm Shank	
	BC67-094	Burr	10 mm	25 mm	75 mm	10 mm Shank	
	BC67-095	Burr	12 mm	25 mm	75 mm	12 mm Shank	

Designed to rout fiberglass, however the upcut/ downcut design which effectively shears fibrous materials makes this tool suitable for cutting aramid fiber composites. Best for routing fibrous reinforcements and epoxies made with glass, carbon and aramid fibres as well as other composite materials.



Solid Carbide Three Edge Phenolic Composite Cutter Bits						Series BC67-200	
	NAP GLADU Tool Number	Flute Cut	A Cutting Diameter	B Cutting Height	Overall Length		
	BC67-205	Upcut	3/8	7/8	3	3/8" Shank	
	BC67-206	Downcut	3/8	7/8	3		
	BC67-211	Upcut	1/2	1 1/8	3	1/2" Shank	
	BC67-215	Upcut	1/2	2 1/8	4		
	BC67-212	Downcut	1/2	1 1/8	3 1/2		
	BC67-216	Downcut	1/2	2 1/8	4 1/2		
Helix Angle 10°							

This bit is designed for low or high spindle speed applications in any CNC machining environment. Free cutting action provides a better finish and a lower noise level. Best for use in phenolic.

This bit is designed for low or high spindle speed applications in any CNC machining environment. Free cutting action provides a better finish and a lower noise level. Best for use in phenolic.

Series BC70-200

Solid Carbide Flush Mounted Saws

Designed for trimming and slotting plastics. The saws are permanently attached to the arbors and are not reversible.

1/2" Shank

NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	Collar Diameter	K Blade Kerf	Overall Length
BC70-204	Right	1	9/16	.062	4
BC70-224	Right	1 1/4	5/8	.062	4

Saw Blade Speed and Feed Chart, Page 146



Series BC70-100

Carbide Tipped Saw Blades

Arbors

These saw blades are designed to trim and groove both hard and soft plastics. The saws are reversible for right and left hand rotation cutting. Blades are specifically designed to be used with arbors in Series BC70-100.

Soft Plastic
Slow Feed

NAP GLADU Tool Number	A Cutting Diameter	Teeth Count	R Tooth Rake	K Blade Kerf	Grind Type
BC70-100	2	10	0°	.095	TCG
BC70-102	2 1/2	10	0°	.095	TCG
BC70-104	3	10	0°	.095	TCG
BC70-106	3 1/2	10	0°	.095	TCG
BC70-108	4	10	0°	.095	TCG

Soft Plastic
Fast Feed

BC70-120	2	16	0°	.095	TCG
BC70-122	2 1/2	20	0°	.095	TCG
BC70-124	3	20	0°	.095	TCG
BC70-126	3 1/2	20	0°	.095	TCG
BC70-128	4	20	0°	.095	TCG

Hard Plastic
Slow Feed

BC70-140	2	10	-5°	.095	TCG
BC70-142	2 1/2	10	-5°	.095	TCG
BC70-144	3	10	-5°	.095	TCG
BC70-146	3 1/2	10	-5°	.095	TCG
BC70-148	4	10	-5°	.095	TCG

Hard Plastic
Fast Feed


BC70-160	2	16	-5°	.095	TCG
BC70-162	2 1/2	20	-5°	.095	TCG
BC70-164	3	20	-5°	.095	TCG
BC70-166	3 1/2	20	-5°	.095	TCG
BC70-168	4	20	-5°	.095	TCG

BC Saw Tool Number	Overall Length
BC70-180	3 1/4
BC70-181	4 1/2
BC70-182	3 1/4
BC70-184	3 1/4

1/2" Shank

5/8" Shank

3/4" Shank



Saw Blade Speed and Feed Chart, Page 146

TCG Triple Chip Grind

High Speed Steel and Solid Carbide - Straight and Spiral Router Bits

[illegible]

Guide to Feeds and Speeds					
NAP GLADU Tool Series	Cutting Diameter	Max RPM	Soft Plastic	Hard Plastic	Fibrous Reinforcements
BC70-100	2"	18,000	150	150	150
BC70-100	2 1/2"	16,000	150	150	150
BC70-100	3"	14,000	150	150	150
BC70-100	3 1/2"	12,000	150	150	150
BC70-100	4"	10,000	150	150	150
BC70-200	> 1 1/2"	14,000	150	150	150
BC70-300	2"	16,000	150	150	150

Use this chart to determine the correct RPM for the saws listed on pages 145 and 146. These measurements are based on the series number and the cutting diameter of each tool. For saws in Series BC70-200 the listed RPM applies to bits with a cutting diameter 1 1/2" or smaller.


Series BC70-500		Plastic Drills with Special Point			
Special plastic drills with a 60° point to eliminate cracking and provide smooth, chip-free finish holes in plastic sheet goods.		NAP GLADU Tool Number	A Cutting Diameter	B Cutting Height	Overall Length
	1/8" Shank	BC70-502	1/8	1 1/2	2 3/4
	5/32" Shank	BC70-506	5/32	1 15/16	3 1/8
	3/16" Shank	BC70-510	3/16	2 1/8	3 1/2
	1/4" Shank	BC70-514	1/4	2 7/16	4
		BC70-520*	5/16	1 3/4	3 1/8
		BC70-524*	3/8	2 1/4	4 3/8
		BC70-528*	7/16	2 1/2	4 3/4
		BC70-532*	1/2	2 5/8	5 1/8
*Shank Length 7/8"					




Series 129-460 BC60-090		Leuco Solid Carbide Lock-Case Cutter					
Designed for the cutting of lock cases and face-plates in doors. Cutting edges with chip breakers and a positive spiral allow for optimum chip evacuation. A two flute design for door hardware cutouts and three flute design only for lock cases		NAP GLADU Tool Number	Edge Cut	A Cutting Diameter	B Cutting Height	C Shank Length	Overall Length
	5/8" Shank	BC60-090	Three	5/8	2	2	6 1/2
	14 mm Shank	178843	Double	14 mm	25 mm	50 mm	155 mm
		178839	Three	14 mm	25 mm	50 mm	155 mm
	16 mm Shank	178958	Double	16 mm	25 mm	50 mm	175 mm
		178840	Three	16 mm	25 mm	50 mm	175 mm
	18 mm Shank	178959	Double	18 mm	25 mm	50 mm	175 mm
		178841	Three	18 mm	25 mm	50 mm	175 mm
	20 mm Shank	178842	Three	20 mm	25 mm	50 mm	175 mm



Series 129-460		Leuco Solid Carbide Latchhole Keyhole Cutter						
Designed for the plunge-cutting and routing of latchholes and keyholes in the door manufacturing industry. Type one is for boring of peepholes and through-holes, type two is for cutting latchholes and keyholes.		NAP GLADU Tool Number	Edge Cut	Cutter Type	A Cutting Diameter	B1 Cutting B2 Height	C Shank Length	Overall Length
	12 mm Shank	179189	Double	One	12 mm	B1 47 mm B2 10 mm	53 mm	110 mm
		179190	Double	One	12 mm	B1 70 mm B2 10 mm	50 mm	130 mm
	14 mm Shank	178359	Double	One	14 mm	B1 47 mm B2 10 mm	45 mm	110 mm
	16 mm Shank	178360	Double	One	16 mm	B1 52 mm B2 11 mm	60 mm	130 mm
		178362	Double	Two	16 mm	B1 65 mm B2 5 mm	60 mm	130 mm
	20 mm Shank	179191	Three	Two	20 mm	B1 70 mm B2 5 mm	60 mm	135 mm



High Speed Steel and Solid Carbide - Straight and Spiral Router Bits

Adapter Bushings - Fiber and Steel					Series BC33-00 BC34-00	
	NAP GLADU Tool Number	X Inside Diameter	Y Outside Diameter	Overall Length	Fiber	This reduces larger collets down to fit smaller shank router bits - increasing the selection of router bits available for use. Available in fiber or steel.
	BC33-01	1/8	1/4	1 1/4		
	BC33-02	3/16	1/4	1 1/4		
	BC33-03	1/4	1/2	1 1/2		
	BC33-04	5/16	1/2	1 1/2		
	BC33-05	3/8	1/2	1 1/2		
	BC34-03	1/4	1/2	1 1/4	Steel	
	BC34-05	3/8	1/2	1 1/4		

Spindle Taper Wiper							Series BC33-60	
	NAP GLADU Tool Number	Handle Diameter	Max Taper Diameter	Taper Length	Total Length	Spindle Type		Used to insure a clean spindle taper before installing collet chucks into CNC router spindles.
	BC33-60	1	1 1/4	2 3/8	6 5/8	ISO-30		
	BC33-62	1	1 3/4	3 1/16	7 1/2	ISO-40		
	BC33-64	1 3/16	2 3/4	4 3/4	9 1/2	ISO-50		

Tool Extender - collet and wrench sold seperately						Series BC33-30	
	NAP GLADU Tool Number	Head Diameter	Shank Length	Extended Length	Use With Collet		Designed to extend the reach of 3/8" and smaller router bits. Used primarily for CNC routers when routing three-dimensional parts. The tool extender should be cut to the appropriate length before use.
	BC33-30	1/2	4	5	ER8	3/8" Shank	
	BC33-32	5/8	5 1/2	6 9/16	ER11	1/2" Shank	
	BC33-36	7/8	5 1/2	6 1/4	ER16		
	BC33-34	5/8	5 1/2	6 1/4	ER11	5/8" Shank	
	BC33-38	7/8	5 1/2	6 9/16	ER16	3/4" Shank	

Series BC33-50		Collets for Tool Extender		Wrenches	
		NAP GLADU Tool Number	Collet Size	Collet Type	BC Saw Tool Number Extension Part Number
		BC33-50	1/8	ER8	BC33-40 BC33-30
		BC33-51	1/8	ER11	BC33-42 BC33-32
		BC33-52	3/16	ER11	BC33-44 BC33-34
		BC33-53	1/4	ER11	BC33-44 BC33-36
		BC33-54	1/8	ER16	BC33-44 BC33-38
		BC33-55	3/16	ER16	
		BC33-56	1/4	ER16	
		BC33-57	5/16	ER16	
		BC33-58	3/8	ER16	
					

Series BC34-50		Collet Life Plug	
		NAP GLADU Tool Number	Collet Size
Collet plugs are designed to prevent full grip collets from collapsing in the back when the shank of the bit does not fully fill the grip collet.		BC34-51	1/4
		BC34-52	3/8
		BC34-53	1/2
		BC34-54	5/8
		BC34-55	3/4
			

Series BC33-10		Collet Brush Kit	
		NAP GLADU Tool Number	Brush Length
		BC33-15	1/4
		BC33-16	3/8
		BC33-17	1/2
		BC33-18	3/4
		BC33-19	1
		BC33-10	Collet Brush Kit (Includes 4 Brushes)
		BC33-25	Collet Brush Kit (Includes 5 Brushes)
			

Insert Router Bits
and Knives




pg 152



pg 152



pg 152



pg 152



pg 153




pg 153



pg 154, 155




pg 154




pg 154



pg 154




pg 154



pg 154



pg 155



pg 155

GBC Insert Router Bits152

GBC Mini Turnover Knives155

ICK Insert Router Bits152

ICK Raker Turnover Knives153-154


ICK Raker Turnover Knives with Countersink155


Screws for Insert Router Bits152


Spoilboard Surfacing Cutters152


Torx Wrenches152



Insert Router Bits and Knives

Spoilboard Surfacing Cutters							Series BC90-000	
	NAP GLADU Tool Number	Shear Angle	Wing Count	A Cutting Diameter	C Shank Length			
	BC90-002	Straight	2	2 1/2	2	1/2" Shank		
	BC90-004	Up-Shear	2	2 1/2	2			
	BC90-006	Straight	3	4	2 1/4	3/4" Shank		
	BC90-008	Up-Shear	3	4	2 1/4			
	BC90-052	Inserts 10/pk					Replacement Parts	
	BC90-102	Screws						
BC90-104	Wrench							
							These are designed for surfacing MDF, particleboard and balsa core spoilboards. Replaceable insert knives permit a quick change of worn inserts.	

Insert Router Bits - GBC and ICK Styles							Series BC90000	
	NAP GLADU Tool Number	A Cutting Diameter	B Cutting Length	C Shank Length	Overall Length	Knife Number		
	90240ICK	5/8	1 11/64	1 3/8	3 5/8	ICK30	1/2" Shank	
	90242ICK	3/4	1 11/64	1 3/8	3 5/8	ICK30		
	90200GBC	1/2	1 3/16	1 3/16	2 7/8	GBC30		
	90210GBC*	5/16	25/32	1 3/8	2 3/8	GBC20		
	90212GBC*	3/8	25/32	1 3/8	2 3/8	GBC20		
	90218GBC*	1/2	25/32	1 3/8	2 3/8	GBC20		
	90220GBC*	1/2	1 3/16	1 3/8	2 3/4	GBC30	3/4" Shank	
	90226GBC*	5/8	2	1 3/8	3 11/16	GBC50		
	90850GBC*	3/4	2	1 9/16	3 7/8	GBC50		
*Non-Plunging ICK Knives inserted with screws GBC "Groove Back Centre," Knives inserted on a groove								
							These router bits are reversible with disposable carbide insert knives, which are economical, costing less than resharpening charges of conventional router bits. Using insert router bits decreases downtime on the job and allows you to maintain strict tolerances.	

Torx Wrenches and Screws for Insert Router Bits					Series 00500 TORX	
	NAP GLADU Tool Number	Corresponding Insert Router		Screw Dimensions		
	00550	90210	90212	M2.5 x 5.5	Screws	
	00560	90200	90218	M3 x 7		
	00570	90240	90242	M3.5 x 4 (for bottom knife)		
	00575	90240	90242	M3.5 x 4 (for main knife)		
	00580	BC90-002 BC90-006	BC90-004 BC90-008	M4 x 5		
	00585	90226 90850	90850	M4 x 11.5		
	T8	90200 90212 90220	90210 90218	—	Torx Wrenches	
	T15	90226 90240 90850	90228 90242	—		
	T20	BC90-002 BC90-006	BC90-004 BC90-008	—		
					These screws fit the insert router bits above and are used to hold the insert knife in place. The torx wrenches are made for use with the insert screws.	

Series ICK		Raker Turnover Knife						
Solid carbide turnover knives made with two cutting edges.		NAP GLADU Tool Number	L Blade Length	H Blade Height	T Blade Thickness	Bevel Angle	Hole Diameter	
General Purpose	ICK7.5G	7.5 mm	12 mm	1.5 mm	55°	4 mm		
	ICK9.6G	9.6 mm	12 mm	1.5 mm	55°	4 mm		
	ICK10.5G	10.5 mm	12 mm	1.5 mm	55°	4 mm		
	ICK11G	11 mm	12 mm	1.5 mm	55°	4 mm		
	ICK13G	13 mm	12 mm	1.5 mm	55°	4 mm		
	ICK15G	15 mm	12 mm	1.5 mm	55°	4 mm		
	ICK15.7G	15.7 mm	12 mm	1.5 mm	55°	4 mm		
	ICK17G	17 mm	12 mm	1.5 mm	55°	4 mm		
	ICK18G	18 mm	12 mm	1.5 mm	55°	4 mm		
	ICK19G	19 mm	12 mm	1.5 mm	55°	4 mm		
	ICK20G	20 mm	12 mm	1.5 mm	55°	4 mm		
MDF, HDF	ICK20X	20 mm	12 mm	1.5 mm	55°	4 mm		
Particle Board	ICK20P	20 mm	12 mm	1.5 mm	55°	4 mm		
Exotic Wood	ICK20E	20 mm	12 mm	1.5 mm	55°	4 mm		
Mirror Finish, Hard	ICK20HM	20 mm	12 mm	1.5 mm	45°	4 mm		
Mirror Finish, Soft	ICK20SM	20 mm	12 mm	1.5 mm	45°	4 mm		

Series ICK		Raker Turnover Knife							
Solid carbide turnover knives made with two cutting edges.		NAP GLADU Tool Number	L Blade Length	H Blade Height	T Blade Thickness	Bevel Angle	Hole Diameter	Centre to Centre	
General Purpose	ICK30G	30 mm	12 mm	1.5 mm	55°	4 mm	14 mm		
	ICK40G	40 mm	12 mm	1.5 mm	55°	4 mm	26 mm		
	ICK50G	50 mm	12 mm	1.5 mm	55°	4 mm	26 mm		
	ICK60G	60 mm	12 mm	1.5 mm	45°	4 mm	26 mm		
	ICK80G	80 mm	13 mm	2.2 mm	55°	4 mm	60 mm		
	ICK100G	100 mm	13 mm	2.2 mm	55°	4 mm	60 mm		
	ICK120G	120 mm	13 mm	2.2 mm	55°	4 mm	60 mm		
MDF, HDF	ICK30X	30 mm	12 mm	1.5 mm	55°	4 mm	14 mm		
	ICK50X	50 mm	12 mm	1.5 mm	55°	4 mm	26 mm		
Particle Board	ICK30P	30 mm	12 mm	1.5 mm	55°	4 mm	14 mm		
	ICK50P	50 mm	12 mm	1.5 mm	55°	4 mm	26 mm		
Exotic Wood	ICK30E	30 mm	12 mm	1.5 mm	55°	4 mm	14 mm		
	ICK50E	50 mm	12 mm	1.5 mm	55°	4 mm	26 mm		
Mirror Finish, Hardwood	ICK30HM	30 mm	12 mm	1.5 mm	45°	4 mm	14 mm		
	ICK40HM	40 mm	12 mm	1.5 mm	45°	4 mm	26 mm		
	ICK50HM	50 mm	12 mm	1.5 mm	45°	4 mm	26 mm		
Mirror Finish, Softwood	ICK30SM	30 mm	12 mm	1.5 mm	45°	4 mm	14 mm		
	ICK40SM	40 mm	12 mm	1.5 mm	45°	4 mm	26 mm		
	ICK50SM	50 mm	12 mm	1.5 mm	45°	4 mm	26 mm		
	ICK60SM	60 mm	12 mm	1.5 mm	45°	4 mm	26 mm		
	ICK80SM	80 mm	12 mm	2.2 mm	45°	4 mm	60 mm		

There are two ways to determine what grade of material is best suited for each individual knife. First, by looking at the inner column, the knives are grouped together based on what grade of material each cuts best. Second, at the end of every tool number there is a letter, which corresponds to the material the knife is designed for. Use these guidelines to choose the correct knife for your application.


Selection Guide for Insert Knife Grades		
The knives are grouped by material, which is listed on the inside column of each chart.	Particle Board	ICK30P 3C ICK50P 5C
	Exotic Wood	ICK30E 3C ICK50E 5C
	Mirror Finish, Hardwood	ICK30HM 3C ICK40HM 4C ICK50HM 5C
	The letters in the part number also represent the material grade.	
	G General Purpose X MDF, HDF P Particle Board E Exotic Wood HM Mirror Finish, Hardwood SM Mirror Finish, Softwood	

Insert Router Bits and Knives


Raker Turnover Knife

Series ICKA


Type One



Type Two



Type Three



NAP GLADU Tool Number	Knife Type	L Blade Length	H Blade Height	T Blade Thickness	Bevel Angle	Hole Diameter
ICKA10.5G	One	10.5 mm	10.5 mm	1.5 mm	55°	4 mm
ICKA12G	One	12 mm	12 mm	1.5 mm	55°	4 mm
ICKA17G	One	17 mm	17 mm	2 mm	55°	4 mm
ICKA19G	One	19 mm	19 mm	2 mm	55°	4 mm
ICKA9G	Two	9 mm	12 mm	1.5 mm	55°	4 mm
ICKA10G	Two	10 mm	12 mm	1.5 mm	55°	4 mm
ICKA12E	One	12 mm	12 mm	1.5 mm	55°	4 mm
ICKA50E*	Three	50 mm	12 mm	1.7 mm	55°	4 mm
ICKA12HM	One	12 mm	12 mm	1.5 mm	45°	4 mm

*Centre to Centre 37 mm

General Purpose



Exotic Wood

Mirror Finish, Hardwood

Solid carbide turnover knives; type one: four cutting edges; type two and type three: two cutting edges and face ground.

Raker Turnover Knife

Series ICKB



NAP GLADU Tool Number	L Blade Length	H Blade Height	T Blade Thickness	Bevel Angle	Hole Diameter	Centre to Centre
ICKB29.5G	29.5 mm	12 mm	1.5 mm	55°	4 mm	14 mm
ICKB30G	30 mm	9 mm	1.5 mm	55°	3.7 mm	14 mm
ICKB39.5G	39.5 mm	12 mm	1.5 mm	55°	4 mm	26 mm
ICKB40G	40 mm	9 mm	1.5 mm	55°	3.7 mm	26 mm
ICKB49.5G	49.5 mm	12 mm	1.5 mm	55°	4 mm	26 mm
ICKB50G	50 mm	9 mm	1.5 mm	55°	3.7 mm	26 mm
ICKB29.5X	29.5 mm	12 mm	1.5 mm	55°	4 mm	14 mm
ICKB30X	30 mm	9 mm	1.5 mm	55°	3.7 mm	14 mm
ICKB50X	50 mm	9 mm	1.5 mm	55°	3.7 mm	26 mm

General Purpose


MDF, HDF

These solid carbide turnover knives are made for shank-type cutters.


Raker Turnover Knife

Series ICKC

Type One



Type Two



NAP GLADU Tool Number	Knife Type	L Blade Length	H Blade Height	T Blade Thickness	a1 Cutting Angle	a2 Angle	Hole Diameter	Centre to Centre
ICKC29.5GL1	One	29.5 mm	12 mm	1.5 mm	a1 15°	a2 15°	4 mm	14 mm
ICKC19.5GL1	Two	19.5 mm	12 mm	1.5 mm	a1 15°	a2 15°	4 mm	—
ICKC19.5GL2	Two	19.5 mm	12 mm	1.5 mm	a1 3.5°	a2 15°	4 mm	—
ICKC49.2GL	Two	49.2 mm	12 mm	1.5 mm	a1 5°	a2 15°	4 mm	26 mm
ICKC29.5GL2	Two	29.5 mm	12 mm	1.5 mm	a1 5°	a2 15°	4 mm	14 mm
ICKC29.5GR1	One	29.5 mm	12 mm	1.5 mm	a1 15°	a2 15°	4 mm	14 mm
ICKC19.5GR	Two	19.5 mm	12 mm	1.5 mm	a1 3.5°	a2 15°	4 mm	—
ICKC29.5GR2	Two	29.5 mm	12 mm	1.5 mm	a1 5°	a2 15°	4 mm	14 mm
ICKC49.2GR	Two	49.2 mm	12 mm	1.5 mm	a1 5°	a2 15°	4 mm	26 mm


General Purpose, Left Hand

General Purpose, Right Hand

Solid carbide turnover knives; type one: two cutting edges, chamfer; type two: two cutting edges and edge bevel.

Series ICKD		Turnover Knife with Countersink							
Solid carbide insert knives with countersink holes. Type one: made with a spur for cutterheads; type two: raker knife made for a spiral cutter head. The machine type is noted in the chart.		NAP GLADU Tool Number	Knife Type	L Blade Length	H Blade Height	T Blade Thickness	Bevel Angle	Hole Diameter	Router Machine
	General Purpose	ICKD14G1	One	14 mm	14 mm	1.2 mm	60°	8.6 mm	—
		ICKD14G2	One	14 mm	14 mm	1.2 mm	60°	8.6 mm	Holz-Her
		ICKD14G3	One	14 mm	14 mm	2 mm	60°	6.3 mm	—
		ICKD14G4*	One	14 mm	14 mm	2 mm	60°	6.3 mm	—
		ICKD13.6G	Two	13.6 mm	13.6 mm	2 mm	45°	6.3 mm	Fisher Brugg
		ICKD14.3G	Two	14.3 mm	14.3 mm	2.5 mm	55°	6.3 mm	Homag
		ICKD20G	Two	20 mm	14.3 mm	2.5 mm	55°	6.3 mm	Homag
	Exotic Wood	ICKD14E	One	14 mm	14 mm	2 mm	60°	6.3 mm	—
	Hardwood	ICKD15H	Two	15 mm	15 mm	2.5 mm	60°	6.4 mm	—
	Mirror Finish, Hardwood	ICKD14HM	One	14 mm	14 mm	2 mm	60°	6.3 mm	—

*Marked for easier changeovers



Series GF GBC		Mini Turnover Knife					
Turnover knives, made for general purpose use; GF: with two cutting edges; GBC: with two cutting edges, end sharpened.		NAP GLADU Tool Number	Knife Type	L Blade Length	H Blade Height	T Blade Thickness	
	General Purpose	GF12G	GF	12 mm	5.5 mm	1.1 mm	
		GF20G	GF	20 mm	5.5 mm	1.1 mm	
		GF40G	GF	40 mm	5.5 mm	1.1 mm	
		GF50G	GF	50 mm	5.5 mm	1.1 mm	
		GBC12G	GBC	12 mm	5.5 mm	1.1 mm	
		GBC20G1	GBC	20 mm	4.1 mm	1.1 mm	
		GBC20G2	GBC	20 mm	5.5 mm	1.1 mm	
		GBC25G	GBC	25 mm	5.5 mm	1.1 mm	
		GBC30G	GBC	30 mm	5.5 mm	1.1 mm	
		GBC50G	GBC	50 mm	5.5 mm	1.1 mm	



Leuco Diamond Tooling
Inserts and Clamping



pg 158



pg 158



pg 158



pg 158



pg 159



pg 159



pg 159



pg 159

Boring Bits	159
Brazed Tooling	159
Clamping Systems	159
Diamond Tooling	158
Drill Bits	159
Insert Knives	158
Insert Tooling	158
Saw Blades	158

Leuco Insert Tooling and Clamping Systems

LEUCO

Leuco Ledermann GmbH is a world leader in the research, design and manufacturing of tooling for the woodworking and plastics industry. As the exclusive dealer of Leuco in Canada, NAP GLADU can supply you with the complete Leuco line of tools including:

Diamond Tooling			LEUCO
			Diamond Tooling Includes: • Router Bits • Bore Tools • Edge Banding Cutters • Hogger Segments • Saw Blades • Custom Tools

Saw Blades			LEUCO
			

Insert Tooling and Insert Knives			LEUCO
			Insert Tooling Includes: • Router Bits • Bore Tools • Super Profilers • EcoPro • Edge Banding Cutters • Moulder Tooling • Custom Tools
			Insert Knives Include: • Straight • Profiled • Custom Knives

Please contact a NAP GLADU Customer Service Representative to request your Leuco catalogue and your NAP GLADU CNC Tooling catalogue.

LEUCO	Clamping Systems		
Clamping Systems Includes: • Collets • Hydraulics • TriBos		 HSK	 HSK
	 QUICK KLACK	 SK	 PS
	 ER	 ER	 ER

LEUCO	Brazen Tooling	Drill Bits	Boring Bits
			



Dowel Drills, Hinge Boring Bits and Accessories



pg 162



pg 163



pg 163



pg 164



pg 165



pg 166-167



pg 167-168



pg 169

Adaptors163

Boring Chucks169

Brad Point Dowel Drills, Carbide Tipped162

Countersinks | Counterbores, Carbide Tipped165


Countersinks | Counterbores, Custom Solid165-167

Hinge Boring Bits167-168


V-Point Through Hole Dowel Drills, Carbide Tipped164

V-Point Through Hole Dowel Drills, Solid Carbide163

Dowel Drills, Hinge Boring Bits and Accessories

Carbide Tipped Brad Point Dowel Drills - Length 57.5 mm						Series 50000	
	NAP GLADU Tool Number	A Cutting Diameter	B Twist Length	C Shank Length	Overall Length	10 mm Shank	These are brad point dowel drills which have a flat chucking surface and an adjustable set screw. Please specify either “R” or “L” for right or left hand rotation when ordering.
	50110	4 mm	30 mm	20 mm	57.5 mm		
	50114	4.5 mm	30 mm	20 mm	57.5 mm		
	50116	5 mm	30 mm	20 mm	57.5 mm		
	50117	5.1 mm	30 mm	20 mm	57.5 mm		
	50118	5.2 mm	30 mm	20 mm	57.5 mm		
	50120	6 mm	30 mm	20 mm	57.5 mm		
	50122	1/4"	30 mm	20 mm	57.5 mm		
	50124	7 mm	30 mm	20 mm	57.5 mm		
	50126	8 mm	30 mm	20 mm	57.5 mm		
	50127	8.1 mm	30 mm	20 mm	57.5 mm		
	50128	8.2 mm	30 mm	20 mm	57.5 mm		
	50129	9 mm	30 mm	20 mm	57.5 mm		
	50130	3/8"	30 mm	20 mm	57.5 mm		
	50132	10 mm	30 mm	20 mm	57.5 mm		
	50134	11 mm	30 mm	20 mm	57.5 mm		
	50136	12 mm	30 mm	20 mm	57.5 mm		
	50138	1/2"	30 mm	20 mm	57.5 mm		
	50140	14 mm	30 mm	20 mm	57.5 mm		
	50142	15 mm	30 mm	20 mm	57.5 mm		
	50144	16 mm	30 mm	20 mm	57.5 mm		

All sizes available in right or left hand rotation

Carbide Tipped Brad Point Dowel Drills - Length 70 mm						Series 50000	
	NAP GLADU Tool Number	A Cutting Diameter	B Twist Length	C Shank Length	Overall Length	10 mm Shank	These are brad point dowel drills which have a flat chucking surface and an adjustable set screw. Please specify either “R” or “L” for right or left hand rotation when ordering.
	50158	4 mm	43 mm	20 mm	70 mm		
	50160	5 mm	43 mm	20 mm	70 mm		
	50161	5.1 mm	43 mm	20 mm	70 mm		
	50162	5.2 mm	43 mm	20 mm	70 mm		
	50163	6 mm	43 mm	20 mm	70 mm		
	50164	1/4"	43 mm	20 mm	70 mm		
	50166	7 mm	43 mm	20 mm	70 mm		
	50167*	7.5 mm	43 mm	20 mm	70 mm		
	50168	8 mm	43 mm	20 mm	70 mm		
	50169	8.1 mm	43 mm	20 mm	70 mm		
	50170	8.2 mm	43 mm	20 mm	70 mm		
	50171	9 mm	43 mm	20 mm	70 mm		
	50172	3/8"	43 mm	20 mm	70 mm		
	50174	10 mm	43 mm	20 mm	70 mm		
	50176	11 mm	43 mm	20 mm	70 mm		
	50178	12 mm	43 mm	20 mm	70 mm		
	50180	1/2"	43 mm	20 mm	70 mm		
	50182	13 mm	43 mm	20 mm	70 mm		
	50184	14 mm	43 mm	20 mm	70 mm		
	50185	15 mm	43 mm	20 mm	70 mm		
	50186	16 mm	43 mm	20 mm	70 mm		

* Custom Size

All sizes available in right or left hand rotation

Series 53000		Metric Solid Carbide V-Point Dowel Drills				
V-Point drills are for clean through hole drilling available in right and left hand rotation. Drills are straight shank and must be used in adaptors below if 10 mm shank is required. Please specify "R" or "L" for right or left hand rotation when ordering.		NAP GLADU Tool Number	A Cutting Diameter	B Twist Length	C Shank Length	Overall Length
	2 mm Shank	53210	2 mm	22 mm	27 mm	49 mm
	2.5 mm Shank	53212	2.5 mm	27 mm	28 mm	55 mm
	3 mm Shank	53214	3 mm	27 mm	28 mm	55 mm
	3.2 mm Shank	53216	3.2 mm	27 mm	28 mm	55 mm
	3.5 mm Shank	53218	3.5 mm	30 mm	25 mm	55 mm
	4 mm Shank	53220	4 mm	30 mm	25 mm	55 mm
	4.5 mm Shank	53222	4.5 mm	30 mm	25 mm	55 mm
	5 mm Shank	53224	5 mm	30 mm	25 mm	55 mm
All sizes available in right or left hand rotation						



Series 01200		Adaptors - allow small size drills to fit metric boring chucks			
These allow the solid carbide straight shank drills above to fit in machines requiring 10 mm shanks with a flat chucking surface.	NAP GLADU Tool Number	X Inside Diameter	Y Outside Diameter	Adaptor Length	
	01210	2 mm	10 mm	23 mm	
	01212	2.5 mm	10 mm	23 mm	
	01214	3 mm	10 mm	23 mm	
	01216	3.2 mm	10 mm	23 mm	
	01218	3.5 mm	10 mm	23 mm	
	01220	4 mm	10 mm	23 mm	
	01222	4.5 mm	10 mm	23 mm	
	01224	5 mm	10 mm	23 mm	



Series 53000A		Adaptors - allow small size drills to fit metric boring chucks			
These allow the solid carbide straight shank drills, pictured above, to fit in machines requiring 10 mm shanks with a flat chucking surface.		NAP GLADU Tool Number	A Corresponding Drill Diameter	C Shank Length	Adaptor Length
	10 mm Shank	53210A	2 mm	20 mm	38 mm
		53212A	2.5 mm	20 mm	38 mm
		53214A	3 mm	20 mm	38 mm
		53216A	3.2 mm	20 mm	38 mm
		53218A	3.5 mm	20 mm	38 mm
		53220A	4 mm	20 mm	38 mm
		53222A	4.5 mm	20 mm	38 mm
		53224A	5 mm	20 mm	38 mm



Dowel Drills, Hinge Boring Bits and Accessories

Carbide Tipped V-Point Dowel Drills - Length 57.5 mm						Series 53000	
	NAP GLADU Tool Number	A Cutting Diameter	B Twist Length	C Shank Length	Overall Length	10 mm Shank	Use one of these V-Point tips for clean through hole drilling and flat chucking surfaces with an adjustable set screw. Please specify “R” or “L” for right or left hand rotation when ordering.
	53110	5 mm	27 mm	26 mm	57.5 mm		
	53112	6 mm	27 mm	26 mm	57.5 mm		
	53113	1/4"	27 mm	26 mm	57.5 mm		
	53114	7 mm	28 mm	25 mm	57.5 mm		
	53116	8 mm	27 mm	26 mm	57.5 mm		
	53120	10 mm	27 mm	26 mm	57.5 mm		
	53122	12 mm	33 mm	20 mm	57.5 mm		
All sizes available in right or left hand rotation							

Carbide Tipped Brad Point Dowel Drills - Length 70 mm						Series 53000	
	NAP GLADU Tool Number	A Cutting Diameter	B Twist Length	C Shank Length	Overall Length	10 mm Shank	Use one of these V-Point tips for clean through hole drilling and flat chucking surfaces with an adjustable set screw. Please specify “R” or “L” for right or left hand rotation when ordering.
	53126	4 mm	35 mm	26 mm	70 mm		
	53128	3/16"	35 mm	26 mm	70 mm		
	53130	5 mm	35 mm	26 mm	70 mm		
	53131	7/32"	35 mm	26 mm	70 mm		
	53132	6 mm	35 mm	26 mm	70 mm		
	53133	1/4"	35 mm	26 mm	70 mm		
	53134	7 mm	35 mm	26 mm	70 mm		
	53136	8 mm	35 mm	26 mm	70 mm		
	53138	9 mm	35 mm	26 mm	70 mm		
	53139	3/8"	35 mm	26 mm	70 mm		
	53140	10 mm	35 mm	26 mm	70 mm		
	53142	12 mm	35 mm	26 mm	70 mm		
	53144	1/2"	35 mm	26 mm	70 mm		
All sizes available in right or left hand rotation							

Series 55000		Carbide Tipped Countersinks - for Metric Twist Drills				
Designed for drilling countersinks in solid wood and panel materials. A socket screw will hold the countersink to drills 3 mm to 6 mm in diameter.	10 mm Shank	NAP GLADU Tool Number	Rotation Direction	A1 Fits Drill Diameter	A2 Countersink Size	Overall Length
		55102	Right			
		55104	Left	3 mm	15 mm	58 mm
		55106	Right	3.5 mm	15 mm	58 mm
		55108	Right			
		55110	Left	4 mm	15 mm	58 mm
		55112	Right			
		55114	Left	4.5 mm	15 mm	58 mm
		55116	Right			
		55118	Left	5 mm	15 mm	58 mm
		55120	Right			
		55122	Left	6 mm	15 mm	58 mm

All sizes available in right or left hand rotation




Series 55000		Countersinks for Dowel Drills - Twist and Shank Clamping			
These countersinks are for attachment to the spiral flutes of brad point and taper point drills (Series 51000 and 53000). All countersinks are available in right or left hand rotation. Please specify “R” or “L” for right or left when ordering.	NAP GLADU Tool Number	X Inside Diameter	Y Outside Diameter	Adaptor Length	
	55000	4 mm	14 mm	15 mm	
	55002	5 mm	16 mm	15 mm	
	55004	6 mm	16 mm	15 mm	
	55006	7 mm	18 mm	15 mm	
	55008	8 mm	18 mm	15 mm	
	55010	9 mm	20 mm	15 mm	
	55012	10 mm	20 mm	15 mm	
	55014	12 mm	22 mm	15 mm	
	55020*	5-10 mm	20 mm	16.5 mm	
	55022*	10-12 mm	22 mm	16.5 mm	


All sizes available in right or left hand rotation

*These countersinks clamp onto Series 51000 and 53000 drills






Series 56000		Custom Counterbores for Dowel Drills - Twist Clamping			
These counterbores are for attachment to the spiral flutes of brad point and taper point drills (Series 51000 and 53000). The counterbores are custom made and require 4-6 weeks for delivery. Please specify the inside diameter required when ordering, as well as “R” or “L” for right or left hand rotation.	NAP GLADU Tool Number	X Inside Diameter	Y Outside Diameter	Adaptor Length	
	56020	Custom	20 mm	20 mm	
	56025	Custom	25 mm	20 mm	
	56030	Custom	30 mm	20 mm	
	56035	Custom	35 mm	20 mm	
	56040	Custom	40 mm	20 mm	
All sizes available in right or left hand rotation					

All sizes available in right or left hand rotation



Dowel Drills, Hinge Boring Bits and Accessories

Custom Solid Counterbore - High Speed Steel						Series 57000	
	A1 Large Diameter	A2 Small Diameter	B Twist Length	C Counterbore Length	Overall Length	Custom Shank	Custom solid counterbore made from high speed steel, when ordering, please state the direction of rotation and the required dimensions according to the diagram shown. All items are custom made and require 4-6 weeks delivery. Extra charges will be added for the addition of v-points, threaded shanks, shanks with driving flats and length adjusting screws.
	Up To: 15 mm	Custom	Custom	Custom	Up To: 130 mm		
	20 mm						
	25 mm						
	30 mm						
	40 mm						
	50 mm						
	All sizes available in right or left hand rotation						
Custom Solid Counterbore - Carbide Tipped						Series 58000	
	A1 Large Diameter	A2 Small Diameter	B Twist Length	C Counterbore Length	Overall Length	Custom Shank	Custom solid counterbore made with carbide tips, when ordering, please state the direction of rotation and the required dimensions according to the diagram shown. All items are custom made and require 4-6 weeks delivery. Extra charges will be added for the addition of v-points, threaded shanks, shanks with driving flats and length adjusting screws.
	Up To: 15 mm	Custom	Custom	Custom	Up To: 130 mm		
	20 mm						
	25 mm						
	30 mm						
	40 mm						
	50 mm						
	All sizes available in right or left hand rotation						
Solid Countersink - Carbide Tipped						Series 59000	
	BC Saw Tool Number	A Small Diameter	B Twist Length	C Countersink Length	Overall Length	10 mm Shank	Custom solid countersink made with carbide tips, when ordering, please state the direction of rotation and the required dimensions according to the diagram shown. All items are custom made and require 4-6 weeks delivery.
	59005	5 mm	15 mm	15 mm	50 mm		
	59006	6 mm	15 mm	15 mm	50 mm		
	59008	8 mm	15 mm	15 mm	50 mm		
	59010	10 mm	15 mm	15 mm	50 mm		
	59105	5 mm	20 mm	15 mm	55 mm		
	59106	6 mm	20 mm	15 mm	55 mm		
	59108	8 mm	20 mm	15 mm	55 mm		
	59110	10 mm	20 mm	15 mm	55 mm		
	All solid countersink tools have a 20 mm Shank Length All sizes available in right or left hand rotation						

Series 60000		Solid Countersink - Carbide Tipped							Custom Sizes Available	
Custom solid countersink made with carbide tips, when ordering, please state the direction of rotation and the required dimensions according to the diagram shown. All items are custom made and require 4-6 weeks delivery.	10 mm Shank	NAP GLADU Tool Number	A Small Diameter	B Twist Length	C End to Twist	D V-Point Length	Overall Length			
		60005	5 mm	22.5 mm	57.5 mm	4 mm	61.5 mm			
		60006	6 mm	22.5 mm	57.5 mm	5 mm	62.5 mm			
		60008	8 mm	22.5 mm	57.5 mm	6.5 mm	64 mm			
		60105	5 mm	35 mm	70 mm	4 mm	74 mm			
		60106	6 mm	35 mm	70 mm	5 mm	75 mm			
		60108	8 mm	35 mm	70 mm	6.5 mm	76.5 mm			
		60110	10 mm	35 mm	70 mm	8.5 mm	78.5			
		All solid countersink tools have a 20 mm Shank Length and a 15 mm Countersink Length All sizes available in right or left hand rotation								

Series 52000		Carbide Tipped Hinge Boring Bits - Length 57.5 mm				
This bit has two cutting edges, two spurs and a centre point to provide for clean hole boring for concealed hinges. Cylindrical 10 mm shanks have a flat chucking surface and adjustable set screw for optimum clamping. All boring bits are available in right or left hand rotation, please specify “R” or “L” when ordering.	10 mm Shank	NAP GLADU Tool Number	A Cutting Diameter	C Shank Length	Overall Length	
		52110	15 mm	26 mm	57.5 mm	
		52112	16 mm	26 mm	57.5 mm	
		52114	18 mm	26 mm	57.5 mm	
		52116	20 mm	26 mm	57.5 mm	
		52118	22 mm	26 mm	57.5 mm	
		52120	24 mm	26 mm	57.5 mm	
		52122	25 mm	26 mm	57.5 mm	
		52124	26 mm	26 mm	57.5 mm	
		52126	28 mm	26 mm	57.5 mm	
		52128	30 mm	26 mm	57.5 mm	
		52130	32 mm	26 mm	57.5 mm	
		52134	35 mm	26 mm	57.5 mm	
		52138	38 mm	26 mm	57.5 mm	
		52140	40 mm	26 mm	57.5 mm	
All sizes available in right or left hand rotation						

Series 52000		Carbide Tipped Hinge Boring Bits - Length 70 mm				
This bit has two cutting edges, two spurs and a centre point to provide for clean hole boring for concealed hinges. The cylindrical 10 mm shanks have a flat chucking surface and adjustable set screw for optimum clamping. When ordering, please specify “R” for right hand rotation or “L” for left hand rotation.	10 mm Shank	NAP GLADU Tool Number	A Cutting Diameter	C Shank Length	Overall Length	
		52142	15 mm	26 mm	70 mm	
		52144	18 mm	26 mm	70 mm	
		52146	20 mm	26 mm	70 mm	
		52148	25 mm	26 mm	70 mm	
		52150	26 mm	26 mm	70 mm	
		52152	30 mm	26 mm	70 mm	
		52154	35 mm	26 mm	70 mm	
		52156	40 mm	26 mm	70 mm	
All sizes available in right or left hand rotation						

Dowel Drills, Hinge Boring Bits and Accessories

Carbide Tipped Hinge Boring Bits - Length 90 mm					Series 52000	
	NAP GLADU Tool Number	A Cutting Diameter	C Shank Length	Overall Length	10 mm Shank	This bit has two cutting edges, two spurs and a centre point to provide for clean hole boring for concealed hinges. The cylindrical 10 mm shanks have a flat chucking surface and an adjustable set screw for optimum clamping. <i>These boring bits are only available for right hand rotation.</i>
	52160	8 mm	30 mm	90 mm		
	52161	10 mm	30 mm	90 mm		
	52162	11 mm	30 mm	90 mm		
	52163	12 mm	30 mm	90 mm		
	52164	13 mm	30 mm	90 mm		
	52165	14 mm	30 mm	90 mm		
	52166	15 mm	30 mm	90 mm		
	52167	16 mm	30 mm	90 mm		
	52168	17 mm	30 mm	90 mm		
	52169	18 mm	30 mm	90 mm		
	52170	19 mm	30 mm	90 mm		
	52171	20 mm	30 mm	90 mm		
	52172	21 mm	30 mm	90 mm		
	52173	22 mm	30 mm	90 mm		
	52174	23 mm	30 mm	90 mm		
	52175	24 mm	30 mm	90 mm		
	52176	25 mm	30 mm	90 mm		
	52177	26 mm	30 mm	90 mm		
	52178	27 mm	30 mm	90 mm		
	52179	28 mm	30 mm	90 mm		
	52180	29 mm	30 mm	90 mm		
	52181	30 mm	30 mm	90 mm		
	52182	31 mm	30 mm	90 mm		
	52183	32 mm	30 mm	90 mm		
	52184	33 mm	30 mm	90 mm		
	52185	34 mm	30 mm	90 mm		
	52186	35 mm	30 mm	90 mm		
	52187	36 mm	30 mm	90 mm		
	52188	37 mm	30 mm	90 mm		
	52189	38 mm	30 mm	90 mm		
	52190	40 mm	30 mm	90 mm		
	52191	42 mm	30 mm	90 mm		
	52192	44 mm	30 mm	90 mm		
	52193	45 mm	30 mm	90 mm		
	52194	46 mm	30 mm	90 mm		
	52195	48 mm	30 mm	90 mm		
	52196	50 mm	30 mm	90 mm		
	52197	55 mm	30 mm	90 mm		
	52198	58 mm	30 mm	90 mm		
	52199	60 mm	30 mm	90 mm		

Series 5		Miscellaneous Boring Chucks								
These 7/16-14 threaded shank chucks accept straight shank drills. They are available in both right and left hand rotations.	7/16-14 Thread	NAP GLADU Tool Number	Rotation Direction	X	Inside Diameter					
		BC62473	Right		1/8					
		BC62474	Right		5/32					
		BC62475	Right		3/16					
		BC62476	Right		7/32					
		BC62477	Right		1/4					
		BC62478	Right		9/32					
		BC62479	Right		5/16					
		BC62480	Right		3/8					
		BC62481	Right		7/16					
		BC62482	Right		1/2					
		BC62483	Right		10 mm					
		BC62484	Left		1/8					
		BC62485	Left		5/32					
		BC62486	Left		3/16					
		BC62487	Left		7/32					
		BC62488	Left		1/4					
		BC62489	Left		9/32					
		BC62490	Left		5/16					
		BC62491	Left		3/8					
		BC62492	Left		7/16					
		BC62493	Left		1/2					
		BC62494	Left		10 mm					
Series 7		Metric Boring Chucks for European Machinery								
These chucks will allow the adaptation of North American bits for use on European boring machines.	8 Thread	NAP GLADU Tool Number	Rotation Direction	X	Inside Diameter	Y	Outside Diameter	Overall Length	Corresponding Machine(s)	
		BC62239	Right		10 mm	16 mm	40 mm	Nottmeyer		
		BC62240	Left		10 mm	16 mm	40 mm	Nottmeyer		
		BC62245	Right		10 mm	16 mm	50 mm	Bilek		
	10 Thread	BC62246	Left		10 mm	16 mm	50 mm	Knoevenagel		
		BC62241	Right		10 mm	19 mm	40 mm	Holtzma, Torwegge, Mayer, Knoevenagel		
		BC62242	Left		10 mm	19 mm	40 mm	Holtzma, Torwegge, Mayer, Knoevenagel		
		BC62243	Right		10 mm	19 mm	41 mm	Alberti, Balestrini, Busellato, Torwegge, Biesse, Vitap, Weeke, Gessner, Morbidelli		
		BC62244	Left		10 mm	19 mm	41 mm	Alberti, Balestrini, Busellato, Torwegge, Biesse, Vitap, Weeke, Gessner, Morbidelli		
		BC62247	Right		10 mm	19 mm	42 mm	Morbidelli, Nottmeyer		
		BC62248	Left		10 mm	19 mm	42 mm	Morbidelli, Nottmeyer		
		BC62239								
		BC62245								
		BC62241								
		BC62247								

Boring Tools



pg 172-173



pg 174-175



pg 176



pg 177



pg 178



pg 179

Carbide Tipped Boring Drills	176
Forstner Bits	172-173
Holesaws	178
Holesaw Accessories	179
Multispur Bits	174-175
Plug Cutters	177


Boring Tools

Imperial Forstner Bits				Series 51000	
	NAP GLADU Tool Number	A Cutting Diameter	Overall Length	5/16" Shank	
	51300	1/4	3 1/2		
	51302	3/8	3 1/2		
	51304	1/2	3 1/2		
	51306	9/16	3 1/2		
	51308	5/8	3 1/2		
	51310	11/16	3 1/2		
	51312	3/4	3 1/2		
	51314	13/16	3 1/2		
	51316	7/8	3 1/2		
	51318	15/16	3 1/2		
	51320	1	3 1/2		
	51322	1 1/16	3 1/2		
	51324	1 1/8	3 1/2		
	51326	1 3/16	3 1/2		
	51328	1 1/4	3 1/2	3/8" Shank	
	51330	1 5/16	3 1/2		
	51332	1 3/8	3 1/2		
	51334	1 1/2	3 1/2		
	51336	1 5/8	3 5/8		
	51338	1 3/4	3 5/8		
	51340	1 7/8	3 5/8		
	51342	2	3 5/8		
	51344	2 1/8	3 5/8	1/2" Shank	
	51346	2 1/4	3 5/8		
	51348	2 3/8	6 1/4		
	51350	2 1/2	6 1/4		
	51352	2 5/8	6 1/4		
	51354	2 3/4	6 1/4		
	51356	2 7/8	6 1/4		
	51358	3	6 1/4		
A versatile high speed steel tool used in drilling true sized holes. Forstner bits are guided by their outside edge instead of a centre point. This enables the bits to drill angled holes, pocket holes, flat bottom holes or completely through holes.					

Series 51000		Metric Forstner Bits		
A versatile high speed steel tool used in drilling true sized holes. Forstner bits are guided by their outside edge instead of a centre point. This enables the bits to drill angled holes, pocket holes, flat bottom holes or completely through holes.	8 mm Shank	NAP GLADU Tool Number	A Cutting Diameter	Overall Length
		51800	10 mm	90 mm
		51802	12 mm	90 mm
		51804	13 mm	90 mm
		51806	14 mm	90 mm
		51808	15 mm	90 mm
		51810	16 mm	90 mm
		51814	18 mm	90 mm
		51816	19 mm	90 mm
		51818	20 mm	90 mm
		51820	21 mm	90 mm
		51822	22 mm	90 mm
		51826	24 mm	90 mm
		51828	25 mm	90 mm
		51830	26 mm	90 mm
	10 mm Shank	51832	28 mm	90 mm
		51834	30 mm	90 mm
		51836	32 mm	90 mm
		51838	34 mm	90 mm
		51840	35 mm	90 mm
		51842	36 mm	90 mm
		51844	38 mm	90 mm
		51846	40 mm	90 mm
		51848	45 mm	90 mm
		51850	50 mm	90 mm
				

Series 51700		Extension Shank - for forstner and drill bits		
Either 130 mm or 250 mm long extension shanks can help get at hard to reach places when drilling or boring.	NAP GLADU Tool Number	A Corresponding Shank Diameter	Overall Length	
	51700	8 mm	130 mm	
	51702	8 mm	250 mm	
	51704	10 mm	130 mm	
	51706	10 mm	250 mm	
				

Boring Tools

Multispur Bits				Series 149	
	NAP GLADU Tool Number	A Cutting Diameter	Overall Length	1/2" Shank	Designed with a precision ground cutting edge to bore fast and lift chips cleanly up and out of the hole. The multiple outlining spurs bore clean holes without chipping or splintering the surface of the wood, the brad point allows for positive centering. Perfect for boring through veneers. Works well for boring with or across the grain, as well as boring overlapping holes. Heat treating ensures tough, uniformly hard cutting edges, plus long tool life.
	BC62736	1/2	6		
	BC62737	9/16	6		
	BC62738	5/8	6		
	BC62739	11/16	6		
	BC62740	3/4	6		
	BC62741	13/16	6		
	BC62742	7/8	6		
	BC62743	15/16	6		
	BC62744	1	6		
	BC62745	1 1/16	6		
	BC62746	1 1/8	6		
	BC62747	1 3/16	6		
	BC62748	1 1/4	6		
	BC62749	1 5/16	6		
	BC62750	1 3/8	6		
	BC62751	1 7/16	6		
	BC62752	1 1/2	6		
	BC62753	1 9/16	6		
	BC62754	1 5/8	6		
	BC62755	1 11/16	6		
	BC62756	1 3/4	6		
	BC62757	1 13/16	6		
	BC62758	1 7/8	6		
	BC62759	1 15/16	6		
	BC62760	2	6		
	BC62761	2 1/8	6		
	BC62762	2 1/4	6		
	BC62763	2 3/8	6		
	BC62764	2 1/2	6		
	BC62765	2 5/8	6		
	BC62766	2 3/4	6		
	BC62767	2 7/8	6		
	BC62768	3	6		
	BC62774	3 1/8	6		
	BC62775	3 1/4	6		
	BC62776	3 1/2	6		
	BC62777	3 3/4	6		
	BC62778	4	6		
BC62769	3 1/8	6	3/4" Shank		
BC62770	3 1/4	6			
BC62771	3 1/2	6			
BC62772	3 3/4	6			
BC62773	4	6			


Series 149CT

Designed identical to Series 149 bits, except furnished with carbide tips.

Carbide Tipped Multispur Bits

1/2" Shank


NAP GLADU Tool Number	A	Cutting Diameter	Overall Length
BC62779*		3/4	6
BC62780*		7/8	6
BC62781*		15/16	6
BC62782*		1	6
BC62783		1 1/16	6
BC62784		1 1/8	6
BC62785		1 3/16	6
BC62786		1 1/4	6
BC62787		1 5/16	6
BC62788		1 3/8	6
BC62789		1 7/16	6
BC62790		1 1/2	6
BC62791		1 9/16	6
BC62792		1 5/8	6
BC62793		1 3/4	6
BC62794		1 7/8	6
BC62795		2	6
BC62796		2 1/8	6
BC62811		2 1/4	6
BC62812		2 3/8	6
BC62813		2 1/2	6
BC62814		2 5/8	6
BC62815		2 3/4	6
BC62816		3	6
BC62821		3 1/4	6
BC62822		3 1/2	6
BC62823		3 3/4	6
BC62824		4	6
3/4" Shank			
BC62817		3 1/4	6
BC62818		3 1/2	6
BC62819		3 3/4	6
BC62820		4	6




*Carbide tips on every other tooth



Boring Tools

Carbide Tipped Two Wing Boring Drills				Series 811CT	
	NAP GLADU Tool Number	A Cutting Diameter	Overall Length	1/2" Shank	These bits are designed to bore clean, accurate holes on plastic laminates and wood. Spurs outline the hole before the chip lifters plane the material to help prevent cracked edges.
	BC62797	1	6		
	BC62798	1 1/8	6		
	BC62799	1 1/4	6		
	BC62800	1 3/8	6		
	BC62801	1 1/2	6		
	BC62802	1 5/8	6		
	BC62803	1 3/4	6		
	BC62804	1 7/8	6		
	BC62805	2	6		
	BC62806	2 1/8	6		
	BC62807	2 1/4	6		
	BC62808	2 1/2	6		
	BC62809	2 3/4	6		
	BC62810	3	6		

Carbide Tipped Three Wing Boring Drills				Series 812CT	
	NAP GLADU Tool Number	A Cutting Diameter	Overall Length	1/2" Shank	Designed to bore Formica and tempered Masonite, as well as abrasive materials and hardwoods.
	BC62825	1/2	6		
	BC62826	9/16	6		
	BC62827	5/8	6		
	BC62828	11/16	6		
	BC62829	3/4	6		
	BC62830	13/16	6		
	BC62831	7/8	6		
	BC62832	1	6		
	BC62833	1 1/8	6		
	BC62834	1 1/4	6		
	BC62835	1 3/8	6		
	BC62836	1 1/2	6		
	BC62837	1 5/8	6		
	BC62838	1 3/4	6		
	BC62839	1 7/8	6		
	BC62840	2	6		
	BC62841	2 1/8	6		
	BC62842	2 1/4	6		
	BC62843	2 1/2	6		

Series 140

Designed to cut cross-grain plugs or end-grain dowels up to 2" in length. Plugs up to 1" thick are easily cleared through the 1 1/8" opening.

1/2" Shank

Carbon Steel Plug Cutters - Softwood

NAP GLADU Tool Number	A Plug Size	B Cutting Height	Overall Length
BC62871	3/8	2 1/8	4 1/2
BC62872	1/2	2 1/8	4 1/2
BC62873	5/8	2 1/8	4 1/2
BC62874	3/4	2 1/8	4 1/2
BC62875	1	2 1/8	4 1/2



Series 600P

These bits are designed to cut a true-sized plug under almost any condition. These cutters work more effectively at clearing chips than Series 140 plug cutters because of the multiple spiral flutes.

1/2" Shank

Carbon Steel Spiral Plug Cutters - Hardwood

NAP GLADU Tool Number	A Plug Size	B Cutting Height	Overall Length
BC62876	3/8	2	4 1/2
BC62877	1/2	2	4 1/2
BC62878	5/8	2	4 1/2
BC62879	3/4	2	4 1/2
BC62880	7/8	2	4 1/2
BC62881	1	2	4 1/2
BC62882	1 1/4	2	4 1/2
BC62883	1 1/2	2	4 1/2
BC62884	1 3/4	2	4 1/2
BC62885	2	2	4 1/2



Boring Tools

Bimetal Variable Pitch Holesaws					Series H0000
	NAP GLADU Tool Number	A (in) Cutting Diameter	A (mm) Cutting Diameter	Arbor Number	These holesaws are designed to cut through any machinable material including cast iron, tool and stainless steel, brass, bronze, plastic, aluminum and wood. A high speed steel, 4/6 variable pitch cutting edge is welded to a tough alloy steel body to provide extra strength. A 1 1/2" cutting depth is obtained when these holesaws are used with the arbor found on page 179.
	H0096	9/16	14 mm	ARB 1, 2, 3	
	H0058	5/8	16 mm	ARB 1, 2, 3	
	H0016	11/16	17 mm	ARB 1, 2, 3	
	H0034	3/4	19 mm	ARB 1, 2, 3	
	H0036	13/16	21 mm	ARB 1, 2, 3	
	H0078	7/8	22 mm	ARB 1, 2, 3	
	H1056	15/16	24 mm	ARB 1, 2, 3	
	H0100	1	25 mm	ARB 1, 2, 3	
	H0116	1 1/16	27 mm	ARB 1, 2, 3	
	H0118	1 1/8	29 mm	ARB 1, 2, 3	
	H0136	1 3/16	30 mm	ARB 1, 2, 3	
	H0114	1 1/4	32 mm	ARB 4, 5, 6	
	H0156	1 5/16	33 mm	ARB 4, 5, 6	
	H0138	1 3/8	35 mm	ARB 4, 5, 6	
	H0176	1 7/16	37 mm	ARB 4, 5, 6	
	H0112	1 1/2	38 mm	ARB 4, 5, 6	
	H0196	1 9/16	40 mm	ARB 4, 5, 6	
	H0158	1 5/8	41 mm	ARB 4, 5, 6	
	H1116	1 11/16	43 mm	ARB 4, 5, 6	
	H0134	1 3/4	44 mm	ARB 4, 5, 6	
	H1136	1 13/16	46 mm	ARB 4, 5, 6	
	H0178	1 7/8	48 mm	ARB 4, 5, 6	
	H0200	2	51 mm	ARB 4, 5, 6	
	H0216	2 1/16	52 mm	ARB 4, 5, 6	
	H0218	2 1/8	54 mm	ARB 4, 5, 6	
	H0214	2 1/4	57 mm	ARB 4, 5, 6	
	H0256	2 5/16	59 mm	ARB 4, 5, 6	
	H0238	2 3/8	60 mm	ARB 4, 5, 6	
	H0212	2 1/2	64 mm	ARB 4, 5, 6	
	H0296	2 9/16	65 mm	ARB 4, 5, 6	
	H0258	2 5/8	67 mm	ARB 4, 5, 6	
	H0234	2 3/4	70 mm	ARB 4, 5, 6	
	H0278	2 7/8	73 mm	ARB 4, 5, 6	
	H0300	3	76 mm	ARB 4, 5, 6	
	H0318	3 1/8	79 mm	ARB 4, 5, 6	
	H0314	3 1/4	83 mm	ARB 4, 5, 6	
	H0338	3 3/8	86 mm	ARB 4, 5, 6	
	H0312	3 1/2	89 mm	ARB 4, 5, 6	
	H0358	3 5/8	92 mm	ARB 4, 5, 6	
	H0334	3 3/4	95 mm	ARB 4, 5, 6	
	H0378	3 7/8	98 mm	ARB 4, 5, 6	
	H0400	4	102 mm	ARB 4, 5, 6	
	H0418	4 1/8	105 mm	ARB 4, 5, 6	
	H0414	4 1/4	108 mm	ARB 4, 5, 6	
	H0438	4 3/8	111 mm	ARB 4, 5, 6	
	H0412	4 1/2	114 mm	ARB 4, 5, 6	
	H0434	4 3/4	121 mm	ARB 4, 5, 6	
	H0500	5	127 mm	ARB 4, 5, 6	
	H0512	5 1/2	140 mm	ARB 4, 5, 6	
	H0600	6	152 mm	ARB 4, 5, 6	

Carbide tipped, carbide grit and diamond holesaws are available in certain sizes

Series ARB		Holesaw Arbors				
For use with the holesaws found on page 178. Can also be used with carbide tipped, carbide grit or diamond holesaws as well. ARB 5, 6 and 7 have drive pins to transfer a large cutting force from the holesaw to the power unit.	NAP GLADU Tool Number	Shank Size	Corresponding Chuck Size	Corresponding Holesaws		
	ARB1	—	1/4	H0096-H0136		
	ARB2	1/4 Triangular	5/16	H0096-H0136		
	ARB3	11/32 Hexagonal	3/8	H0096-H0136		
	ARB4	7/16 Hexagonal	1/2	H0096-H0136		
	ARB5	11/32 Hexagonal	3/8	H0114-H0600		
	ARB6	7/16 Hexagonal	1/2	H0114-H0600		
	ARB7	5/8 Hexagonal	3/4	H0114-H0600		

Series DRL		Holesaw Pilot Drills			
High speed steel and carbide tipped pilot drills, used for guiding and keeping the holesaw in the correct position during sawing operations.	NAP GLADU Tool Number	Drill Description			
	DRL1	High Speed Steel 1/4" Drill Bit for all arbors except ARB4			
	DRL2	High Speed Steel 1/4" Drill Bit for ARB4			
	DRLCT	Carbide Tipped 1/4" Drill Bit for all arbors			

Series ACC		Holesaw Accessories				
A wide variety of accessories to make holesawing easier: arbor extensions for reach in difficult to cut situations; arbor adaptors to adapt smaller arbor threads to larger holesaw threads; ejector springs to facilitate core removal; drive plates designed to take cutting pressure off drive pinholes during heavy operations in stationary and portable machines.	1/2" Shank	NAP GLADU Tool Number	Accessory Description	Corresponding Arbor	Corresponding Holesaw	
		EXT1	12" x 7/16" Extension	ARB 3, 5	—	
		EXT2	12" x 7/16" Extension	ARB 4, 7	—	
		ARA	Arbor Adaptor	ARB 2, 3, 4	H0114-H0600	
		EIE	Ejector Spring	ARB 1-7	—	
		DRP1	Drive Plate	—	H0300-H0418	
		DRP2	Drive Plate	—	H0414-H0600	

Twist Drills



pg 182-185



pg 185



pg 186



pg 186



pg 187-190



pg 191-192



pg 192



pg 193-195

Centre Drills, Straight Shank, Brad Point	191-192
Centre Drills, Straight Shank, V-Point	192
Dowel Drills, Screw Shank, Brad Point	182-185
Dowel Drills, Screw Shank, V-Point	185
Jobber Drills	193-195
Machine Drills, Brad Point	187-190
Power Ship Auger Bits	186
Vix Bits	185

Twist Drills

Carbon Steel Screw Shank Brad Point Dowel Drills

Series 203

	NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length
	BC62000	Right	3/8	2	3 1/2
	BC62001	Right	7/16	2	3 1/2
	BC62004	Right	1/8	3	4 1/2
	BC62005	Right	3/16	3	4 1/2
	BC62006	Right	7/32	3	4 1/2
	BC62007	Right	1/4	3	4 1/2
	BC62008	Right	9/32	3	4 1/2
	BC62009	Right	5/16	3	4 1/2
	BC62010	Right	11/32	3	4 1/2
	BC62011	Right	3/8	3	4 1/2
	BC62012	Right	25/64	3	4 1/2
	BC62013	Right	13/32	3	4 1/2
	BC62014	Right	7/16	3	4 1/2
	BC62015	Right	29/64	3	4 1/2
	BC62016	Right	1/2	3	4 1/2
	BC62017	Right	9/16	3	4 1/2
	BC62018	Right	5/8	3	4 1/2
	BC62019	Right	3/4	3	4 1/2
	BC62020	Right	7/8	3	4 1/2
	BC62021	Right	1	3	4 1/2
	BC62002	Left	3/8	2	3 1/2
	BC62003	Left	7/16	2	3 1/2
	BC62022	Left	1/8	3	4 1/2
	BC62023	Left	3/16	3	4 1/2
	BC62024	Left	7/32	3	4 1/2
	BC62025	Left	1/4	3	4 1/2
	BC62026	Left	5/16	3	4 1/2
	BC62027	Left	11/32	3	4 1/2
	BC62028	Left	3/8	3	4 1/2
	BC62029	Left	7/16	3	4 1/2
	BC62030	Left	1/2	3	4 1/2

7/16 - 14 Thread

This bit is designed with brad point and outlying spurs for precision dowel hole boring. These drills are made of the finest carbon tool steel, heat treated and precision ground to exacting standards. Overall lengths are held to very close tolerances in both left and right hand tools to ensure uniform drilling in multiple boring operations. A rounded shoulder has a pinhole for easy removal from machines.

Series X203

Designed exactly like the Series 203 drills, except these are made of high speed steel. This steel will maintain maximum production with only minimum sharpening. The threaded shank is relatively soft to ensure against breakage.

7/16 - 14 Thread

High Speed Steel Screw Shank Brad Point Dowel Drills

NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length
BC62031	Right	1/4	2	3 1/2
BC62032	Right	5/16	2	3 1/2
BC62033	Right	3/8	2	3 1/2
BC62034	Right	7/16	2	3 1/2
BC62035	Right	1/2	2	3 1/2
BC62041	Right	3/16	3	4 1/2
BC62042	Right	1/4	3	4 1/2
BC62043	Right	9/32	3	4 1/2
BC62044	Right	5/16	3	4 1/2
BC62045	Right	11/32	3	4 1/2
BC62046	Right	3/8	3	4 1/2
BC62047	Right	25/64	3	4 1/2
BC62048	Right	7/16	3	4 1/2
BC62049	Right	29/64	3	4 1/2
BC62050	Right	1/2	3	4 1/2
BC62051	Right	9/16	3	4 1/2
BC62052	Right	5/8	3	4 1/2
BC62053	Right	3/4	3	4 1/2
BC62054	Right	7/8	3	4 1/2
BC62055	Right	1	3	4 1/2
BC62036	Left	1/4	2	3 1/2
BC62037	Left	5/16	2	3 1/2
BC62038	Left	3/8	2	3 1/2
BC62039	Left	7/16	2	3 1/2
BC62040	Left	1/2	2	3 1/2
BC62056	Left	3/16	3	4 1/2
BC62057	Left	1/4	3	4 1/2
BC62058	Left	9/32	3	4 1/2
BC62059	Left	5/16	3	4 1/2
BC62060	Left	11/32	3	4 1/2
BC62061	Left	3/8	3	4 1/2
BC62062	Left	25/64	3	4 1/2
BC62063	Left	7/16	3	4 1/2
BC62064	Left	29/64	3	4 1/2
BC62065	Left	1/2	3	4 1/2
BC62066	Left	9/16	3	4 1/2
BC62067	Left	5/8	3	4 1/2
BC62068	Left	3/4	3	4 1/2
BC62069	Left	1	3	4 1/2




Twist Drills

High Speed Steel Screw Shank Brad Point Dowel Drills - Long Shank						Series X203B	
	NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length	7/16 -14 Thread	These are designed primarily for the Bell 24 Double End Mitre and Boring Machine. They can also be used on any machine where runout has become a problem. The extended shaft ensures rigidity, especially on small diameter tools. The overall length of these bits match that of Series 203, however it is made of higher grade high speed steel.
	BC62070	Right	3/16	1 3/4	4 1/2		
	BC62071	Right	1/4	1 3/4	4 1/2		
	BC62072	Right	5/16	1 3/4	4 1/2		
	BC62073	Right	3/8	1 3/4	4 1/2		
	BC62074	Right	25/64	1 3/4	4 1/2		
	BC62075	Right	7/16	1 3/4	4 1/2		
	BC62076	Right	1/2	1 3/4	4 1/2		
	BC62077	Left	3/16	1 3/4	4 1/2		
	BC62078	Left	1/4	1 3/4	4 1/2		
	BC62079	Left	5/16	1 3/4	4 1/2		
	BC62080	Left	3/8	1 3/4	4 1/2		
	BC62081	Left	25/64	1 3/4	4 1/2		
	BC62082	Left	7/16	1 3/4	4 1/2		
	BC62083	Left	1/2	1 3/4	4 1/2		

High Speed Steel Screw Shank Brad Point Dowel Drills - Short Shank						Series X203J	
	NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length	7/16 -14 Thread	Designed for use in J.S. Richardson Boring Machines, but can also be used in Root, Bell, Greenlee and other machines using threaded spindles. The short length reduces runout.
	BC62084	Right	1/8	1 1/2	2 3/4		
	BC62085	Right	3/16	1 1/2	2 3/4		
	BC62086	Right	7/32	1 1/2	2 3/4		
	BC62087	Right	1/4	1 1/2	2 3/4		
	BC62088	Right	5/16	1 1/2	2 3/4		
	BC62089	Right	3/8	1 1/2	2 3/4		
	BC62090	Right	7/16	1 1/2	2 3/4		
	BC62091	Right	1/2	1 1/2	2 3/4		
	BC62092	Left	1/4	1 1/2	2 3/4		
	BC62093	Left	3/8	1 1/2	2 3/4		
	BC62094	Left	7/16	1 1/2	2 3/4		

Individual Carbon Steel Brad Point Wood Boring Drills						Series 200A	
	NAP GLADU Tool Number	A Cutting Diameter	B Twist Length	C Shank Length	Overall Length	1/8" Shank 3/16" Shank 1/4" Shank 5/16" Shank 3/8" Shank	These drills are designed to be used in portable electric drills or drill presses with chucks of 3/8" or more.
	BC62547	1/8	1 1/2	1 1/4	2 7/8		
	BC62548	3/16	1 3/4	1 3/4	3 1/2		
	BC62541	1/4	3 1/8	1 1/4	4 3/8		
	BC62542	5/16	3 1/8	1 1/4	4 3/8		
	BC62543	3/8	3 1/8	1 1/4	4 3/8		
	BC62544	7/16	3 1/8	1 1/4	4 3/8		
	BC62545	1/2	3 1/8	1 1/4	4 3/8		

Series 203CT		Carbide Tipped Screw Shank Brad Point Dowel Drills					
These bits are designed especially for drilling in plastics, laminated products, chip cores and fine grained hardwoods such as maple and pecan.		NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length	
	7/16 -14 Thread	BC62103	Right	1/4	3	4 1/2	
		BC62104	Right	5/16	3	4 1/2	
		BC62105	Right	3/8	3	4 1/2	
		BC62106	Right	25/64	3	4 1/2	
		BC62107	Right	7/16	3	4 1/2	
		BC62108	Right	1/2	3	4 1/2	
		BC62109	Left	1/4	3	4 1/2	
		BC62110	Left	5/16	3	4 1/2	
		BC62111	Left	3/8	3	4 1/2	
		BC62112	Left	25/64	3	4 1/2	
		BC62113	Left	7/16	3	4 1/2	
		BC62114	Left	1/2	3	4 1/2	
		BC62528	Right	6 mm	3	4 1/2	
		BC62530	Right	8 mm	3	4 1/2	
		BC62532	Right	10 mm	3	4 1/2	
		BC62529	Left	6 mm	3	4 1/2	
		BC62531	Left	8 mm	3	4 1/2	
		BC62533	Left	10 mm	3	4 1/2	

Series X204		High Speed Steel Screw Shank V-Point Dowel Drills					
The V-Point on these dowel drills has been accurately ground to ensure smooth boring. The shank on this tool is relatively soft to allow for easy removal from the chuck in the event of breakage.		NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length	
	7/16 -14 Thread	BC62095	Right	3/8	3	4 1/2	
		BC62096	Right	7/16	3	4 1/2	
		BC62097	Left	3/8	3	4 1/2	
		BC62098	Left	7/16	3	4 1/2	

Twist Drills

Carbon Steel Power Ship Auger Bits					Series 157	
	NAP GLADU Tool Number	A Cutting Diameter	B Twist Length	Overall Length	Hex Shank	Designed for deep wood boring where small nails or other foreign material could be present. This bit features a hollow centre twist for fast, continuous chip flow.
	BC47017	1/4	12	18		
	BC47018	5/16	12	18		
	BC47019	3/8	12	18		
	BC47020	7/16	12	18		
	BC47021	1/2	12	18		
	BC47022	9/16	12	18		
	BC47023	5/8	12	18		
	BC47024	11/16	12	18		
	BC47025	3/4	12	18		
	BC47026	13/16	12	18		
	BC47027	7/8	12	18		
	BC47028	15/16	12	18		
	BC47029	1	12	18		
	BC47030	1 1/16	12	18		
	BC47031	1 1/8	12	18		
	BC47033	1 1/4	12	18		
	BC47035	1 3/8	12	18		
	BC47036	1 1/2	12	18		

Vix Bits						Series 137	
	NAP GLADU Tool Number	A Hole Diameter	Hole Size	Corresponding Screw Size	Part Description	1/4" Shank	These bits are designed for accuracy while cutting holes for hinges, striker plates, door butts, window pulls and other hardware using screws.
	BC63350	5/64	#3	#3, 4	—		
	BC63359	7/64	#5	#5, 6	—		
	BC63360	9/64	#9	#8, 9, 10	—		
	BC63352	11/64	#12	#12	—		
	BC63354	13/64	#14	#14, 16	—		
	BC63351	5/64	#3	—	Drill-HSS	Replacement Drills	
	BC63361	7/64	#5	—	Drill-HSS		
	BC63362	9/64	#9	—	Drill-HSS		
	BC63353	11/64	#12	—	Drill-HSS		
	BC63355	13/64	#14	—	Drill-HSS		

Series 200

Designed for cross-grain boring and other work requiring smooth and accurate holes. The head, twist and shank are ground for accuracy after hardening while two outlining spurs cut in advance of the chip lifter.


1/2" Shank


Carbon Steel Brad Point Machine Drills

NAP GLADU Tool Number	A Cutting Diameter	B Twist Length	Overall Length
BC62115	1/8	3	5
BC62116	5/32	3	5
BC62117	3/16	3	5
BC62118	7/32	3	5
BC62119	1/4	3	5
BC62120	17/64	3	5
BC62121	9/32	3	5
BC62122	5/16	3	5
BC62123	11/32	3	5
BC62124	3/8	3	5
BC62125	25/64	3	5
BC62126	13/32	3	5
BC62127	7/16	3	5
BC62128	15/32	3	5
BC62129	1/2	3	5
BC62130	5/8	3	5
BC62131	3/4	3	5
BC62132	1/8	4	6
BC62133	5/32	4	6
BC62134	3/16	4	6
BC62135	7/32	4	6
BC62136	1/4	4	6
BC62137	17/64	4	6
BC62138	9/32	4	6
BC62139	19/64	4	6
BC62140	5/16	4	6
BC62141	11/32	4	6
BC62142	3/8	4	6
BC62143	25/64	4	6
BC62144	13/32	4	6
BC62145	7/16	4	6
BC62146	29/64	4	6
BC62147	15/32	4	6
BC62148	1/2	4	6
BC62149	17/32	4	6
BC62150	9/16	4	6
BC62151	19/32	4	6
BC62152	5/8	4	6
BC62153	21/32	4	6
BC62154	11/16	4	6
BC62155	3/4	4	6
BC62156	25/32	4	6
BC62157	13/16	4	6
BC62158	7/8	4	6
BC62159	15/16	4	6
BC62160	1	4	6
BC62161	1 1/16	4	6
BC62162	1 1/8	4	6
BC62163	1 1/4	4	6



Twist Drills

High Speed Steel Brad Point Machine Drills					Series X200	
	NAP GLADU Tool Number	A Cutting Diameter	B Twist Length	Overall Length	1/2" Shank	Identical to Series 200 drills, except these bits are made of high speed steel for added drill life in tough applications. The twist is specially ground to give maximum chip clearance.
	BC62164	3/16	3	5		
	BC62165	1/4	3	5		
	BC62166	9/32	3	5		
	BC62167	5/16	3	5		
	BC62168	11/32	3	5		
	BC62169	3/8	3	5		
	BC62170	7/16	3	5		
	BC62171	1/2	3	5		
	BC62172	1/4	4	6		
	BC62173	9/32	4	6		
	BC62174	5/16	4	6		
	BC62175	11/32	4	6		
	BC62176	3/8	4	6		
	BC62177	13/32	4	6		
	BC62178	7/16	4	6		
	BC62179	1/2	4	6		
	BC62180	17/32	4	6		
	BC62181	9/16	4	6		
	BC62182	5/8	4	6		
	BC62183	11/16	4	6		
	BC62184	3/4	4	6		
	BC62185	13/16	4	6		
	BC62186	7/8	4	6		
	BC62187	15/16	4	6		
	BC62188	1	4	6		

Carbide Tipped Brad Point Machine Drills					Series 200CT	
	NAP GLADU Tool Number	A Cutting Diameter	B Twist Length	Overall Length	1/2" Shank	Identical to Series 200 drills, except these are carbide tipped for drilling plastics, laminates, chip core and tough to drill materials.
	BC62189	1/4	3	5		
	BC62190	5/16	3	5		
	BC62191	3/8	3	5		
	BC62192	7/16	3	5		
	BC62193	1/2	3	5		
	BC62194	5/8	3	5		
	BC62195	3/4	3	5		
	BC62196	1/4	4	6		
	BC62197	5/16	4	6		
	BC62198	3/8	4	6		
	BC62199	7/16	4	6		
	BC62200	1/2	4	6		
	BC62201	5/8	4	6		
	BC62202	3/4	4	6		

Series 205B		Imperial Carbon Steel Brad Point Machine Wood Drills			
Carbon steel drills with a brad point tip are for drilling clean, accurate holes. Sizes up to 5/16" have a straight shank, where sizes 11/32" to 1" have 5/16" to 1/2" shanks.		NAP GLADU Tool Number	A Cutting Diameter	Overall Length	
	1/8" Shank	BC20503	1/8	2 5/8	
	5/32" Shank	BC20504	5/32	2 5/8	
	3/16" Shank	BC20505	3/16	3 3/8	
	7/32" Shank	BC20555	7/32	3 3/8	
	1/4" Shank	BC20506	1/4	4	
	9/32" Shank	BC20507	9/32	4	
	5/16" Shank	BC20508	5/16	4 1/2	
		BC20509	11/32	4 1/2	
		BC20510	3/8	5 1/4	
		BC20511	7/16	5 5/8	
		BC20512	1/2	6 1/8	
	3/8" Shank	BC20514	9/16	6 5/8	
		BC20516	5/8	7 1/8	
		BC20519	3/4	7 3/4	
	1/2" Shank	BC20522	7/8	8 1/4	
		BC20525	1	8 5/8	


Series 205BM		Metric Carbon Steel Brad Point Machine Wood Drills			
These carbon steel brad point drills are identical to Series 205B drills, except they are available in metric sizes.		NAP GLADU Tool Number	A Cutting Diameter	Overall Length	
	3 mm Shank	BC20503M	3 mm	60 mm	
	4 mm Shank	BC20504M	4 mm	75 mm	
	5 mm Shank	BC20505M	5 mm	85 mm	
	6 mm Shank	BC20506M	6 mm	95 mm	
	7 mm Shank	BC20507M	7 mm	105 mm	
	8 mm Shank	BC20508M	8 mm	115 mm	
		BC20509M	9 mm	120 mm	
		BC20510M	10 mm	130 mm	
		BC20511M	11 mm	140 mm	
		BC20512M	12 mm	150 mm	
	10 mm Shank	BC20513M	13 mm	150 mm	
		BC20514M	14 mm	160 mm	
		BC20515M	15 mm	170 mm	
		BC20516M	16 mm	180 mm	
		BC20518M	18 mm	190 mm	
		BC20520M	20 mm	205 mm	
	13 mm Shank	BC20522M	22 mm	210 mm	
		BC20524M	24 mm	210 mm	
		BC20525M	25 mm	200 mm	
		BC20526M	26 mm	220 mm	
		BC20528M	28 mm	220 mm	
		BC20530M	30 mm	220 mm	

Twist Drills

High Speed Steel Brad Point Machine Wood Drills					Series X205BM
	NAP GLADU Tool Number	A	Cutting Diameter	Overall Length	
	BC20535M		3.5 mm	70 mm	3.5 mm Shank
	BC20545M		4.5 mm	80 mm	4.5 mm Shank
	BC20555M		5.5 mm	90 mm	5.5 mm Shank
	BC20565M		6.5 mm	100 mm	6.5 mm Shank
	BC20575M		7.5 mm	110 mm	7.5 mm Shank
	BC20585M		8.5 mm	120 mm	8 mm Shank
	BC20595M		9.5 mm	125 mm	
	BC20515M		10.5 mm	135 mm	
					These bits are identical to Series 205BM drills, except they are made from higher quality, high speed steel for more difficult boring applications.
Imperial Carbide Tipped Brad Point Machine Wood Drills					Series 340BCT
	NAP GLADU Tool Number	A	Cutting Diameter	Overall Length	
	BC34212		3/16	80 mm	4.5 mm Shank
	BC34213		1/4	95 mm	6 mm Shank
	BC34214		5/16	115 mm	7.5 mm Shank
	BC34215		3/8	125 mm	9 mm Shank
	BC34217		1/2	150 mm	10 mm Shank
					These are quality tipped brad point drills for boring into plastics, laminates, chip core and other tough to drill materials.
Metric Carbide Tipped Brad Point Machine Wood Drills					Series 340BMCT
	NAP GLADU Tool Number	A	Cutting Diameter	Overall Length	
	BC34005		5 mm	85 mm	5 mm Shank
	BC34006		6 mm	90 mm	6 mm Shank
	BC34008		8 mm	115 mm	8 mm Shank
	BC34010		10 mm	130 mm	10 mm Shank
	BC34012		12 mm	150 mm	
					These are quality tipped brad point drills for boring into plastics, laminates, chip core and other tough to drill materials.

Series X122B	High Speed Steel Straight Shank Brad Point Centre Drills - 6" Length					
These are for use with all types of adjustable counterbores and countersinks, or for straight boring jobs. Made from high speed steel for longer life in difficult to drill material.	NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length	
	BC62385	Right	1/8	2 1/4	6	
	BC62386	Right	5/32	2 1/4	6	
	BC62387	Right	3/16	2 1/4	6	
	BC62388	Right	7/32	2 1/4	6	
	BC62389	Right	1/4	2 1/4	6	
	BC62390	Right	9/32	2 1/4	6	
	BC62391	Right	19/64	2 1/4	6	
	BC62392	Right	5/16	2 1/4	6	
	BC62393	Right	3/8	2 1/4	6	
	BC62394	Left	3/16	2 1/4	6	
	BC62395	Left	7/32	2 1/4	6	
	BC62396	Left	1/4	2 1/4	6	


Series X122BED	High Speed Steel Straight Shank Brad Point Centre Drill - 6" Length					
These bits are designed for use with all types of adjustable counterbores and countersinks, or for straight boring jobs. These are close to Series X122B, the difference being a longer twist length (3 1/2") for deeper drilling.	NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length	
	BC62381	Right	19/64	3 1/2	6	

Series X122B8	High Speed Steel Straight Shank Brad Point Centre Drills - 8" Length					
These are designed for use with counterbores when a deep pilot hole is required.	NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length	
	BC62382	Right	3/16	3 1/2	8	
	BC62383	Right	7/32	3 1/2	8	
	BC62384	Right	1/4	3 1/2	8	

Twist Drills

High Speed Steel Straight Shank Brad Point Centre Drills - 4.5" Length						Series X124B
	NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length	For use with counterbores and countersinks, as well as for straight boring. Two outlining spurs and a brad point create clean, accurate holes. These bits are made from tough, long lasting, high speed steel.
	BC62402	Right	1/8	2 1/4	4 1/2	
	BC62403	Right	5/32	2 1/4	4 1/2	
	BC62404	Right	3/16	2 1/4	4 1/2	
	BC62405	Right	7/32	2 1/4	4 1/2	
	BC62406	Right	1/4	2 1/4	4 1/2	
	BC70522	Left	3/16	2 1/4	4 1/2	
	BC70523	Left	7/32	2 1/4	4 1/2	
	BC70524	Left	1/4	2 1/4	4 1/2	

High Speed Steel Straight Shank V-Point Centre Drills - 6" Length						Series X122D
	NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length	These straight shank drills are designed for use in counterbores and countersinks; made from high speed steel for a longer tool life.
	BC62426	Right	3/32	2 1/4	6	
	BC62427	Right	1/8	2 1/4	6	
	BC62428	Right	5/32	2 1/4	6	
	BC62429	Right	11/16	2 1/4	6	
	BC62430	Right	3/64	2 1/4	6	
	BC62431	Right	7/32	2 1/4	6	
	BC62432	Right	1/4	2 1/4	6	
	BC62433	Right	9/32	2 1/4	6	
	BC62434	Right	5/16	2 1/4	6	
	BC62435	Right	3/8	2 1/4	6	

High Speed Steel Straight Shank V-Point Centre Drills - 4.5" Length						Series X124D
	NAP GLADU Tool Number	Rotation Direction	A Cutting Diameter	B Twist Length	Overall Length	These straight shank drills are designed for use in counterbores and countersinks; made from high speed steel for a longer tool life.
	BC62450	Right	3/32	2 1/4	4 1/2	
	BC62451	Right	1/8	2 1/4	4 1/2	
	BC62452	Right	9/64	2 1/4	4 1/2	
	BC62453	Right	5/32	2 1/4	4 1/2	
	BC62454	Right	11/16	2 1/4	4 1/2	
	BC62455	Right	3/16	2 1/4	4 1/2	
	BC62456	Right	7/32	2 1/4	4 1/2	
	BC62457	Right	1/4	2 1/4	4 1/2	
	BC62458	Right	9/32	2 1/4	4 1/2	
	BC62459	Right	5/16	2 1/4	4 1/2	
	BC62460	Right	3/8	2 1/4	4 1/2	

Series X10

These bits are designed for heavy-duty applications in wood, steel and plastic. The high temperance, black oxide finish and 118° point provide optimum cutting efficiency.

Imperial High Speed Steel Jobber Drills

NAP GLADU Tool Number	A Cutting Diameter	Decimal Equivalent	B Twist Length	Overall Length
BC02001	1/64	.0156	3/16	13/16
BC02002	1/32	.0312	13/32	1 3/16
BC02003	3/64	.0469	5/8	1 1/2
BC02004	1/16	.0625	25/32	1 11/16
BC02005	5/64	.0781	15/16	1 15/16
BC02006	3/32	.0938	1 3/16	2 1/4
BC02007	7/64	.1094	1 5/16	2 13/32
BC02008	1/8	.1250	1 7/16	2 9/16
BC02009	9/64	.1406	1 17/32	2 3/4
BC02010	5/32	.1562	1 11/16	2 15/16
BC02011	11/64	.1719	1 27/32	3 5/32
BC02012	3/16	.1875	2 1/16	3 3/8
BC02013	13/64	.2031	2 1/16	3 3/8
BC02014	7/32	.2188	2 1/4	3 21/32
BC02015	15/64	.2344	2 1/4	3 21/32
BC02016	1/4	.2500	2 1/2	3 31/32
BC02017	17/64	.2656	2 23/32	4 9/32
BC02018	9/32	.2812	2 23/32	4 9/32
BC02019	19/64	.2969	2 15/16	4 19/32
BC02020	5/16	.3125	2 15/16	4 19/32
BC02021	21/64	.3281	2 15/16	4 19/32
BC02022	11/32	.3438	3 3/16	4 29/32
BC02023	23/64	.3594	3 3/16	4 29/32
BC02024	3/8	.3750	3 7/16	5 1/4
BC02025	25/64	.3906	3 7/16	5 1/4
BC02026	13/32	.4062	3 7/16	5 1/4
BC02027	27/64	.4219	3 11/16	5 9/32
BC02028	7/16	.4375	3 11/16	5 9/32
BC02029	29/64	.4531	3 11/16	5 9/32
BC02030	15/32	.4688	3 31/32	5 15/16
BC02031	31/64	.4844	3 31/32	5 15/16
BC02032	1/2	.5000	3 31/32	5 15/16
BC02033	33/64	.5156	4 13/16	6 5/8
BC02034	17/32	.5313	4 13/16	6 5/8
BC02035	35/64	.5469	4 13/16	6 5/8
BC02036	9/16	.5625	4 13/16	6 5/8
BC02037	37/64	.5781	4 13/16	6 5/8
BC02038	19/32	.5938	5 3/16	7 1/8
BC02039	39/64	.6094	5 3/16	7 1/8
BC02040	5/8	.6250	5 3/16	7 1/8
BC02041	41/64	.6406	5 3/16	7 1/8
BC02042	21/32	.6563	5 3/16	7 1/8
BC02043	43/64	.6719	5 5/8	7 5/8
BC02044	11/16	.6875	5 5/8	7 5/8
BC02045	3/4	.7500	5 1/2	8 1/16



Larger sized diameters are available upon request in prentice style drill with 1/2" shank

Twist Drills

Imperial High Speed Steel Jobber Drills - Left Hand Rotation

Series X10L



NAP GLADU Tool Number	A Cutting Diameter	Decimal Equivalent	B Twist Length	Overall Length
BC03002	1/32	.0312	13/32	1 3/16
BC03003	3/64	.0469	5/8	1 1/2
BC03004	1/16	.0625	25/32	1 11/16
BC03005	5/64	.0781	15/16	1 15/16
BC03006	3/32	.0938	1 3/16	2 1/4
BC03007	7/64	.1094	1 5/16	2 13/32
BC03008	1/8	.1250	1 7/16	2 9/16
BC03009	9/64	.1406	1 17/32	2 3/4
BC03010	5/32	.1562	1 11/16	2 15/16
BC03011	11/64	.1719	1 27/32	3 5/32
BC03012	3/16	.1875	2 1/16	3 3/8
BC03013	13/64	.2031	2 1/16	3 3/8
BC03014	7/32	.2188	2 1/4	3 21/32
BC03015	15/64	.2344	2 1/4	3 21/32
BC03016	1/4	.2500	2 1/2	3 31/32
BC03017	17/64	.2656	2 23/32	4 9/32
BC03018	9/32	.2812	2 23/32	4 9/32
BC03019	19/64	.2969	2 15/16	4 19/32
BC03020	5/16	.3125	2 15/16	4 19/32
BC03021	21/64	.3281	2 15/16	4 19/32
BC03022	11/32	.3438	3 3/16	4 29/32
BC03023	23/64	.3594	3 3/16	4 29/32
BC03024	3/8	.3750	3 7/16	5 1/4
BC03025	25/64	.3906	3 7/16	5 1/4
BC03026	13/32	.4062	3 7/16	5 1/4
BC03027	27/64	.4219	3 11/16	5 9/32
BC03028	7/16	.4375	3 11/16	5 9/32
BC03029	29/64	.4531	3 11/16	5 9/32
BC03030	15/32	.4688	3 31/32	5 15/16
BC03031	31/64	.4844	3 31/32	5 15/16
BC03032	1/2	.5000	3 31/32	5 15/16

Designed for heavy-duty applications in wood, steel and plastic. The high temperance, black oxide finish and 118° point allows for optimum cutting efficiency.

Series X10M

Designed for heavy-duty applications in wood, steel and plastic. The high temperance, black oxide finish and 118° point allows for optimum cutting efficiency.

Metric High Speed Steel Jobber Drills

NAP GLADU Tool Number	A Cutting Diameter	Decimal Equivalent	B Twist Length	Overall Length
BC04100	1 mm	.0394	12 mm	34 mm
BC04200	2 mm	.0787	24 mm	49 mm
BC04300	3 mm	.1181	33 mm	61 mm
BC04400	4 mm	.1575	43 mm	75 mm
BC04500	5 mm	.1969	52 mm	86 mm
BC04600	6 mm	.2362	57 mm	93 mm
BC04700	7 mm	.2756	69 mm	109 mm
BC04800	8 mm	.3150	75 mm	117 mm
BC04900	9 mm	.3543	81 mm	125 mm
BC05000	10 mm	.3937	87 mm	133 mm
BC05100	11 mm	.4331	94 mm	142 mm
BC05120	12 mm	.4724	101 mm	151 mm
BC05130	13 mm	.5118	101 mm	151 mm
BC05140	14 mm	.5512	108 mm	160 mm
BC05150	15 mm	.5906	114 mm	169 mm
BC05160	16 mm	.6299	120 mm	178 mm
BC05170	17 mm	.6693	125 mm	184 mm
BC05180	18 mm	.7087	130 mm	191 mm
BC05190	19 mm	.7480	135 mm	198 mm
BC05200	20 mm	.7874	140 mm	205 mm



Counterbores and
Countersinks



pg 198



pg 198-199



pg 199-200



pg 201, 203




pg 200-202

Counterbores Countersinks, Screw Shank	.198
Counterbores, Straight Shank	.201, 203
Counterbores, Various	.200-202
Countersinks, Straight Shank	.198-199
Countersinks, Various	.199-200

Series 122VCT

Designed for seating flat head screws which require a tapered countersunk hole. The double flute twist with wide channels allows for easy chip clearance. Carbide tipped for longer life in particle boards, fiber boards and plastics. A drill can be held by a split and set screw on the shank. For use with drills listed on pages 191-192.

Centre drills not included with countersinks



Series 125CT

Designed with two cutting edges beveled at 82° to match the taper of flat head screws. Carbide tipped for longer life in particle boards, fiber boards and plastics. The drill is held to the countersink by a socket set screw. For use with drills listed on pages 191-192.

Centre drills not included with countersinks



Series 202CT

These countersinks are designed with two cutting edges beveled at 82° to match the taper of flat head screws. They are carbide tipped for longer life in particle boards, fiber boards and plastics. The drill is held to the countersink by a socket set screw. For use with drills listed on pages 191-192.

*Designed to be used with Diplug
Centre drills not included with countersinks



Carbide Tipped Adjustable Countersink						Series 202CTA
	NAP GLADU Tool Number	A1 Countersink Diameter	A2 Drill Diameter	B Cutting Depth	Overall Length	These are designed to fit drill diameters from 1/8" to 9/32" and produce countersunk holes from 13/32" to 37/64" in diameter. They are carbide tipped for clean cuts and longer tool life. A system of screws allows for gripping of the adjustable countersink over drills found on pages 191-192. Each adjustable countersink is supplied with its own key and plastic pouch.
	55900	13/32	1/8	12 mm	32 mm	
		27/64	9/64			
		29/64	5/32			
		15/32	3/16			
		1/2	13/64			
		33/64	7/32			
		17/32	15/64			
		9/16	1/4			
		37/64	9/32			
Centre drills not included with countersinks						

Machine Countersinks



A


NAP GLADU Tool Number	A Countersink Diameter	Overall Length
55530	1/2	2
55532	5/8	2
55534	3/4	2

Centre drills not included with countersinks

Series 202C

5/16" Shank

Designed with five precision cutting edges for chatter free 90° countersinking.

Carbon Steel Multi-Spur Counterbores				Series 120	
	NAP GLADU Tool Number	A1 Counterbore Diameter	A2 Drill or Shank Diameter	An aggressive counterbore cutter designed to fit any drill 1/2" diameter or larger with a 1/2" shank. Designed to be used with drills on pages 187-192.	
	BC62345	1 1/8	1/2		
	BC62346	1 1/4	1/2		
	BC62347	1 3/8	1/2		
	BC62348	1 1/2	1/2		
	BC62349	1 5/8	1/2		
	BC62350	1 3/4	1/2		
	BC62351	1 7/8	1/2		
	BC62352	2	1/2		
	BC62353	2 1/8	1/2		
	BC62354	2 1/4	1/2		
	BC62355	2 1/2	1/2		

Series 122CT

Designed to bore smooth, flat-bottomed holes. The double fluted twist with wide channels makes for easy chip clearance. Carbide tipped for longer life in particle boards, fiber boards and plastics. The centre drill is held in place by a split shank and set screw. These can be used with the drills featured on pages 189-192.

Carbide Tipped Counterbores

NAP GLADU Tool Number	A1 Counterbore Diameter	A2 Drill Diameter	B Twist Length	Overall Length
BC62292	3/8	3/16	2 1/2	4 1/2
BC62293	1/2	3/16	2 1/2	4 1/2
BC62294	1/2	7/32	2 1/2	4 1/2
BC62295	1/2	1/4	2 1/2	4 1/2

Centre drills not included with counterbores



Series 250CTS

These bits are designed to bore smooth, flat-bottomed holes. Carbide tipped for longer life in particle boards, fiber boards and plastics. Counterbore is held to the drill by a set screw. For use with drills on pages 189-192.

Carbide Tipped Counterbores with Shank

	NAP GLADU Tool Number	A1 Counterbore Diameter	A2 Drill Diameter	Overall Length
5/16" Shank	55540	3/8	1/8	1 7/8
	55542	25/64	5/32	1 7/8
	55544	25/64	11/64	1 7/8
3/8" Shank	55320	1/2	3/16	1 7/8
	55322	1/2	7/32	1 7/8
	55324	1/2	15/64	1 7/8
	55326	1/2	1/4	1 7/8

Centre drills not included with counterbores



Counterbores and Countersinks

Carbide Tipped Counterbores without Shank

Series 250CT

	NAP GLADU Tool Number	A1 Counterbore Diameter	A2 Drill Diameter	Overall Length
	55910	5/8	1/4	1 1/2
	55912	5/8	9/32	1 1/2
	55914	5/8	5/16	1 1/2
	55916	3/4	5/16	1 1/2
	55918	3/4	3/8	1 1/2

Centre drills not included with counterbores

— | A2 | — A1

These are designed to bore smooth, flat-bottomed holes. They are carbide tipped for a longer tool life, for use in particle boards, fiber boards and plastics. Counterbore is held to the drill by a set screw. For use with drills on pages 191-192.

Carbon Steel Counterbores

Series 123

Style One  — A2 — A1	NAP GLADU Tool Number	A1 Counterbore Diameter	A2 Drill Diameter	Bore Style	Overall Length
	BC62301	3/8	3/16	1	1 1/2
Style Two  — A2 — A1	BC62302	1/2	3/16	1	1 1/2
	BC62303	1/2	7/32	1	1 1/2
	BC62304	1/2	1/4	1	1 1/2
	BC62305	5/8	1/4	2	2
	BC62306	5/8	5/16	2	2
	BC62307	3/4	1/4	2	2
	BC62308	3/4	5/16	2	2
	BC62309	7/8	5/16	2	2
	BC62310	7/8	3/8	2	2
	BC62311	7/8	7/16	2	2
	BC62312	1	5/16	2	2
	BC62313	1	3/8	2	2
	BC62314	1	1/2	2	2
	BC62315	1 1/8	1/2	2	2
	BC62316	1 1/4	1/2	2	2
	BC62317	1 3/8	1/2	2	2
	BC62318	1 1/2	1/2	2	2

Centre drills not included with counterbores

These counterbores are designed with extension-lip head to bore smooth, flat-bottomed holes. A set screw holds the counterbore in place on the drill. For use with drills on pages 187-192.

Series 122

Designed to bore smooth, flat-bottomed holes, a double fluted twist with wide channels makes for easy chip clearance. A centre drill can be held in place by a split shank and set screw. These counterbores can be used with the drills featured on pages 191-192.

Carbon Steel Counterbores

NAP GLADU Tool Number	A1 Counterbore Diameter	A2 Drill Diameter	B Twist Length	Overall Length
BC62261	3/8	1/8	2 1/2	4 1/2
BC62262	3/8	5/32	2 1/2	4 1/2
BC62263	3/8	3/16	2 1/2	4 1/2
BC62264	7/16	3/16	2 1/2	4 1/2
BC62265	7/16	7/32	2 1/2	4 1/2
BC62266	1/2	1/8	2 1/2	4 1/2
BC62267	1/2	5/32	2 1/2	4 1/2
BC62268	1/2	3/16	2 1/2	4 1/2
BC62269	1/2	7/32	2 1/2	4 1/2
BC62270	1/2	1/4	2 1/2	4 1/2
BC62271	9/16	3/16	2 1/2	4 1/2
BC62272	9/16	1/4	2 1/2	4 1/2
BC62273	5/8	3/16	2 1/2	4 1/2
BC62274	5/8	1/4	2 1/2	4 1/2
BC62275	5/8	9/32	2 1/2	4 1/2
BC62276	5/8	5/16	2 1/2	4 1/2
BC62277	3/4	3/16	2 1/2	4 1/2
BC62278	3/4	1/4	2 1/2	4 1/2
BC62279	3/4	9/32	2 1/2	4 1/2
BC62280	3/4	5/16	2 1/2	4 1/2
BC62281	3/4	3/8	2 1/2	4 1/2



Centre drills not included with counterbores




Conversions, Troubleshooting and Indexes

Troubleshooting Guide


Common Cutting Problems	Common Causes
• tool breakage • excessive tool wear • burning in cut • rough cutting • glazed cutting	• Using dull or improperly sharpened tools. • The feed rate is too slow. • The feed rate is too fast. • The router is under-powered. No more than 20% of the available RPM should be lost under load. • The collet is loose or glazed. • The RPM is too fast or slow for the style of router bit being used. • The tool could be made of the wrong material for the job. For example, the router bit could be made of solid carbide rather than high speed steel. • There is not enough tool clearance on the cutting edge.

Router Bit Terminology




Straight Flute Bit



Spiral Bit



Helix Angles



Helpful Hints for Quality Routing

Proper tool selection and use will greatly increase the quality of the cut and extend the life of the tool.

- Cutting length should never be longer than necessary. Increased or extra cutting length causes vibration, deflection, and a lower quality finish cut. The cutting length should also never exceed four times the shank diameter. Router bits exceeding this limit are increasingly susceptible to breakage.
- Always use the largest shank diameter possible. Larger diameters increase tool strength and reduce the possibility of breakage. A 3/8" diameter shank is 50% stronger than a 1/4" shank. Similarly, the strength of a 1/2" shank diameter is 50% stronger than a 3/8" shank.
- Worn or glazed router collets account for 80% of router bit breakage problems. Increased breakage and dark markings on the shank of the tool indicate collet problems. Regular inspection of collet integrity is critical to ensure maximum productivity.
- Machine integrity should be inspected on a regular basis. Over time, collet or spindle run-out may increase through wear and tear. Run-out, unless otherwise stated in the machine manual, should not exceed 0.004 inches. You can check the run-out by placing a dowel pin into the collet and a dial indicator against this pin while manually rotating the collet. If the run-out is larger than the suggested maximums, replacement of the collet and/or spindle may be necessary.
- Overfeeding or forcing the material into a cut can cause chip compression, resulting in bending and/or breakage. The tool should be allowed to "bite" its way through the material. The operator should feel a constant, even pressure throughout the length of the cut.
- Underfeeding of material into the cut will cause heat build-up and subsequent excessive friction. This results in reduced tool life and/or breakage.
- Remember to use lubricant. By using lubricant whenever possible you can reduce heat build-up and increase the life of the tool.
- Always have materials clamped securely on the machine table. Doing so will help to avoid bouncing or vibrating and ensure a smooth cut.
- Router bits should be inserted a minimum of 5/8" into the router collet to ensure maximum safety.
- Adjust router speed to match the diameter of the bit and the material being cut. Spindle speeds range from 8000 to 50,000 RPM, by assuring the correct speed for the bit in use, the life of the tool will not be compromised. A NAP GLADU Representative will be glad to help you determine your application's ideal speed.
- Dust collection is important for clean cuts and long tool life. The more chips and dust in the cut, particularly when routing through the board, the more work the tool is subjected to.
- Excessive RPM loss results in poor cuts, shorter tool life and extreme machine wear. If when cutting or routing, your machine bogs down or loses more than 20% of its no-load RPM, either the machine is underpowered, the feed rate is too high for the machine, or the bit is too dull.

For other helpful hints please see the "High Speed Steel and Solid Carbide Router Selection Guide" (Page 100), the "CNC Router Feed Chart" (Pages 210-211) and the "Boring Chart for Wood Screws" (Page 208).

Conversions, Troubleshooting and Indexes


Boring Chart for Wood Screws

How To Use This Guide

This table simplifies the selection of the tool size best suited to the selected wood screw. The tool size for the shank hole (the non-threaded portion of the screw) is listed in the nearest fractional equivalent column, next to the shank diameter; the tool size for the pilot hole (the threaded portion of the screw) is listed in the nearest fractional equivalent column, next to the root diameter. The fractional equivalents and undersize/oversize decimals indicate how close a bit of given fractional size will bore to the actual screw dimension and whether the fit will be snug or loose. In selecting a tool size for the pilot hole, note that root diameters are average dimensions measured at the middle of the threaded portion. On

some screws, the root diameter tapers slightly from the end of the screw, increasing toward the head. It is usually good practice to bore the pilot hole the same size as the root diameter in hardwoods, such as oak, and about 15% smaller for softwoods, such as pine and Douglas fir. In some cases, allowances can be made to compensate for moisture content and other varying factors. The same rule can be used for shank holes. The *shank diameters* shown below are standard specifications subject to tolerances of +0.004 and -0.007. *Maximum head diameters* are also standard specifications which apply to flat and oval head screws. Head sizes run from 5% to 10% smaller for round head screws.

Screw Number	A Maximum Head Diameter	Threads per Inch	B Shank Diameter (Inches in Decimals)	Nearest Fractional Equivalent			C Root Diameter (Inches in Decimals)	Nearest Fractional Equivalent		
0	.119	32	.060	1/16	.002	Oversized	.040	3/64	.007	Oversized
1	.146	28	.073	5/64	.005	Oversized	.046	3/64		Basic Size
2	.172	26	.086	3/32	.007	Oversized	.054	1/16	.008	Oversized
3	.199	24	.099	7/64	.010	Oversized	.065	1/16	.002	Undersized
4	.225	22	.112	7/64	.003	Undersized	.075	5/64	.003	Oversized
5	.252	20	.125	1/8		Basic Size	.085	5/64	.007	Undersized
6	.279	18	.138	9/64	.002	Oversized	.094	3/32		Basic Size
7	.305	16	.151	5/32	.005	Oversized	.102	7/64	.007	Oversized
8	.332	15	.164	5/32	.007	Undersized	.112	7/64	.003	Undersized
9	.358	14	.177	11/64	.005	Undersized	.122	1/8	.003	Oversized
10	.385	13	.190	3/16	.002	Undersized	.130	1/8	.005	Undersized
11	.411	12	.203	13/64		Basic Size	.139	9/64	.001	Oversized
12	.438	11	.216	7/32	.003	Oversized	.148	9/64	.007	Undersized
14	.491	10	.242	1/4	.008	Oversized	.165	5/32	.009	Undersized
16	.544	9	.268	17/64	.002	Undersized	.184	3/16	.003	Oversized
18	.597	8	.294	19/64	.003	Oversized	.204	13/64	.001	Undersized
20	.650	8	.320	5/16	.007	Undersized	.223	7/32	.004	Undersized
24	.756	7	.372	3/8	.003	Oversized	.260	1/4	.010	Undersized



Decimal and Metric Equivalents											
Fraction	Decimal	mm	Fraction	Decimal	mm	Fraction	Decimal	mm	Fraction	Decimal	mm
1/64	.015625	.40	17/64	.265625	6.8	33/64	.515625	13.1	49/64	.765625	19.5
1/32	.03125	.80	9/32	.28125	7.2	17/32	.53125	13.5	25/32	.78125	19.9
3/64	.46875	1.2	19/64	.296875	7.6	35/64	.546875	13.9	51/64	.796875	20.2
1/16	.0625	1.6	5/16	.3125	8.0	9/16	.5625	14.3	13/16	.8125	20.6
5/64	.078125	2.0	21/64	.328125	8.4	37/64	.578125	14.7	53/64	.828125	21.0
3/32	.09375	2.4	11/32	.34375	8.8	19/32	.59375	15.1	27/32	.84375	21.4
7/64	.109375	2.8	23/64	.359375	9.2	39/64	.609375	15.5	55/64	.859375	21.8
1/8	.125	3.2	3/8	.375	9.6	5/8	.625	15.9	7/8	.875	22.2
9/64	.140625	3.6	25/64	.390625	10.0	41/64	.640625	16.3	57/64	.890625	22.6
5/32	.15625	4.0	13/32	.40625	10.4	21/32	.65625	16.7	29/32	.90625	23.0
11/64	.171875	4.4	27/64	.421875	10.8	43/64	.671875	17.1	59/64	.921875	23.4
3/16	.1875	4.8	7/16	.4375	11.2	11/16	.6875	17.5	15/16	.9375	23.8
13/64	.203125	5.2	39/64	.453125	11.6	54/64	.703125	17.9	61/64	.953125	24.2
7/32	.21875	5.6	15/32	.46875	12.0	23/32	.71875	18.3	31/32	.96875	24.6
15/64	.234375	6.0	31/64	.484375	12.4	47/64	.734375	18.7	63/64	.984375	25.0
1/4	.25	6.4	1/2	.5	12.8	3/4	.75	19.1	1	1.0	25.4

Standard Gauges - Birmingham or Stubbs											
Gauge	Inches	mm	Gauge	Inches	mm	Gauge	Inches	mm	Gauge	Inches	mm
0000	.454	11.532	7	.180	4.572	17	.058	1.473	27	.016	.406
000	.425	10.795	8	.165	4.190	18	.049	1.244	28	.014	.356
00	.380	9.652	9	.148	3.759	19	.042	1.066	29	.013	.330
0	.340	8.636	10	.134	3.403	20	.035	.889	30	.012	.305
1	.300	7.620	11	.120	3.048	21	.032	.812	31	.010	.254
2	.284	7.213	12	.109	2.768	22	.028	.711	32	.009	.229
3	.259	6.578	13	.095	2.413	23	.025	.635	33	.008	.203
4	.238	6.045	14	.083	2.108	24	.022	.559	34	.007	.178
5	.220	5.588	15	.072	1.828	25	.020	.508	35	.005	.127
6	.203	5.156	16	.065	1.651	26	.018	.457	36	.004	.102

Conversion Chart	
1 Inch	= 25.4 Millimeters
.001 Inch	= .0254 Millimeters
1 Millimeter	= .03937 Inches
.1 Millimeter	= .00394 Inches
.01 Millimeter	= .00039 Inches
1 Pound	= .4536 Kilograms
1 Ounce	= 28.3495 Grams
1 Kilogram	= 2.2046 Pounds
1 Gallon	= 3.7853 Litres
1 Litre	= .2642 Gallons
1 Bar	= 14.5 PSI
1 PSI	= .069 Bars
1 Kilowatt	= 1.33 Horsepower
1 Horsepower	= .750 Kilowatts

Conversions, Troubleshooting and Indexes

CNC Router Feed Chart - Wood, Wood Products, Metal Doors

These feed rates are in inches per minute and are only guidelines. Actual speed and feed rates will depend on individual equipment and goals. Generally, the faster a bit is fed, the longer the edges will last. For maximum life, start at a "safe" rate, then push feed rate until either finish is undesirable, or tool is risking breakage. Other factors that affect feed rate are:

- **Rigidity of Set Up**

Vibration is a major source of tool wear and poor finish. Adjust feed rate to minimize vibration. Often a faster rate can improve finishes.

- **Router environment**

Other variable that affect every routing application are spindle, horsepower, rigidity and runout, collet condition, clamping system and tool sharpness. Adjust feed rate to achieve desired finish.

- **Spindle Speed**

Adjust feed rate chart on a linear basis relative to 18,000 spindle RPM. If spindle is 20,000 RPM, increase speed by 10%; if spindle is 14,500 RPM, reduce speed rate by approximately 20%.

- **Finish**

Find the fastest feed rate that will enable you to obtain a satisfactory finish for the best tool life.

- **Routing Formulas**

Feed Rate (Inches per Minute) = RPM x Number of Cutting Edges x Chip Load

Chip Load = Feed Rate / (RPM x Number of Cutting Edges)

Speed (RPM) = Feed Rate / (Number of Cutting Edges x Chip Load)

NAP GLADU Tool Series	Cutting Diameter	Cutting Depth	Spindle Speed	Soft Natural Wood	Hard Natural Wood	Soft Plywood	Hard Plywood	MDF	Laminated Chipboard	Laminated Plywood	Metal Door Foam Core
BC10-00	1/4	1/4	18,000	100-200	—	—	—	—	—	—	—
BC12-00	1/2	1/2	18,000	—	100-300	—	—	—	—	—	—
BC12-80	1/2	1/2	18,000	100-500	100-300	—	—	—	—	—	—
BC14-00	1/2	2	18,000	100-500	—	—	—	—	—	—	—
BC15-00	1/2	2	18,000	—	—	—	—	—	—	—	—
BC15-50	1/2	2	2,000-2,500	—	—	—	—	—	—	—	100-200
BC15-75	1/2	2	2,000-2,500	150	—	—	—	—	—	—	200-300
BC30-00	N/A	Varies	18,000	150	150	—	—	150	—	—	—
BC37-50	*	*	18,000	150	150	150	150	150	—	—	—
BC37-60	*	*	18,000	150	150	150	150	150	—	—	—
BC38-00	*	*	18,000	150	150	—	—	—	—	—	—
BC38-50	*	*	18,000	150	150	150	150	150	—	—	—
BC38-60	*	*	18,000	150	150	150	150	150	—	—	—
BC40-000	1/2	3/4	18,000	100-300	100-300	—	—	—	—	—	—
BC40-100	1/2	3/4	18,000	150-400	150-400	—	—	—	—	—	—
BC40-200	1/2	3/4	18,000	100-300	100-300	—	—	—	—	—	—
BC40-300	1/2	3/4	18,000	150-400	150-400	—	—	—	—	—	—
BC40-400	1/2	3/4	18,000	150-400	150-400	—	—	—	—	—	—
BC52-200	1/2	3/4	18,000	200-400	200-400	—	—	200-450	—	—	—
BC57-200	1/2	3/4	18,000	200-400	200-400	—	—	200-450	—	—	—
BC52-400	12 mm	3/4	18,000	200-400	200-400	—	—	200-450	—	—	—
BC57-400	12 mm	3/4	18,000	200-400	200-400	—	—	200-450	—	—	—
BC52-900	1/2	3/4	18,000	200-400	200-400	—	—	200-450	—	—	—
BC56-200	1/2	3/4	18,000	200-400	200-400	200-400	200-400	200-400	—	—	—
BC57-900	1/2	3/4	18,000	200-400	200-450	—	—	200-450	—	—	—
BC60-000 (high)	1/2	3/4	18,000	600-1,000	600-1,000	600-1,200	600-1,200	500-1,000	—	—	—
BC60-000 (low)	1/2	3/4	18,000	700-1,200	700-1,200	700-1,500	700-1,500	600-1,500	—	—	—
BC60-090	1/2	3/4	18,000	100-400	100-400	100-400	100-400	100-400	—	—	—
BC60-100 (1 edge)	1/2	3/4	18,000	100-600	100-600	100-600	100-600	100-500	100-600	100-600	—
BC60-100 (2 edge)	1/2	3/4	18,000	400-1,200	400-1,000	400-1,200	400-1,000	400-800	400-1,200	400-1,000	—
BC60-100 (3 edge)	1/2	3/4	18,000	500-1,600	500-1,500	700-1,800	700-1,600	600-1,200	700-1,800	700-1,600	—
BC60-100C	1/2	3/4	18,000	400-1,500	400-1,200	400-1,400	400-1,200	400-1,000	400-1,400	400-1,200	—
BC60-200	1/2	3/4	18,000	200-600	200-500	—	—	200-500	—	—	—
BC60-470	1/2	3/4	18,000	200-600	200-500	—	—	200-500	—	—	—
BC60-300	1/2	3/4	18,000	400-1,500	400-1,200	400-1,400	400-1,200	400-1,000	—	—	—
BC60-400	1/2	3/4	18,000	400-1,500	400-1,200	400-1,400	400-1,200	400-1,000	—	—	—
BC60-350	1/2	3/4	18,000	500-1,600	500-1,500	700-1,800	700-1,600	600-1,200	—	—	—
BC60-430	1/2	3/4	18,000	500-1,600	500-1,500	700-1,800	700-1,600	600-1,200	—	—	—
BC60-450	12 mm	3/4	18,000	200-600	200-500	—	—	200-500	—	—	—
BC60-500 (M)	1/2	3/4	18,000	500-1,600	500-1,500	700-2,400	700-2,200	600-1,600	700-2,400	700-2,200	—
BC60-600	1/2	3/4	18,000	1,000-1,800	1,000-1,800	1,200-3,000	1,200-2,800	1,000-2,000	1,200-3,000	1,200-2,800	—
BC60-700	1/2	3/4	18,000	1,000-1,800	1,000-1,800	1,200-3,000	1,200-2,800	1,000-2,000	—	—	—
BC60-900	1/2	3/4	18,000	700-1,200	700-1,200	700-1,500	700-1,500	600-1,500	—	—	—
BC60-950	1/2	3/4	18,000	400-1,500	400-1,200	400-1,400	400-1,200	400-1,000	—	—	—
BC61-000	1/4	1/2	18,000	100-300	—	—	—	—	—	—	—
BC61-200	1/4	1/2	18,000	100-300	100-250	100-250	100-200	100-250	—	—	—
BC62-200	1/4	1/2	18,000	150-300	150-300	—	—	150-300	—	—	—
BC63-200	1/4	1/2	18,000	150-300	150-300	—	—	150-300	—	—	—

*Depth of Cut = Half of the Cutting Edge Diameter

CNC Router Feed Chart - Plastics, Foam and Aluminum

NAP GLADU Tool Series	Soft Plastic	Hard Plastic	Fibrous Reinforcements	Foam	Aluminum	Solid Surface
BC10-00	150	—	—	—	—	—
BC12-00	—	—	—	100	—	—
BC14-00	—	—	—	—	90	Aluminum Extrusion or Aluminum UAD Doors Windows
BC15-00	—	—	—	—	90	—
BC37-50	150	150	—	—	—	150
BC37-60	150	Depth of Cut 150	Depth of Cut —	—	—	150
BC38-50	150	1/2 of CED 150	1/2 of CED —	—	—	150
BC38-60	150	150	—	—	—	150
BC40-000	—	—	—	—	120	—
BC40-100	—	—	—	—	120	—
BC40-300	—	—	—	—	120	16,000 RPM
BC52-000	—	—	—	150	150	150-200
BC52-200	200	—	—	—	—	150-200
BC52-400	200	—	—	—	—	150-200
BC52-600	275	250	—	—	—	150
BC53-000	—	—	150	—	—	3/8" CED, 5/8" DOC
BC56-000P	—	250	150	—	—	150-200
BC56-430	300	275	—	—	—	—
BC56-450	—	250	150	—	—	150-200
BC56-600	300	275	—	—	—	—
BC57-000	—	—	150	—	150	16,000 RPM
BC57-200	—	—	—	—	—	150-200
BC57-400	—	—	—	—	—	150-200
BC57-600	300	275	—	—	—	—
BC58-000	—	—	150	—	—	—
BC55-000	—	—	150	—	—	—
BC59-000	—	—	150	—	—	—
BC54-000	—	—	150	—	—	—
BC60-200	—	300	—	—	—	100-300
BC60-470	—	300	250	—	—	100-300
BC61-000P	350	300	—	—	—	—
BC61-400	350	300	—	—	—	—
BC62-000	—	—	100	—	150	—
BC62-400	—	—	100	—	150	—
BC62-600	—	—	—	—	54-144	—
BC62-700	—	200	—	—	—	100-180
BC62-750	150	150	—	—	—	100-180
BC62-800	—	200	—	—	—	100-180
BC62-850	150	150	—	—	—	100-180
BC62-900	—	—	—	—	54-144	—
BC63-000	—	—	100	—	150	—
BC63-400	—	—	100	—	150	—
BC63-600	—	—	—	—	54-144	—
BC63-700	—	200	—	—	—	100-180
BC63-750	150	150	—	—	—	100-180
BC63-800	—	200	—	—	—	100-180
BC63-850	150	150	—	—	—	100-180
BC63-900	—	—	—	—	54-144	—
BC66-000	125	125	—	—	—	125
BC66-200	150	150	—	—	—	—
BC66-250	150	150	—	—	—	—
BC66-300	175	150	—	—	150	—
BC66-350	175	150	—	—	150	—
BC67-000	—	—	125	—	—	—

This feed chart is based on 18,000 RPM, 1/4" cutting diameter and 1/4" cutting height. These feed rates are in inches per minute and are only guidelines. The actual speed and feed rates will depend on individual equipment and goals. Generally, the faster a bit is fed, the longer the edges will last. For maximum life, start at a "safe" rate, then push feed rate until either finish is undesirable, or tool is risking breakage. Other factors that affect feed rate are:

- Rigidity of Set Up**
Vibration is a major source of tool wear and poor finish. Adjust feed rate to minimize vibration. Often a faster rate can improve finishes.
- Router environment**
Other variable that affect every routing application are spindle, horsepower, rigidity and runout, collet condition, clamping system and tool sharpness. Adjust feed rate to achieve desired finish.
- Number of Flutes**
Single flute tools should be fed at a slightly higher rate (approximately 10% more) than double flute tools.
- Bit Diameter**
This chart is for 1/4" diameter bits. Bit diameter feed factors are as follows: 3/8" diameter, plus 10%; 1/2" diameter, plus 20%.
- Depth of Cut**
Decrease feed rate approximately 25% for each multiple of the depth cut. For example, if the depth is 2 times, reduce by 25%; if the depth is 3 times, reduce by 50%.
- Spindle Speed**
Adjust your feed rate chart on a linear basis relative to 18,000 spindle RPM. If spindle is 20,000 RPM, increase speed by 10%; if spindle is 14,500 RPM, reduce speed rate by approximately 20%.
- Finish**
Find the fastest feed rate that will enable you to obtain a satisfactory finish for the best tool life.
- Routing Formulas**

$$\text{Feed Rate}^* = \text{RPM} \times \text{Number of Cutting Edges} \times \text{Chip Load}$$

$$\text{Chip Load} = \text{Feed Rate} / (\text{RPM} \times \text{Number of Cutting Edges})$$

$$\text{Speed (RPM)} = \text{Feed Rate} / (\text{Number of Cutting Edges} \times \text{Chip Load})$$

*Feed Rate is in Inches per Minute

Conversions, Troubleshooting and Indexes

Series Alpha-Numeric Index

Series 0000021, 27, 97	Series 22000L7	Series 45000G57	Series 76000K85	Series BC52-000B ...112	Series BC62-700 ...134
Series 5169	Series 2300011-12	Series 45000H57	Series 7700085	Series BC52-000BL .112	Series BC62-750 ...135
Series 7169	Series 2400018-19	Series 4600020, 58, 64-68, 72-76	Series 78000A86	Series BC52-400 ...113	Series BC62-800 ...136
Series 0010097	Series 2500025-28, 65		Series 78000B86	Series BC52-600 ...113	Series BC62-850 ...137
Series 120200	Series 25000L26	Series 46000A51	Series 78000C86	Series BC52-900 ...113	Series BC62-900 ...136
Series 121198	Series 2600024-25, 28	Series 46000B51	Series 78000D87	Series BC53-000 ...114	Series BC63-000 ...137
Series 121V198	Series 26000B24	Series 46000C51	Series 78000E87	Series BC54-000 ...121	Series BC63-200 ...138
Series 122203	Series 2700014-17	Series 46000D52	Series 78000F87	Series BC54-300 ...114	Series BC63-400 ...137
Series 122CT201	Series 2900021	Series 46000E52	Series 78000G88	Series BC55-000 ...121	Series BC63-600 ...138
Series 122V198	Series 3000020	Series 46000F52	Series 78000H88	Series BC55-300 ...114	Series BC63-700 ...138
Series 122VCT199	Series 3100013-14, 75	Series 4700031-32	Series 78000I88	Series BC56-000G .115	Series BC63-750 ...139
Series 123202	Series 3200022-24	Series 47000B31	Series 78000J89	Series BC56-000P .115	Series BC63-800 ...139
Series 125CT199	Series 3300022	Series 47000D69	Series 78000K89	Series BC56-200 ...116	Series BC63-850 ...140
Series 1297	Series 3400013, 20	Series 47000E69	Series 78000L89	Series BC56-400 ...116	Series BC63-900 ...140
Series 129-460147	Series 3900036, 38	Series 47000F69	Series 79000A90	Series BC56-430 ...117	Series BC66-000 ...142-143
Series 137186	Series 4000037, 41	Series 47000G70	Series 79000B90	Series BC56-450 ...117	Series BC66-200 ...141
Series 140177	Series 40000B37	Series 47000H70	Series 79000C90	Series BC56-600 ...118	Series BC66-250 ...141
Series 149174	Series 4100038-39, 42, 73	Series 47000I70	Series 79000D91	Series BC57-000 ...117	Series BC66-300 ...141
Series 149CT175		Series 4800033-36	Series 79000E91	Series BC57-200 ...118-119	Series BC66-350 ...141
Series 155186	Series 4200028-31	Series 50000162	Series ACC179	Series BC57-400 ...120	Series BC67-000 ...144
Series 157186	Series 42000B29	Series 51000172-173	Series ARB179	Series BC57-600 ...120	Series BC67-200 ...144
Series 164182	Series 4300042-44	Series 51700173	Series BC10-00101	Series BC57-900 ...120	Series BC70-100 ...145
Series 200187	Series 43000A44	Series 52000167-168	Series BC11-00101	Series BC58-000 ...121	Series BC70-200 ...145
Series 200A184	Series 43000B45	Series 53000163-164	Series BC12-00102	Series BC59-000 ...121	Series BC70-300 ...146
Series 200CT188	Series 43000C45	Series 53000A163	Series BC12-80102	Series BC60-000 ...122	Series BC70-500 ...147
Series 202C200	Series 43000D45	Series 55000165	Series BC14-00103	Series BC60-090 ...147	Series BC90-000 ...152
Series 202CT199	Series 43000E46	Series 56000165	Series BC15-00103	Series BC60-100C .124	Series DRL179
Series 202CTA200	Series 43000F46	Series 57000166	Series BC15-50103	Series BC60-100DE .124	Series H0000178
Series 203182	Series 43000G46	Series 58000166	Series BC15-75104	Series BC60-100M .125	Series ICK153
Series 203CT185	Series 43000H47	Series 59000166	Series BC16-50104	Series BC60-100MW 126	Series ICKA154
Series 205B189	Series 43000I47	Series 60000167	Series BC18-00104	Series BC60-100SE .123	Series ICKB154
Series 205BM189	Series 43000J47	Series 6300079	Series BC20-00105	Series BC60-100TE .125	Series ICKC154
Series 250CT202	Series 43000K48	Series 70000A76	Series BC20-10105	Series BC60-200 ...126	Series ICKD155
Series 250CTS201	Series 43000L48	Series 70000B77	Series BC28-20105	Series BC60-300 ...127	Series GBC155
Series 340BCT190	Series 43000M48	Series 70000C77	Series BC33-00148	Series BC60-350 ...127	Series GF155
Series 340BMCT ...190	Series 43000N49	Series 7200078	Series BC33-10149	Series BC60-400 ...128	Series TORX152
Series 0050095, 152	Series 43000P49	Series 72000B78	Series BC33-30148	Series BC60-430 ...128	Series X10193
Series 0060095	Series 43000Q49	Series 75000A80	Series BC33-60148	Series BC60-450 ...129	Series X10L194
Series 600P177	Series 43000R50	Series 75000B80	Series BC34-00148	Series BC60-470 ...129	Series X10M195
Series 0070096	Series 43000S50	Series 75000C80	Series BC34-50149	Series BC60-500 ...130	Series X122B191
Series 0080096	Series 4400040-41, 61-63	Series 75000D81	Series BC35-00106	Series BC60-500M .130	Series X122B8191
Series 0090095		Series 75000E81	Series BC35-50106	Series BC60-600 ...130	Series X122BED ...191
Series 811CT176	Series 44000A63	Series 75000F81	Series BC37-50106	Series BC60-700 ...131	Series X122D192
Series 812CT176	Series 44000B63	Series 76000A82	Series BC38-00107	Series BC60-900 ...131	Series X124B192
Series 01200163	Series 44000C64	Series 76000B82	Series BC38-50107	Series BC60-950 ...132	Series X124D192
Series 130019, 94	Series 44000D64	Series 76000C82	Series BC40-000D .108	Series BC61-000 ...133	Series X200188
Series 1000053-54	Series 4500050, 58-60	Series 76000D83	Series BC40-000U .108	Series BC61-000P .133	Series X203183
Series 1100053-55	Series 45000A55	Series 76000E83	Series BC40-100D .109	Series BC61-200 ...132	Series X203B184
Series 200009	Series 45000B55	Series 76000F83	Series BC40-100U .109	Series BC61-400 ...132	Series X203I184
Series 210004	Series 45000C56	Series 76000G84	Series BC40-300 ...110	Series BC62-000 ...134	Series X204185
Series 220005-8	Series 45000D56	Series 76000H84	Series BC40-550 ...110	Series BC62-200 ...134	Series X205BM ...190
Series 22000A10	Series 45000E56	Series 76000I84	Series BC52-200 ...111	Series BC62-400 ...134	
Series 22000C10	Series 45000F57	Series 76000J85	Series BC52-000 ...112	Series BC62-600 ...135	

Tool Number Alpha-Numeric Index

0010097	130394	1031454	202189	21469SC4	222776	22488SC5	24240C19
0011097	130419, 94	1031654	202209	21470SC4	22277A10	22489SC5	24242B19
0011297	130594	1032054	202229	21471SC4	22277L7	22490SC5	24244A19
0021097	130694	1032254	202249	21472SC4	222786	22491SC5	2440218
0021221	1306A94	1032454	202269	21473SC4	222796	22492SC5	2440418
0021321	130794	1032654	202289	21474SC4	222806	22493SC5	2440618
0021497	130894	1032854	202309	21475SC4	22280A10	22869C10	2440818
0021697	130994	1033054	202329	21476SC4	222816	228707	2441018
0021897	1309A94	1033254	202369	21477SC4	22281L7	228717	2441218
0022097	131094	1120653	202389	21478SC4	222826	228727	2441418
0022297	131194	1120853	202409	21479SC4	222836	228737	2441618
0023097	131294	1121253	202429	222106	222846	22873L7	2441818
0023297	131394	1121453	202449	222126	222856	228747	2442218
0025027	131494	1122053	202469	222146	222876	228757	2442418
0035027	131594	1122253	202489	222186	222886	22875L7	2520026
0041097	131694	1122453	202509	222266	222906	228767	2520126
0041221	131794	1122853	202529	22226A10	222916	22876L7	25201L26
0050295	131894	1123053	202549	22226L7	22292A10	228787	2520226
0050495	131994	1123253	202569	222286	222936	228797	25202L26
0050695	132094	1124454	202589	22228L7	222946	228807	2520326
0050895	132194	1124654	202609	222346	22294A10	228817	25203L26
0051095	1321A94	1124854	202629	222366	222956	228827	2520426
0051219, 95	132294	1125054	202649	22236L7	22295A10	2320011	25204L26
0051495	1322A94	1125254	202669	222386	222966	2320111	2521326
0051695	132394	1125454	202689	22238A10	224015	2320411	2521426
0051895	132494	1125854	204109	222406	224025	2320611	2521526
0052095	132594	1126054	204129	222426	224035	2322011	2521626
0052295	132694	1126254	204149	22242A10	224045	2322211	25216L26
00550152	132794	1126454	204169	222436	224065	2322411	2521726
00560152	135094	1126654	204189	22243L7	224085	2322611	25217L26
00570152	135194	1126854	204209	222446	224095	2324412	2521826
00575152	135294	1127054	204229	222456	224105	2324512	2522026
00580152	135394	1129055	204249	22245A10	224125	2324612	25220L26
00585152	1353A94	1140653	204269	222476	224145	2324812	2522626
0061095	1353B94	1140853	204289	22247A10	224185	2325012	2522726, 65
0062095	1353C94	1141253	204309	22247C10	224225	2325112	25227L26
0063095	1353D94	1141453	204329	22247L7	224245	2325212	2522826
0064095	135494	1142053	204349	222496	224265	2325412	25228L26
0070296	135594	1142253	204369	22249A10	22426A10	2325612	2522926
0070496	135694	1142453	204389	22249C10	224285	2326212	2531626
0070696	135794	1142853	204409	22249L7	224345	2326412	2540026
0070896	135894	1143053	204429	222506	22434A10	232708	2540526
0071096	135994	1143253	204449	222516	224365	232728	2540626
0071196	136094	1144454	204469	222526	22436A10	232748	2540826
0071296	137019	1144654	204489	22252A10	224385	232768	2541026
0071496	137119	1144854	204509	22252C10	224415	2328011	2541226
0071596	137219	1145054	204529	22252L7	224425	2328111	2541526
0071696	137319	1145254	204549	222536	224445	2328211	25415L26
0080296	137419	1145454	212144	22253C10	22444A10	2340011	2541626
0080419, 96	137519	1145854	212184	222546	224455	2343012	2541826
0080696	137619	1146054	212284	222566	22445A10	2343212	2542026
0081096	137719	1146254	212364	222576	224475	2343412	25420L26
0081219, 96	137819	1146454	212384	22257L7	224555	2343612	2542226
0081496	137919	1146654	212454	222596	224565	2343812	2542426
0081696	138019	1146854	212474	222606	224585	2344012	2543026
0081896	138119	1147054	212494	22260A10	22458A10	2344112	2544028
0082096	138219	1240021	212524	22260L7	224595	2344212	2545025
0082296	138319	1240121	212564	222616	224655	2344312	2546025
0090295	138419	1240221	212604	222626	224665	2344412	2548025
0090495	138519	1240321	214004	22262A10	224685	2344612	2548225
0090695	138619	1240421	214044	222646	224695	2346012	2550227
0090895	1020653	1240521	214064	222676	224745	2388011	25502L27
0091095	1020853	1240621	214084	222686	224765	2388211	2550427
0091295	1021253	1240721	214124	222696	22476A10	2420218	25504L27
01210163	1021453	1240821	214144	22269A10	224785	2420418	2551227
01212163	1022053	1240921	214184	222706	224795	2420618	25512L27
01214163	1022253	1241021	21418L7	22270L7	22479A10	2420818	2551427
01216163	1022453	1241121	214224	222716	22480SC5	2421018	25514L27
01218163	1022853	1241221	214284	222726	22481SC5	2421218	2552027
01220163	1023053	1241321	214344	22272L7	22482SC5	2421418	25520L27
01222163	1023253	1241421	214364	222736	22483SC5	2421618	2552227
01224163	1030654	1241521	214444	222746	22484SC5	2421818	25522L27
130094	1030854	1241621	214454	222756	22485SC5	2422018	2552427
130194	1031054	1241721	214584	22275L7	22486SC5	2422218	25524L27
130294	1031254	202169	214684	222766	22487SC5	2422418	2553227

Conversions, Troubleshooting and Indexes

Tool Number Alpha-Numeric Index Continued

25532L27	3125414	3924238	4141439	4249031	4349449	4628072	4820633
2553427	3125675	3924438	4141639	4249231	4349649	4628272	4822034
25534L27	3125875	3924838	4141839	4320047	4349849	4628468	4822434
2560027	3140013	3925236	4142039	4320247	4349949	4628667	4823035
2560227	3140113	3925436	4142239	4321048	4420061	4628867	4823235
2620224	3140213	3942238	4142439	4321248	4420261	4629020	4823435
2620424	3140413	3942438	4142639	4321648	4421061	4629120	4823635
2620824	3140613	3942638	4145242	4321848	4421862	4629220	4824035
2621024	3140813	3942838	4145442	4322443	4422062	4629320	4824235
2621224	3141213	3943038	4145642	4322644	4422262	4629420	4824436
2621424	3143613	3943238	4145842	4322843	4422662	4629520	4824636
2621624	3143813	3943638	4146042	4323044	4422863	4629620	4840033
2621824	3144413	3943738	4146242	4323242	4423063	4629720	4840233
2622024	3220424	3945036	4146442	4323442	4423263	4629820	4840433
2622224	3220624	3945236	4146642	4323650	4423464	4640268	4841033
2626024	3220824	4020237	4148038	4323850	4423664	4641068	4841233
2640224	3221024	4020437	4148238	4324243	4425041	4642051	4841433
2640424	3222722	4020637	4148438	4325048	4425241	4642251	4841633
2640624	3222922	40206B37	4149039	4325248	4425641	4643265	4842034
26406B24	3223122	4020837	4221429	4325646	4425841	4646066	4842234
2640824	3227223	4021037	4221529	4325846	4426240	4646266	4842434
2641024	3227423	4021137	4221629	4326044	4426640	4646466	4844035
2641224	3227623	4021237	4221829	4326244	4426840	4647466	4844235
2641424	3240824	4021437	4222029	4326645	4427240	4647566	4844436
2645028	3242222	4022441	4222229	4326845	4520450	4647666	50110162
2646024	3242322	4040037	4222429	4327045	4520650	4647867	50114162
2646224	3242422	40400B37	4222529	4327245	4520750	4648067	50116162
2647024	3242622	40401B37	4222629	4327645	4522056	4720232	50117162
2649025	3242722	4040237	4222829	4327845	4522255	4720432	50118162
2740214	3242822	40402B37	4223229	4328046	4522455	4720632	50120162
2740614	3242922	4040437	4223429	4328246	4522656	4720832	50122162
2740814	3243022	4040637	4223629	4328446	4522856	4721032	50124162
2741015	3243122	4040837	4223829	4328647	4523057	47210B31	50126162
2741215	3243222	4042041	4224029	4328847	4523257	4721232	50127162
2741415	3246323	4042241	4224229	4329047	4523457	4721432	50128162
2742215	3246423	4042441	4224429	4329247	4524058	47214B31	50129162
2742415	3246723	4121239	4224629	4329449	4525058	4721632	50130162
2743016	3246823	4121439	4225030	4329549	4526059	4721832	50132162
2743416	3247223	4121639	4225230	4329649	4527060	47218B31	50134162
2744217	3247423	4121839	4225430	4329849	4527260	4721932	50136162
2744417	3247623	4122039	4225630	4329949	4527460	4722032	50138162
2745217	3248223	4122239	4225830	4340047	4528060	47220B31	50140162
2745417	3248423	4122439	4226030	4340247	4529059	4722132	50142162
2745517	3248623	4122539	4226230	4341048	4620268	4722232	50144162
2745617	3249022	4122639	4226628	4341248	4620468	47222B31	50158162
2746017	3249222	4122839	4226828	4341648	4621068	4722332	50160162
2746217	3249422	4122939	42268B28	4341848	4621268	4722432	50161162
2746417	3249622	4123039	4227030	4342043	4622051	47224B31	50162162
2746617	3249822	4123239	4227230	4342243	4622251	4722632	50163162
2746817	3340222	4123439	4227430	4342443	4622452	4725031	50164162
2747017	3340422	4123639	4227630	4342644	4622652	4725231	50166162
2747217	3340622	4123839	4227830	4342843	4622852	4725431	50167162
2747417	3340822	4124039	4228630	4343042	4623064	4725631	50168162
2748017	3341022	4124239	4228830	4343242	4623265	4725831	50169162
2748217	3341222	4125242	4240229	4343650	4623465	4726032	50170162
2748417	3420213	4125442	4240429	4343850	4623565	47260B32	50171162
2921021	3420413	4125642	4240629	4344043	4623765	4727069	50172162
2940021	3420613	4125842	4241029	4344243	4623865	4727269	50174162
2940221	3420813	4126042	4241229	4345048	4623965	4727469	50176162
2940421	3440213	4126242	4241429	4345248	4624058	4728070	50178162
2940821	3440413	4126442	4241629	4345646	4625072	4728270	50180162
2941021	3440613	4126642	4241829	4345846	4625272	4728470	50182162
3020220	3440820	4126842	42418B29	4346044	4626073	4740232	50184162
3040220	3441020	4127042	4242429	4346645	4626266	4740432	50185162
3120613	3441220	4127242	42424B29	4347045	4626466	4740632	50186162
3120813	3922238	4127442	4242629	4347245	4626574	4740832	51300172
3121013	3922438	4127642	42426B29	4347645	4626674	4741032	51302172
3121413	3922638	4127842	4243229	4347845	4626774	4741232	51304172
3121613	3922838	4128042	4243629	4348046	4626875	4741432	51306172
3123613	3923038	4128242	4246528	4348246	4626976	4741632	51308172
3123813	3923238	4129073	4246628	4348446	4627072	4741832	51310172
3124013	3923638	4129273	42466B28	4348647	4627272	4745231	51312172
3124213	3923738	4129473	4248030	4348847	4627466	4820033	51314172
3125014	3923838	4129673	4248230	4349047	4627673	4820233	51316172
3125214	3924038	4141239	4248430	4349247	4627873	4820433	51318172

Tool Number Alpha-Numeric Index Continued

51320172	52165168	55010165	7030076	179191147	BC03023194	BC12-12102	BC20512M189
51322172	52166168	55012165	7031077	ARA179	BC03024194	BC12-13102	BC20513M189
51324172	52167168	55014165	7031277	ARB1179	BC03025194	BC12-14102	BC20514189
51326172	52168168	55020165	7200478	ARB2179	BC03026194	BC12-16102	BC20514M189
51328172	52169168	55022165	72004B78	ARB3179	BC03027194	BC12-17102	BC20515M189
51330172	52170168	55102165	7200878	ARB4179	BC03028194	BC12-18102	BC20516189
51332172	52171168	55104165	72008B78	ARB5179	BC03029194	BC12-19102	BC20516M189
51334172	52172168	55106165	7523081	ARB6179	BC03030194	BC12-24102	BC20518M189
51336172	52173168	55108165	7523281	ARB7179	BC03031194	BC12-25102	BC20519189
51338172	52174168	55110165	7523481	BC02001193	BC03032194	BC12-26102	BC20520M189
51340172	52175168	55112165	7523680	BC02002193	BC04100195	BC12-27102	BC20522189
51342172	52176168	55114165	7523880	BC02003193	BC04200195	BC12-30102	BC20522M189
51344172	52177168	55116165	7524080	BC02004193	BC04300195	BC12-31102	BC20524M189
51346172	52178168	55118165	7620085	BC02005193	BC04400195	BC12-32102	BC20525189
51348172	52179168	55120165	7620285	BC02006193	BC04500195	BC12-33102	BC20525M189
51350172	52180168	55122165	7620484	BC02007193	BC04600195	BC12-35102	BC20526M189
51352172	52181168	55310199	7620682	BC02008193	BC04700195	BC12-36102	BC20528M189
51354172	52182168	55312199	7620882	BC02009193	BC04800195	BC12-37102	BC20530M189
51356172	52183168	55314199	7621082	BC02010193	BC04900195	BC12-51102	BC20535M190
51358172	52184168	55316199	7621283	BC02011193	BC05000195	BC12-55102	BC20545M190
51700173	52185168	55320201	7621483	BC02012193	BC05100195	BC12-79102	BC20555189
51702173	52186168	55322201	7621683	BC02013193	BC05120195	BC12-80102	BC20555M190
51704173	52187168	55324201	7621884	BC02014193	BC05130195	BC12-81102	BC20565M190
51706173	52188168	55326201	7622084	BC02015193	BC05140195	BC12-82102	BC20575M190
51800173	52189168	55530200	7622284	BC02016193	BC05150195	BC12-83102	BC20585M190
51802173	52190168	55532200	7622484	BC02017193	BC05160195	BC12-84102	BC20595M190
51804173	52191168	55534200	7729085	BC02018193	BC05170195	BC12-86102	BC20515M190
51806173	52192168	55510199	7729285	BC02019193	BC05180195	BC12-87102	BC28-20105
51808173	52193168	55512199	7729485	BC02020193	BC05190195	BC12-88102	BC28-25105
51810173	52194168	55514199	7749085	BC02021193	BC05200195	BC14-00103	BC28-30105
51814173	52195168	55516199	7749285	BC02022193	BC10-00101	BC14-03103	BC33-01148
51816173	52196168	55518199	7825089	BC02023193	BC10-01101	BC14-04103	BC33-02148
51818173	52197168	55520199	7825289	BC02024193	BC10-02101	BC14-05103	BC33-03148
51820173	52198168	55522199	7825489	BC02025193	BC10-03101	BC15-00103	BC33-04148
51822173	52199168	55524199	7825689	BC02026193	BC10-04101	BC15-02103	BC33-05148
51826173	53110164	55540201	7825889	BC02027193	BC10-05101	BC15-03103	BC33-10149
51828173	53112164	55542201	7826086	BC02028193	BC10-06101	BC15-05103	BC33-15149
51830173	53114164	55544201	7826286	BC02029193	BC10-07101	BC15-52103	BC33-16149
51832173	53116164	55900200	7826486	BC02030193	BC10-09101	BC15-53103	BC33-17149
51834173	53120164	55910202	7826687	BC02031193	BC10-10101	BC15-54103	BC33-18149
51836173	53122164	55912202	7826887	BC02032193	BC10-11101	BC15-55103	BC33-19149
51838173	53126164	55914202	7827087	BC02033193	BC10-13101	BC15-57103	BC33-25149
51840173	53128164	55916202	7827288	BC02034193	BC10-18101	BC15-60103	BC33-30148
51842173	53130164	55918202	7827488	BC02035193	BC10-20101	BC15-61103	BC33-32148
51844173	53131164	56020165	7827688	BC02036193	BC10-22101	BC15-75104	BC33-34148
51846173	53132164	56025165	7928091	BC02037193	BC10-24101	BC16-50104	BC33-36148
51848173	53133164	56030165	7928291	BC02038193	BC10-78101	BC16-51104	BC33-38148
51850173	53134164	56035165	7928490	BC02039193	BC11-00101	BC16-52104	BC33-40149
52110167	53136164	56040165	7928690	BC02040193	BC11-01101	BC18-00104	BC33-42149
52112167	53138164	59005166	7928890	BC02041193	BC11-02101	BC18-02104	BC33-44149
52114167	53139164	59006166	90200GBC152	BC02042193	BC11-03101	BC18-03104	BC33-50149
52116167	53140164	59008166	90210GBC152	BC02043193	BC11-04101	BC20-00105	BC33-51149
52118167	53142164	59010166	90212GBC152	BC02044193	BC11-05101	BC20-02105	BC33-52149
52120167	53144164	59105166	90218GBC152	BC02045193	BC11-06101	BC20-03105	BC33-53149
52122167	53210163	59106166	90220GBC152	BC03002194	BC11-07101	BC20-10105	BC33-54149
52124167	53210A163	59108166	90226GBC152	BC03003194	BC11-09101	BC20-11105	BC33-55149
52126167	53212163	59110166	90240ICK152	BC03004194	BC11-10101	BC20503189	BC33-56149
52128167	53212A163	60005167	90242ICK152	BC03005194	BC11-11101	BC20503M189	BC33-57149
52130167	53214163	60006167	90850GBC152	BC03006194	BC11-71101	BC20504189	BC33-58149
52134167	53214A163	60008167	178359147	BC03007194	BC11-72101	BC20504M189	BC33-60148
52138167	53216163	60105167	178360147	BC03008194	BC11-73101	BC20505189	BC33-62148
52140167	53216A163	60106167	178362147	BC03009194	BC11-74101	BC20505M189	BC33-64148
52142167	53218163	60108167	178839147	BC03010194	BC11-75101	BC20506189	BC34-03148
52144167	53218A163	60110167	178840147	BC03011194	BC11-76101	BC20506M189	BC34-05148
52146167	53220163	6321079	178841147	BC03012194	BC11-77101	BC20507189	BC34-51149
52148167	53220A163	6322079	178842147	BC03013194	BC11-78101	BC20507M189	BC34-52149
52150167	53222163	6322279	178843147	BC03014194	BC12-00102	BC20508189	BC34-53149
52152167	53222A163	6341079	1788988	BC03015194	BC12-01102	BC20508M189	BC34-54149
52154167	53224163	6342079	1789008	BC03016194	BC12-03102	BC20509189	BC34-55149
52156167	53224A163	6342279	1789028	BC03017194	BC12-05102	BC20509M189	BC34005190
52160168	55000165	6343079	1789048	BC03018194	BC12-06102	BC20510189	BC34006190
52161168	55002165	7020076	178958147	BC03019194	BC12-08102	BC20510M189	BC34008190
52162168	55004165	7020276	178959147	BC03020194	BC12-09102	BC20511189	BC34010190
52163168	55006165	7021077	179189147	BC03021194	BC12-10102	BC20511M189	BC34012190
52164168	55008165	7022077	179190147	BC03022194	BC12-11102	BC20512189	BC34212190

Conversions, Troubleshooting and Indexes

Tool Number Alpha-Numeric Index Continued

BC34213190	BC40-108109	BC47033186	BC52-622113	BC56-340116	BC57-318119	BC60-019122	BC60-168HW .123
BC34214190	BC40-109109	BC47035186	BC52-624113	BC56-360116	BC57-320119	BC60-020122	BC60-169124
BC34215190	BC40-110109	BC47036186	BC52-626113	BC56-361S .116	BC57-321S .119	BC60-037122	BC60-169C .124
BC34217190	BC40-111109	BC52-040112	BC52-638113	BC56-362116	BC57-322118	BC60-038122	BC60-169MW .126
BC35-02106	BC40-112109	BC52-050112	BC52-640113	BC56-365116	BC57-323118	BC60-051122	BC60-170123
BC35-03106	BC40-113109	BC52-060112	BC52-642113	BC56-366S116	BC57-324118	BC60-052122	BC60-171124
BC35-04106	BC40-114109	BC52-060L .112	BC52-644113	BC56-370116	BC57-325119	BC60-053122	BC60-171C .124
BC35-05106	BC40-115109	BC52-070112	BC52-650113	BC56-385116	BC57-325L .119	BC60-054122	BC60-171MW .126
BC35-06106	BC40-116109	BC52-080112	BC52-910113	BC56-390116	BC57-326118	BC60-055122	BC60-172124
BC35-11106	BC40-117109	BC52-080L .112	BC52-923113	BC56-395116	BC57-330119	BC60-056122	BC60-172C .124
BC35-12106	BC40-119109	BC52-090112	BC52-924113	BC56-410116	BC57-340119	BC60-061122	BC60-172L .124
BC35-13106	BC40-121109	BC52-100112	BC52-936113	BC56-411116	BC57-360119	BC60-062122	BC60-172MW .126
BC35-15106	BC40-122109	BC52-120112	BC53-040114	BC56-412116	BC57-361S .119	BC60-063122	BC60-173125
BC35-50106	BC40-123109	BC52-140112	BC53-080114	BC56-414116	BC57-362119	BC60-064122	BC60-173L .125
BC35-51106	BC40-124109	BC52-160112	BC54-040121	BC56-416116	BC57-365119	BC60-065122	BC60-174125
BC35-52106	BC40-130109	BC52-240111	BC54-050121	BC56-418116	BC57-365L .119	BC60-066122	BC60-175125
BC35-53106	BC40-131109	BC52-240B .112	BC54-060121	BC56-430117	BC57-366S .119	BC60-071122	BC60-176125
BC37-50106	BC40-132109	BC52-240BL .112	BC54-080121	BC56-431117	BC57-367119	BC60-072122	BC60-177125
BC37-51106	BC40-133109	BC52-240L .111	BC54-320114	BC56-432117	BC57-370119	BC60-073122	BC60-185123
BC37-52106	BC40-134109	BC52-244111	BC54-325114	BC56-434117	BC57-380119	BC60-074122	BC60-186124
BC38-01107	BC40-135109	BC52-250111	BC54-360114	BC56-436117	BC57-385119	BC60-075122	BC60-186C .124
BC38-02107	BC40-136109	BC52-251111	BC54-365114	BC56-438117	BC57-385L .119	BC60-076122	BC60-186L .124
BC38-03107	BC40-137109	BC52-260111	BC54-440121	BC56-450117	BC57-390119	BC60-090147	BC60-195123
BC38-05107	BC40-138109	BC52-260B .112	BC54-460121	BC56-451117	BC57-395119	BC60-102123	BC60-196124
BC38-06107	BC40-139109	BC52-260BL .112	BC54-480121	BC56-452117	BC57-395L .119	BC60-106123	BC60-196C .124
BC38-50107	BC40-140109	BC52-260L .111	BC55-040121	BC56-454117	BC57-410120	BC60-110123	BC60-197125
BC38-51107	BC40-141109	BC52-261111	BC55-050121	BC56-456117	BC57-411120	BC60-111125	BC60-198124
BC38-52107	BC40-142109	BC52-270111	BC55-060121	BC56-458117	BC57-412120	BC60-112124	BC60-198L .124
BC38-53107	BC40-143109	BC52-271111	BC55-080121	BC56-460118	BC57-414120	BC60-113125	BC60-199125
BC40-001108	BC40-144109	BC52-280111	BC55-320114	BC56-612118	BC57-416120	BC60-120123	BC60-239126
BC40-002108	BC40-153109	BC52-280B .112	BC55-325114	BC56-614118	BC57-418120	BC60-120L .123	BC60-240126
BC40-003108	BC40-158109	BC52-280BL .112	BC55-360114	BC56-616118	BC57-420120	BC60-121125	BC60-241126
BC40-004108	BC40-301S .110	BC52-281S .111	BC55-365114	BC56-618118	BC57-422120	BC60-122HS .123	BC60-242126
BC40-005108	BC40-302S .110	BC52-285111	BC56-040115	BC56-620118	BC57-424120	BC60-123125	BC60-243126
BC40-006108	BC40-303S .110	BC52-285L .111	BC56-041115	BC56-624118	BC57-426120	BC60-123C .124	BC60-244126
BC40-007108	BC40-304S .110	BC52-287111	BC56-050115	BC56-625118	BC57-623120	BC60-123MW .126	BC60-245126
BC40-008108	BC40-307H .110	BC52-290111	BC56-060115	BC56-625L .118	BC57-625120	BC60-124124	BC60-246126
BC40-009108	BC40-307S .110	BC52-300111	BC56-061115	BC56-626118	BC57-627120	BC60-124C .124	BC60-249126
BC40-010108	BC40-308H .110	BC52-310111	BC56-062115	BC56-628118	BC57-637120	BC60-125125	BC60-250126
BC40-011108	BC40-308S .110	BC52-310L .111	BC56-062L .115	BC56-638118	BC57-639120	BC60-126125	BC60-251126
BC40-012108	BC40-311S .110	BC52-318111	BC56-063115	BC56-639118	BC57-643120	BC60-126MW .126	BC60-252126
BC40-015108	BC40-312S .110	BC52-320111	BC56-070115	BC56-650118	BC57-645120	BC60-127L .125	BC60-253126
BC40-016108	BC40-333H .110	BC52-320B .112	BC56-080115	BC56-652118	BC57-651120	BC60-132123	BC60-254126
BC40-019108	BC40-333S .110	BC52-320BL .112	BC56-081115	BC56-654118	BC57-910120	BC60-133 .124	BC60-269126
BC40-021108	BC40-334H .110	BC52-321S .111	BC56-082115	BC56-655118	BC57-921120	BC60-134123	BC60-270126
BC40-022108	BC40-334S .110	BC52-325111	BC56-082L .115	BC57-040117	BC57-923120	BC60-135124	BC60-271126
BC40-023108	BC40-335H .110	BC52-325L .111	BC56-084115	BC57-050117	BC57-924120	BC60-135C .124	BC60-272126
BC40-024108	BC40-335S .110	BC52-330111	BC56-086115	BC57-060117	BC57-936120	BC60-136123	BC60-307127
BC40-030108	BC40-336H .110	BC52-340111	BC56-090115	BC57-070117	BC58-040121	BC60-137 .124	BC60-308127
BC40-031108	BC40-336S .110	BC52-360111	BC56-100115	BC57-080117	BC58-060121	BC60-137C .124	BC60-311127
BC40-032108	BC40-339H .110	BC52-360B .112	BC56-120115	BC57-090117	BC58-080121	BC60-138123	BC60-312127
BC40-033108	BC40-339S .110	BC52-360BL .112	BC56-121115	BC57-100118	BC59-040121	BC60-139124	BC60-313127
BC40-034108	BC40-340H .110	BC52-361S .111	BC56-122115	BC57-120117	BC59-060121	BC60-139C .124	BC60-314127
BC40-035108	BC40-340S .110	BC52-362111	BC56-122L .115	BC57-140117	BC59-080121	BC60-140124	BC60-315127
BC40-036108	BC40-343H .110	BC52-365111	BC56-124115	BC57-160117	BC59-440121	BC60-140C .124	BC60-316127
BC40-037108	BC40-343S .110	BC52-365L .111	BC56-140115	BC57-240119	BC59-460121	BC60-142123	BC60-317127
BC40-038108	BC40-344H .110	BC52-366S .111	BC56-160115	BC57-240L .119	BC59-480121	BC60-152125	BC60-318127
BC40-039108	BC40-344S .110	BC52-367111	BC56-162115	BC57-244119	BC60-001122	BC60-154125	BC60-321127
BC40-040108	BC40-562110	BC52-370111	BC56-162L .115	BC57-250119	BC60-002122	BC60-155125	BC60-322127
BC40-041108	BC40-564110	BC52-380111	BC56-164115	BC57-251119	BC60-003122	BC60-156125	BC60-325127
BC40-042108	BC47017186	BC52-385111	BC56-240116	BC57-260119	BC60-004122	BC60-157125	BC60-326127
BC40-043108	BC47018186	BC52-385L .111	BC56-250116	BC57-260L .119	BC60-005122	BC60-158125	BC60-337127
BC40-044108	BC47019186	BC52-390111	BC56-260116	BC57-261119	BC60-006122	BC60-160123	BC60-338127
BC40-051108	BC47020186	BC52-395111	BC56-270116	BC57-264119	BC60-007122	BC60-161125	BC60-350127
BC40-052108	BC47021186	BC52-395L .111	BC56-280116	BC57-270119	BC60-008122	BC60-161L .125	BC60-351127
BC40-053108	BC47022186	BC52-410113	BC56-281S .116	BC57-271119	BC60-009122	BC60-162HS .123	BC60-352127
BC40-054108	BC47023186	BC52-411113	BC56-285116	BC57-280119	BC60-010122	BC60-163125	BC60-353127
BC40-058108	BC47024186	BC52-412113	BC56-287116	BC57-281S .119	BC60-011122	BC60-163C .124	BC60-354127
BC40-101109	BC47025186	BC52-414113	BC56-290116	BC57-285119	BC60-012122	BC60-163MW .126	BC60-355127
BC40-102109	BC47026186	BC52-416113	BC56-300116	BC57-285L .119	BC60-013122	BC60-164 .124	BC60-360127
BC40-103109	BC47027186	BC52-418113	BC56-310116	BC57-287119	BC60-014122	BC60-164C .124	BC60-361127
BC40-104109	BC47028186	BC52-420113	BC56-320116	BC57-290119	BC60-015122	BC60-165123	BC60-370127
BC40-105109	BC47029186	BC52-422113	BC56-321S .116	BC57-300119	BC60-016122	BC60-165L .123	BC60-371127
BC40-106109	BC47030186	BC52-424113	BC56-325116	BC57-310119	BC60-017122	BC60-166125	BC60-372127
BC40-107109	BC47031186	BC52-426113	BC56-330116	BC57-310L .119	BC60-018122	BC60-167123	BC60-373127

BC60-374 ...127	BC60-901 ...131	BC62-320 ...134	BC62-880 ...137	BC62039 ...183	BC62117 ...187	BC62191 ...188	BC62303 ...202
BC60-375 ...127	BC60-902 ...131	BC62-360 ...134	BC62-882 ...137	BC62040 ...183	BC62118 ...187	BC62192 ...188	BC62304 ...202
BC60-411 ...128	BC60-905 ...131	BC62-410 ...134	BC62-884 ...137	BC62041 ...183	BC62119 ...187	BC62193 ...188	BC62305 ...202
BC60-412 ...128	BC60-906 ...131	BC62-411 ...134	BC62-886 ...137	BC62042 ...183	BC62120 ...187	BC62194 ...188	BC62306 ...202
BC60-413 ...128	BC60-907 ...131	BC62-412 ...134	BC62-888 ...137	BC62043 ...183	BC62121 ...187	BC62195 ...188	BC62307 ...202
BC60-414 ...128	BC60-908 ...131	BC62-414 ...134	BC62-890 ...137	BC62044 ...183	BC62122 ...187	BC62196 ...188	BC62308 ...202
BC60-415 ...128	BC60-909 ...131	BC62-604 ...135	BC62-892 ...137	BC62045 ...183	BC62123 ...187	BC62197 ...188	BC62309 ...202
BC60-416 ...128	BC60-910 ...131	BC62-606 ...135	BC62-894 ...137	BC62046 ...183	BC62124 ...187	BC62198 ...188	BC62310 ...202
BC60-417 ...128	BC60-950 ...132	BC62-610 ...135	BC62-896 ...137	BC62047 ...183	BC62125 ...187	BC62199 ...188	BC62311 ...202
BC60-418 ...128	BC60-951 ...132	BC62-612 ...135	BC62-898 ...137	BC62048 ...183	BC62126 ...187	BC62200 ...188	BC62312 ...202
BC60-419 ...128	BC60-954 ...132	BC62-614 ...135	BC62-899 ...137	BC62049 ...183	BC62127 ...187	BC62201 ...188	BC62313 ...202
BC60-420 ...128	BC60-955 ...132	BC62-618 ...135	BC62-902 ...136	BC62050 ...183	BC62128 ...187	BC62202 ...188	BC62314 ...202
BC60-431 ...128	BC60-956 ...132	BC62-620 ...135	BC62-904 ...136	BC62051 ...183	BC62129 ...187	BC62239 ...169	BC62315 ...202
BC60-432 ...128	BC60-957 ...132	BC62-622 ...135	BC62-906 ...136	BC62052 ...183	BC62130 ...187	BC62240 ...169	BC62316 ...202
BC60-433 ...128	BC60-958 ...132	BC62-624 ...135	BC62-908 ...136	BC62053 ...183	BC62131 ...187	BC62241 ...169	BC62317 ...202
BC60-434 ...128	BC60-959 ...132	BC62-625 ...135	BC62-910 ...136	BC62054 ...183	BC62132 ...187	BC62242 ...169	BC62318 ...202
BC60-435 ...128	BC61-040 ...133	BC62-626 ...135	BC62-912 ...136	BC62055 ...183	BC62133 ...187	BC62243 ...169	BC62338 ...199
BC60-436 ...128	BC61-041 ...133	BC62-630 ...135	BC62-914 ...136	BC62056 ...183	BC62134 ...187	BC62244 ...169	BC62339 ...199
BC60-437 ...128	BC61-042 ...133	BC62-634 ...135	BC62-916 ...136	BC62057 ...183	BC62135 ...187	BC62245 ...169	BC62340 ...199
BC60-438 ...128	BC61-042L ...133	BC62-712 ...134	BC62-918 ...136	BC62058 ...183	BC62136 ...187	BC62246 ...169	BC62345 ...200
BC60-439 ...128	BC61-043 ...133	BC62-713 ...134	BC62-920 ...136	BC62059 ...183	BC62137 ...187	BC62247 ...169	BC62346 ...200
BC60-440 ...128	BC61-044 ...133	BC62-715 ...134	BC62-922 ...136	BC62060 ...183	BC62138 ...187	BC62248 ...169	BC62347 ...200
BC60-451 ...129	BC61-045 ...133	BC62-718 ...134	BC62-924 ...136	BC62061 ...183	BC62139 ...187	BC62249 ...198	BC62348 ...200
BC60-452 ...129	BC61-050 ...133	BC62-719 ...134	BC62-926 ...136	BC62062 ...183	BC62140 ...187	BC62250 ...198	BC62349 ...200
BC60-453 ...129	BC61-052 ...133	BC62-720 ...134	BC62-928 ...136	BC62063 ...183	BC62141 ...187	BC62251 ...198	BC62350 ...200
BC60-454 ...129	BC61-060 ...133	BC62-725 ...134	BC62-930 ...136	BC62064 ...183	BC62142 ...187	BC62252 ...198	BC62351 ...200
BC60-455 ...129	BC61-061 ...133	BC62-726 ...134	BC62-932 ...136	BC62065 ...183	BC62143 ...187	BC62253 ...198	BC62352 ...200
BC60-456 ...129	BC61-062 ...133	BC62-733 ...134	BC62-934 ...136	BC62066 ...183	BC62144 ...187	BC62254 ...198	BC62353 ...200
BC60-457 ...129	BC61-062L ...133	BC62-762 ...135	BC62-936 ...136	BC62067 ...183	BC62145 ...187	BC62255 ...198	BC62354 ...200
BC60-458 ...129	BC61-063 ...133	BC62-763 ...135	BC62-938 ...136	BC62068 ...183	BC62146 ...187	BC62257 ...198	BC62355 ...200
BC60-459 ...129	BC61-064 ...133	BC62-768 ...135	BC62-940 ...136	BC62069 ...183	BC62147 ...187	BC62258 ...198	BC62381 ...191
BC60-460 ...129	BC61-070 ...133	BC62-769 ...135	BC62-942 ...136	BC62070 ...184	BC62148 ...187	BC62259 ...198	BC62382 ...191</

Conversions, Troubleshooting and Indexes

Tool Number Alpha-Numeric Index Continued

BC62475169	BC62772174	BC62874177	BC63-783139	BC63350186	BC67-215144	H0036178	ICK50HM153
BC62476169	BC62773174	BC62875177	BC63-802139	BC63351186	BC67-216144	H0058178	ICK50P153
BC62477169	BC62774174	BC62876177	BC63-804139	BC63352186	BC70-100145	H0078178	ICK50SM153
BC62478169	BC62775174	BC62877177	BC63-806139	BC63353186	BC70-102145	H0096178	ICK50X153
BC62479169	BC62776174	BC62878177	BC63-808139	BC63354186	BC70-104145	H0100178	ICK60G153
BC62480169	BC62777174	BC62879177	BC63-810139	BC63355186	BC70-106145	H0112178	ICK60SM153
BC62481169	BC62778174	BC62880177	BC63-812139	BC63359186	BC70-108145	H0114178	ICK80G153
BC62482169	BC62779175	BC62881177	BC63-814139	BC63360186	BC70-120145	H0116178	ICK80SM153
BC62483169	BC62780175	BC62882177	BC63-816139	BC63361186	BC70-122145	H0118178	ICK100G153
BC62484169	BC62781175	BC62883177	BC63-818139	BC63362186	BC70-124145	H0134178	ICK120G153
BC62485169	BC62782175	BC62884177	BC63-820139	BC66-073142	BC70-126145	H0136178	ICKA9G154
BC62486169	BC62783175	BC62885177	BC63-822139	BC66-074142	BC70-128145	H0138178	ICKA10G154
BC62487169	BC62784175	BC63-040137	BC63-824139	BC66-075142	BC70-140145	H0156178	ICKA10.5G154
BC62488169	BC62785175	BC63-050137	BC63-826139	BC66-076142	BC70-142145	H0158178	ICKA12E154
BC62489169	BC62786175	BC63-060137	BC63-828139	BC66-077143	BC70-144145	H0176178	ICKA12G154
BC62490169	BC62787175	BC63-070137	BC63-830139	BC66-078143	BC70-146145	H0178178	ICKA12HM154
BC62491169	BC62788175	BC63-080137	BC63-832139	BC66-079143	BC70-148145	H0196178	ICKA17G154
BC62492169	BC62789175	BC63-090137	BC63-834139	BC66-082142	BC70-160145	H0200178	ICKA19G154
BC62493169	BC62790175	BC63-100137	BC63-836139	BC66-083142	BC70-162145	H0212178	ICKA50E154
BC62494169	BC62791175	BC63-120137	BC63-838139	BC66-084142	BC70-164145	H0214178	ICKB29.5G154
BC62528185	BC62792175	BC63-140137	BC63-840139	BC66-085143	BC70-166145	H0216178	ICKB29.5X154
BC62529185	BC62793175	BC63-160137	BC63-842139	BC66-086143	BC70-168145	H0218178	ICKB30G154
BC62530185	BC62794175	BC63-240138	BC63-844139	BC66-087143	BC70-180145	H0234178	ICKB30X154
BC62531185	BC62795175	BC63-260138	BC63-846139	BC66-092142	BC70-181145	H0238178	ICKB39.5G154
BC62532185	BC62796175	BC63-280138	BC63-848139	BC66-093142	BC70-182145	H0256178	ICKB40G154
BC62533185	BC62797176	BC63-285138	BC63-849139	BC66-094142	BC70-184145	H0258178	ICKB49.5G154
BC62541184	BC62798176	BC63-300138	BC63-852140	BC66-120143	BC70-202145	H0278178	ICKB50G154
BC62542184	BC62799176	BC63-320138	BC63-854140	BC66-121143	BC70-224145	H0296178	ICKB50X154
BC62543184	BC62800176	BC63-360138	BC63-856140	BC66-122143	BC70-300146	H0300178	ICKC19.5GL1154
BC62544184	BC62801176	BC63-410137	BC63-858140	BC66-123143	BC70-302146	H0312178	ICKC19.5GL2154
BC62545184	BC62802176	BC63-411137	BC63-860140	BC66-160143	BC70-320146	H0314178	ICKC19.5GR154
BC62547184	BC62803176	BC63-412137	BC63-862140	BC60-161143	BC70-322146	H0318178	ICKC29.5GL1154
BC62548184	BC62804176	BC63-414137	BC63-864140	BC66-162143	BC70-340146	H0334178	ICKC29.5GL2154
BC62701186	BC62805176	BC63-604138	BC63-866140	BC66-163143	BC70-342146	H0338178	ICKC29.5GR1154
BC62702186	BC62806176	BC63-606138	BC63-868140	BC66-200141	BC70-360146	H0358178	ICKC29.5GR2154
BC62703186	BC62807176	BC63-610138	BC63-870140	BC66-202141	BC70-362146	H0378178	ICKC49.2GL154
BC62704186	BC62808176	BC63-612138	BC63-872140	BC66-204141	BC70-502147	H0400178	ICKC49.2GR154
BC62705186	BC62809176	BC63-614138	BC63-874140	BC66-206141	BC70-506147	H0412178	ICKD13.6G155
BC62706186	BC62810176	BC63-618138	BC63-876140	BC66-208141	BC70-510147	H0414178	ICKD14E155
BC62736174	BC62811175	BC63-620138	BC63-878140	BC66-210141	BC70-514147	H0418178	ICKD14G1155
BC62737174	BC62812175	BC63-622138	BC63-880140	BC66-250141	BC70-520147	H0434178	ICKD14G2155
BC62738174	BC62813175	BC63-624138	BC63-882140	BC66-252141	BC70-524147	H0438178	ICKD14G3155
BC62739174	BC62814175	BC63-625138	BC63-884140	BC66-254141	BC70-528147	H0500178	ICKD14G4155
BC62740174	BC62815175	BC63-626138	BC63-886140	BC66-256141	BC70-532147	H0512178	ICKD14.3G155
BC62741174	BC62816175	BC63-630138	BC63-888140	BC66-258141	BC70522192	H0600178	ICKD14HM155
BC62742174	BC62817175	BC63-634138	BC63-890140	BC66-260141	BC70523192	H1056178	ICKD15H155
BC62743174	BC62818175	BC63-700138	BC63-892140	BC66-306141	BC70524192	H1116178	ICKD20G155
BC62744174	BC62819175	BC63-701138	BC63-894140	BC66-308141	BC90-002152	H1136178	T8152
BC62745174	BC62820175	BC63-710138	BC63-896140	BC66-314141	BC90-004152	ICK7.5G153	T15152
BC62746174	BC62821175	BC63-711138	BC63-898140	BC66-320141	BC90-006152	ICK9.6G153	T20152
BC62747174	BC62822175	BC63-712138	BC63-899140	BC66-326141	BC90-008152	ICK10.5G153	
BC62748174	BC62823175	BC63-713138	BC63-902140	BC66-356141	BC90-052152	ICK11G153	
BC62749174	BC62824175	BC63-715138	BC63-904140	BC66-358141	BC90-102152	ICK13G153	
BC62750174	BC62825176	BC63-716138	BC63-906140	BC66-364141	BC90-104152	ICK15G153	
BC62751174	BC62826176	BC63-717138	BC63-908140	BC66-370141	Diplug199	ICK15.7G153	
BC62752174	BC62827176	BC63-718138	BC63-910140	BC66-376141	DR1179	ICK17G153	
BC62753174	BC62828176	BC63-719138	BC63-912140	BC67-080144	DR12179	ICK18G153	
BC62754174	BC62829176	BC63-720138	BC63-914140	BC67-082144	DR1CT179	ICK19G153	
BC62755174	BC62830176	BC63-724138	BC63-916140	BC67-084144	DRP1179	ICK20E153	
BC62756174	BC62831176	BC63-725138	BC63-918140	BC67-090144	DRP2179	ICK20G153	
BC62757174	BC62832176	BC63-726138	BC63-920140	BC67-091144	EJE179	ICK20HM153	
BC62758174	BC62833176	BC63-733138	BC63-922140	BC67-092144	EXT1179	ICK20P153	
BC62759174	BC62834176	BC63-750139	BC63-924140	BC67-093144	EXT2179	ICK20SM153	
BC62760174	BC62835176	BC63-751139	BC63-926140	BC67-094144	GBC12G155	ICK20X153	
BC62761174	BC62836176	BC63-760139	BC63-928140	BC67-095144	GBC20G1155	ICK30E153	
BC62762174	BC62837176	BC63-761139	BC63-930140	BC67-120144	GBC20G2155	ICK30G153	
BC62763174	BC62838176	BC63-762139	BC63-932140	BC67-122144	GBC25G155	ICK30HM153	
BC62764174	BC62839176	BC63-763139	BC63-934140	BC67-124144	GBC30G155	ICK30P153	
BC62765174	BC62840176	BC63-766139	BC63-936140	BC67-160144	GBC50G155	ICK30SM153	
BC62766174	BC62841176	BC63-767139	BC63-938140	BC67-162144	GF12G155	ICK30X153	
BC62767174	BC62842176	BC63-768139	BC63-940140	BC67-164144	GF20G155	ICK40G153	
BC62768174	BC62843176	BC63-769139	BC63-942140	BC67-205144	GF40G155	ICK40HM153	
BC62769174	BC62871177	BC63-774139	BC63-944140	BC67-206144	GF50G155	ICK40SM153	
BC62770174	BC62872177	BC63-775139	BC63-946140	BC67-211144	H0016178	ICK50E153	
BC62771174	BC62873177	BC63-776139	BC63-948140	BC67-212144	H0034178	ICK50G153	

